

MIDWEST ENVIRONMENTAL **MANAGEMENT COMPANY**

123 North 4th Street • Suite 202 • La Crosse, Wisconsin 54601 Phone: (608) 784-5688 • FAX: (608) 784-7350


Date: 3-13-07	Time: 1425 No. of Pages: (including this cover)
<u>To</u> :	
Company Name: _	WDNR
Attention/Dept:	DOUG JOSEPH
FAX Number: _	715-839-6076
From:	SCOTT JENSEN
, , , , , , , , , , , , , , , , , , ,	Midwest Environmental Management Company
Comments: _	REQUESTED DOCS
_	FOR JOLIVETTE CLEANERS
·	FRENCH ISCAND, LAX.

The information contained in this facsimile material is CONFIDENTIAL and is intended ONLY FOR THE RECIPIENT named above.

If you have received this material in error, please contact us immediately.

Thank you!

[•] Industrial Hygiene Services • Indoor Air Quality Investigations • Asbestos, Lead Inspection, Monitoring • • Environmental Site Assessments • Environmental Engineering •




Midwest Environmental Management Company

MEMCO

SITE ASSESSMENT **FOR UNDERGROUND STORAGE TANKS**

Jolivette Cleaners & Laundry 1645 Caroline Street La Crosse, Wisconsin

January 13, 1995



SITE ASSESSMENT FOR

UNDERGROUND STORAGE TANKS


Jolivette Cleaners & Laundry 1645 Caroline Street La Crosse, Wisconsin

Project Number TK94474 January 13, 1995

Prepared By:

Midwest Environmental Management Company 123 North 4th Street, Suite 304 La Crosse, Wisconsin 54601 (608) 784-5688

Dean Ellefson
Environmental Technician
DILHR Certification #05705



300 Gallon Stoddard Solvent Tank

SAMPLE	FIELD Analysis	LABORATORY ANALYSIS	
LOCATION	Sample Description	FID Response	Gasoline Range Organics (minimum detection limit: 2.0 ppm)
001 1' Below Center of 300 Gallon Solvent Tank 7' BGL	Sand: medium grained, subrounded to subangular, moderately sorted. No noticeable hydrocarbon odor. No visible hydrocarbon staining. Munsell: 10YR-3/4. USCS: SP.	1.4	None Detected



Jolivette Cleaners & Laundry 1645 Caroline Street La Crosse, Wisconsin

SOIL SAMPLE DATA TABLE 300 Gallon Stoddard Solvent Tank

Project Number: TK94474 Date: 12-19-94 Prepared By: DE



January 13, 1995

Tank Response Unit - SW/3 DNR P.O. Box 7921 Madison, Wisconsin 53707



Subject: Site Assessment for the Jolivette Cleaners & Laundry property.

To whom it may concern:

Enclosed please find one copy of Midwest Environmental Management Company's site assessment report for the Jolivette Cleaners & Laundry property located at 1645 Caroline Street, La Crosse, Wisconsin for your records. This site involved the removal of one 300 gallon Stoddard Solvent underground storage tank from the above mentioned address on December 7, 1994. A late site assessment was performed on December 12, 1994.

Midwest Environmental did not encounter indications of hydrocarbon contamination at this tank site. Laboratory analysis of samples collected from the required sampling locations confirmed that there was no detectable concentrations of Gasoline Range Organic contamination in the samples collected at this site. Midwest Environmental is therefore recommending this site for closure.

If you should have any questions or require further information please feel free to contact us at your convenience.

Sincerely,


Dean Ellefson

Environmental Technician

enclosure: Site Assessment Report



Midwest Environmental Management Company



Laclosse - WI

SITE ASSESSMENT FOR UNDERGROUND STORAGE TANKS

Jolivette Cleaners & Laundry 1645 Caroline Street La Crosse, Wisconsin

January 13, 1995





SITE ASSESSMENT

FOR

Underground Storage Tanks

Jolivette Cleaners & Laundry 1645 Caroline Street La Crosse, Wisconsin

Project Number TK94474 January 13, 1995

Prepared By:

Midwest Environmental Management Company 123 North 4th Street, Suite 304 La Crosse, Wisconsin 54601 (608) 784-5688

Dean Ellefson
Environmental Technician
DILHR Certification #05705

1.0 INTRODUCTION

This <u>late underground</u> storage tank site assessment was performed on December 12, 1994 at the Jolivette Cleaners and Laundry property located at 1645 Caroline Street in the City of La Crosse, La Crosse County, Wisconsin after the removal of one (1) 300 gallon Stoddard Solvent underground storage tank and the backfilling of the tank removal excavation. The tank system was reported by the excavation contractor, Swanson Construction Incorporated, to have been removed on December 7, 1994.

The Certified Site Assessor for this project was Dean R. Ellefson, Department of Industry, Labor and Human Relations Certification #05705, Midwest Environmental Management Company, 123 North 4th Street - Suite 304, La Crosse, Wisconsin 54601, telephone number (608) 784-5688.

1.1 Site Information

Location

The property which is the subject of this site assessment report was located in the southeast quarter of the northwest quarter of Section 19, Township 16 North, Range 7 West. The location of the property is represented on Figure 1, the "Site Location Map".

<u>Underground Storage Tank and Property Owner</u>

The owner of the underground storage tank, and the property on which it was located, was the Jolivette Cleaners and Laundry, 1645 Caroline Street, La Crosse, Wisconsin 54603, telephone number (608) 784-1599, represented by Ms. Almina Heisz.

Past and Present Property Use

The property is currently and has been in use by the Jolivette Cleaners and Laundry since 1951. The 300 gallon 142 Solvent 66/3 was reported by Ms. Heisz to have been installed at the Jolivette Cleaners and Laundry facility in 1979.

Site Conditions

According to information made available to Midwest Environmental Management Company, there are no Leaking Underground Storage Tank (LUST) sites or gas stations located on neighboring properties at this time.

The surficial layer of soil located on this site is generally composed of fine to medium grained sand. Based upon the USGS La Crescent, Minnesota topographic map, the groundwater depth at this site is estimated to be approximately 20 feet below the ground surface.

Weather Conditions

The weather conditions during the site assessment investigation were sunny skies with temperatures ranging from 20 to 25 degrees Fahrenheit. No precipitation occurred on the day of sample collection (December 12) or on the day prior to sample collection (December 11). Midwest Environmental Management Company was not able to determine whether precipitation had occurred on the day of the actual tank removal (December 7) or on the day prior to the tank removal (December 6).

1.2 Tank Information

The tank removed from this property consisted of one (1) 300 gallon Stoddard Solvent underground storage tank (UST) and associated vent pipe. According to the Material Safety Data Sheet made available to Midwest Environmental Management Company this solvent consisted of Unocal 142 Solvent 66/3.

The 300 gallon Stoddard Solvent UST was reported by Mr. Paul Rogge of Swanson Construction to have been buried approximately 2 feet below ground level. Ms. Almina Heisz, owner of the Jolivette Cleaners and Laundry, reported that the tank was used to store a cleaning solvent used by the Jolivette Cleaners and Laundry facility. The tank was located beneath an unpaved and nonvegetated area approximately 13 feet north and 23 feet east of the northwest corner of the Jolivette Cleaners and Laundry building located at 1645 Caroline Street, La Crosse, Wisconsin. This site is represented on Figure 2, the "Site Layout Map".

300 Gallon 142 Solvent 66/3 Tank

The 300 gallon Stoddard Solvent underground storage tank was oriented from east to west at this site. Midwest Environmental Management Company was not present during the tank removal on December 7 and was therefore not able to observe the condition of the tank or piping.

The fill pipe was reported by the excavation contractor to have been located at the west end of the tank and to have extended upward to approximately 2 feet above ground level.

The vent pipe for the 300 gallon Stoddard Solvent tank was reported to have been located in the center of the tank. The vent pipe was reported to extend south approximately 13 feet to a point adjacent to the north wall of the building, at a point approximately 22 feet east of the northwest corner of the building. At this point a vertical section of pipe extended upward to approximately 6 feet above ground level.

The supply piping was reported to have been removed in 1989 at the time the tank was taken out of service. No supply piping was reported to be present at the time of the tank removal on December 7, 1994.

Tank History

The 300 gallon Stoddard Solvent tank was reported to have been installed at this location in 1979. Information was not available to Midwest Environmental Management Company concerning the actual date of installation. The tank was reported to have been utilized for storing cleaning solvent for use by the Jolivette Cleaners and Laundry facility. The tank was reportedly taken out of service in 1989 at which time the tank was reportedly pumped out and the supply piping removed.

Previous Tank Removals

Midwest Environmental Management Company did not receive information regarding any underground storage tanks which may have been removed from this site in the past.

Tanks Remaining On Site

Midwest Environmental Management Company observed one Aboveground Storage Tank (AST) remaining on site. This is estimated to be a 265 gallon AST which contains Stoddard Solvent for use by the Jolivette Cleaners and Laundry. The AST is currently located adjacent to the north wall of the building, approximately 24 feet east of the northwest corner of the building.

South of the state of the state

Previous Site Investigations and Tank Tightness Tests

Midwest Environmental Management Company did not receive information regarding any investigation conducted in the past. Records documenting the results of a tank tightness test, if one was performed at this site, were not made available to Midwest Environmental Management Company.

2.0 TANK REMOVAL AND CLEANING

2.1 Service Providers

Excavation Contractor

The excavation contractor for this tank removal operation was Swanson Construction Incorporated, 1238 Clinton Street, La Crosse, Wisconsin, 54603, telephone number (608) 784-2601.

Certified Remover/Cleaner

The certified remover/cleaner for this project was Paul Rogge, DILHR certification #05919, Swanson Construction Incorporated, 1238 Clinton Street, La Crosse, Wisconsin, 54603, telephone number (608) 784-2601.

Waste Hauler

The waste hauler for this project was Bill's Pumping Service Incorporated, 106 East Clinton Street, La Crosse, Wisconsin, 54601, telephone number (608) 782-7633.

Tank Destruction

Tank destruction services were to be provided by Alter Scrap Possessing, 2850 Hemstock Drive, La Crosse, Wisconsin, 54601, (608) 783-8201. The removed tank was reportedly transported by trailer to the Alter Scrap Possessing facility in La Crosse, Wisconsin by Swanson Construction, Inc. The tank was to be cut for scrap and the material recycled.

2.2 Tank Removal Activities

Excavation

The opening of the excavation began on December 7, 1994. Midwest Environmental Management Company was not was not made aware of what time the excavation was opened, or what time the tank was removed from the excavation.

Purging

The tank was reportedly purged prior to removal using dry ice. Greg Bauer of Central Wisconsin Inspection Service, Inc., 2312 D Crestview Drive, Suite 229, Hudson, Wisconsin 54016, telephone number (715) 381-5602, was on site as the local Department of Industry, Labor and Human Relations (DILHR) representative.

Removal

The 300 gallon Stoddard Solvent tank and vent piping were reportedly removed from the excavation by Swanson Construction.

Tank Cleaning

The tank was reported to have had the remaining product pumped out at the time the tank was taken out of service in 1989. The supply piping was also reportedly removed at that time. Apparently the opening in the tank was not plugged and consequently approximately 100 gallons of water had accumulated in the tank. Bill's Pumping Service reportedly pumped out the tank on the day of the tank removal prior to removal. After the tank was purged with dry ice and removed from the excavation, the tank was reportedly cleaned by the certified remover using floordry material. Approximately 10 gallons of tank sludge were recovered from the tank and reportedly disposed of with the water from inside the tank by Bill's Pumping Service.

Excavation Backfilling

The excavation was backfilled with the original excavated material. No additional fill material was required. The remaining depression was reportedly filled with material generated by evening out surficial irregularities in the area immediately surrounding the tank excavation.

3.0 VISUAL INSPECTION

3.1 300 Gallon 142 Solvent 66/3 Tank

The 300 gallon Stoddard Solvent tank was estimated by the certified remover to be approximately 5 feet in length and 3.5 feet in diameter. The tank and associated system piping were constructed of single wall bare steel. The tank was not overfill protected and no spill containment was present. Midwest Environmental Management Company was not present to observe the removed tank and piping and was not able to make a determination concerning their condition.

3.2 Excavation Inspection

The tank excavation was not observed directly by Midwest Environmental Management Company. Based upon soil samples collected from hand auger borings conducted during the late site assessment on December 12, 1994, Midwest Environmental Management Company was able to determine that the area of excavation contained predominantly medium grained sand. Groundwater was not encountered during the hand auger borings.

The hand auger soil sample collected from this tank site was found to exhibit no obvious indications of hydrocarbon contamination. The sample was collected from beneath the middle of the removed tank and displayed no noticeable hydrocarbon odors and no visible hydrocarbon staining.

4.0 SOIL SAMPLE ANALYSIS PROCEDURES

4.1 Hand Auger Boring Procedures

Hand Auger Equipment

The boreholes at this tank site were advanced utilizing a hand-operated bucket auger. The auger bucket consisted of a 1.5 inch inside-diameter, 5.5 inch long stainless steel cylinder which contained two stainless steel auger teeth. The auger bucket was mounted with a pin attachment to a 7/8 inch outside diameter, 4 foot in length solid steel shaft section which in turn contained a pin for the mounting of a steel T-handle.

Hand Auger Borings

The T-handle and auger bucket were attached to the auger shaft and the borehole was advanced by clockwise manual rotation of the auger assembly which caused the auger teeth to advance the auger bucket into the soil. The auger bucket was withdrawn from the borehole at intervals of 6 inches and the accumulated soil was removed. No lubricants were used on any part of the auger apparatus.

Equipment Decontamination

Upon reaching sample collection depth, the auger bucket was decontaminated by scrubbing with a solution of Alconox® laboratory detergent and rinsing with potable water. The auger was then advanced down the borehole for an additional 6 inches and a soil sample was brought to the surface for preservation and analysis.

Borehole Abandonment

Upon completion of the hand auger boring activity, each borehole was abandoned in accordance with Wisconsin Department of Natural Resources NR 141 requirements in order to prevent contaminant migration within the borehole. Each hole was abandoned utilizing "Enviroplug" bentonite granules as the borehole abandonment material.

4.2 Field Analysis

Field Sample Collection

A portion of each soil sample was collected using disposable latex gloves and was placed into a clean pint-size glass canning jar for field screening headspace analysis. Each jar was filled to approximately one-half capacity with soil and the mouth of the jar was covered with a double layer of aluminum foil. The lid ring was then screwed on over the foil and the sample was shaken to disaggregate the soil. The sample was then allowed to warm to a temperature of 70° Fahrenheit or warmer and to degas for a minimum of 45 minutes. The glass jars were decontaminated after each use by scrubbing with a solution of Alconox laboratory cleaner and were then rinsed with potable water. The sample collector's gloves were disposed of after the collection of each sample.

Field Screening Analysis

A flame ionization detector was utilized to detect the presence of volatile and semivolatile organic compounds in the soil vapor of the samples collected from this tank site. The flame ionization detector utilized for this project was a Foxboro® "Century" Model 128 Organic Vapor Analyzer.

The instrument was calibrated before use with commercially prepared calibration gas standards. For calibration, the instrument was first placed in normal operation and allowed a twenty minute warm-up and stabilization period. The zero baseline of the instrument was then established with the use of a commercially prepared zero air calibration gas which contained a total hydrocarbon content of less than 1 part per million. A commercially prepared 95 parts per million methane-in-air gas standard was then utilized to calibrate the instrument. The calibration gases were withdrawn from the gas cylinders into a collapsed mylar air sample bag and were then introduced into the instrument utilizing the instrument's own pump. The instrument was then calibrated in all three sensitivity settings and adjusted as necessary to meet manufacturer's specifications.

For sample analysis, the flame ionization detector was placed into operating mode and allowed a twenty minute warm-up and stabilization period. The detector apparatus was then checked for system leaks and adjusted as necessary. The probe extension of the flame ionization detector was then introduced through the foil covering into the headspace of the field sample jar, and the highest stable reading within ten to twenty seconds was recorded.

Geological Analysis

The remaining portion of each soil sample was described and logged in the field. Information was recorded regarding soil type and composition, grain size, shape, sorting, and sample odor and staining. The samples were also classified in accordance with the United Soil Classification System and matched with Munsell Soil Color Charts. Soil sample information was also recorded concerning the time, date, location and depth for each sample collected.

4.3 Laboratory Analysis

Sample Collection Procedures

Upon the completion of the excavation activity, soil samples were collected for laboratory analysis. For Gasoline Range Organics (GRO) soil samples to be submitted for laboratory analysis, 25 gram portions of soil were immediately placed into duplicate 60 milliliter glass laboratory jars and preserved with 25 milliliters of laboratory-provided trap grade methanol, and capped with teflonlined screw-on lids. After collection, the sample jars were weighed with an a Acculab Pocket Pro 150-B portable electronic scale to ensure proper sample weight. The sample collector wore new disposable latex gloves which were disposed of after the collection of each sample.

Each sample jar was labeled as to sample number, location, sample depth, time, date, and sample collector. The samples were then cooled to 4° Celsius with ice, stored in an insulated shipping container and transported by United Parcel Service to a certified laboratory for analysis. A laboratory-supplied chain of custody document was completed, signed, and enclosed with the shipping container.

Certified Laboratory

The provider of laboratory analysis services for this project was Northern Lake Service, Inc., 400 North Lake Avenue, Crandon, Wisconsin, 54520. Northern Lake Service is a Wisconsin Department of Natural Resources-certified soil analysis laboratory, holding Laboratory Certification Number 721026460.

<u>Laboratory</u> Analysis

The soil sample collected during the site assessment was delivered with chain-of-custody documentation to Northern Lake Service for analysis on December 13, 1994. Based upon the nature of the contents of the tank at this site, analysis for Wisconsin Modified Method Gasoline Range Organics (GRO) was requested for the sample collected in association with the 300 gallon Stoddard Solvent tank. The minimum detection limit for Wisconsin Modified Gasoline Range Organics at this laboratory is 2.0 parts per million (ppm).

5.0 SAMPLE ANALYSIS RESULTS

Midwest Environmental Management Company collected one soil sample from this tank site. The location of this sample is depicted on Figure 2, the "Site Layout Map". The results of the field and laboratory analysis for the soil sample collected from this site are represented on the "Soil Sample Data Table" included with this report.

Sample 001 - Center of 300 Gallon Stoddard Solvent Tank

Sample Location

Soil sample #001 was collected from native soil approximately 1 foot beneath the base of the center of the 300 gallon Stoddard Solvent tank. The sample was collected from 7 feet below ground level and was subjected to laboratory and field analysis.

Field Analysis

This sample was composed of dark yellowish brown predominantly medium grain sand. The sand was subrounded to subangular in grain shape and moderately sorted. The Munsell soil color classification was determined to be 10YR-3/4. The United Soil Classification System (USCS) soil classification was determined to be poorly graded sand (USCS group symbol: SP). This sample was found to contain no noticeable hydrocarbon odors and no visible hydrocarbon staining. Headspace analysis of this sample with the flame ionization detector (FID) yielded a response of 1.4 instrument units.

Laboratory Analysis

This sample was analyzed in the laboratory and was determined to contain no detectable concentrations of GRO.

6.0 SITE ASSESSMENT SUMMARY

One (1) 300 gallon Stoddard Solvent underground storage tank and associated vent piping were removed from the Jolivette Cleaners and Laundry property on December 7, 1994. According to the Material Safety Data Sheet made available to Midwest Environmental Management Company this solvent consisted of Unocal 142 Solvent 66/3. A late site assessment was performed at this tank site by Midwest Environmental Management Company on December 12, 1994. The necessary soil sample was collected from the filled in excavation with a stainless steel hand auger, following WDNR guidelines.

Field Analysis

The soil sample collected from beneath the center of the 300 gallon Stoddard Solvent tank was found to contain no noticeable hydrocarbon odors and no visible hydrocarbon staining. Headspace analysis of this sample with the flame ionization detector yielded a response of 1.4 instrument units.

Laboratory Results


Certified laboratory analysis of the soil sample collected from the tank site resulted in no detectable concentrations of Gasoline Range Organics contamination for the sample collected from beneath the center of the 300 gallon Stoddard Solvent tank.


Recommendation

Based upon the laboratory analysis results which indicated that the soil sample collected from this tank site was found to contain no detectable concentrations of Gasoline Range Organics, Midwest Environmental Management Company is recommending this site for closure.



FIGURES & TABLES





300 Gallon Stoddard Solvent Tank

SAMPLE LOCATION	FIELD ANALYSIS	LABORATORY ANALYSIS	
	Sample Description	FID Response	Gasoline Range Organics (minimum detection limit: 2.0 ppm)
001 1' Below Center of 300 Gallon Solvent Tank 7' BGL	Sand: medium grained, subrounded to subangular, moderately sorted. No noticeable hydrocarbon odor. No visible hydrocarbon staining. Munsell: 10YR-3/4. USCS: SP.	1.4	None Detected



Jolivette Cleaners & Laundry 1645 Caroline Street La Crosse, Wisconsin

SOIL SAMPLE DATA TABLE 300 Gallon Stoddard Solvent Tank

Project Number: TK94474 Date: 12-19-94 Prepared By: DE



LABORATORY REPORT

NORTHERN LAKE SERVICE, INC.

WIS. LAB CERT. NO. 721026460

Analytical Laboratory and Environmental Services 400 North Lake Avenue - Crandon, WI 54520

Ph:(715)478-2777 Fax:(715)478-3060

ANALYTICAL REPORT

Page: 1

Client:

Midwest Environmental Mgt. Co.

123 North 4th St.,

Suite 303

La Crosse, WI 54601

Attn: Jason Herbst

NLS Project 12858

Client Project: Jolivette Cleaners

Client Sample ID: Soil,001 7' BGL

NLS Sample Number: 70140

Ref. Line 1 of COC 10982 Description: Soil,001 7' BGL

Reported: 12/15/94 Received: 12/13/94 Collected: 12/12/94

Date Performed Parameter Result Solids, total on solids 95.3 % 12/13/94 GRO (soil) < 2.0 mg/Kg12/13/94

Additional Comments: spike-102%, spike-dup-102%

Organics Extraction (GRO) 12/13/94

Client Sample ID: Trip Blank

NLS Sample Number: 70141

COC Description: Trip Blank (meth)

Collected: 12/12/94 Received: 12/13/94 Reported: 12/15/94

Parameter Result GRO (soil) < 2.0 mg/Kg

Additional Comments: spike-102%, spike-dup-102%

Laboratory Director

Date Performed

12/13/94



NORTHERN LAKE SERVICE, INC.

Analytical Laboratory and Environmental Services

400 North Lake Avenue • Crandon, WI 54520 Tel: (715) 478-2777 • Fax: (715) 478-3060

SAMPLE COLLECTION AND CHAIN OF CUSTODY RECORD

Wisconsin Lab Cert. No. 721026460

RET	URN THIS FORM	M WITH SAM	IPLES.												
1 1	IENT				***************************************		OJECT TITLE					_			
1	DRESS	ENVIK	INMIFICTAL	MISNA	GOBING C	٥	PROJECT NO. P.O. NO.								
123 N 1/11 51 Scotte 30						PR	OJECI NO.					P.O. N	Ю.		
							NTACT					PHON			
	COCIRUS	Sc	cul		27601	J.	250N	Her	2135)		16	(8)	784-568	8
ITE	M (ILE LAB NO		SAMPLE ID	DATE	LLECTION	SAMPLE TYPE	GRAB/ COMP.	Plus	NIAIN	Tiso)	SERVAT	IVE	С	OLLECTION REMARKS	
_ 1	1	i	7/BSL	17-17-	811 110-45	50/L	6183	1	7	11.1001					
2	1		DRIP BC		17 70.73	1. ,0,0			/						
3	1011		1/5/14 116	. WUIZ			<u> </u>								
4													<u> </u>		
1-		_				<u> </u>] ' [<u> </u>			
5		ļ										<u> </u>			
6	_														
7							<u> </u>								
8															
9															
10												<u> </u>			
11												<u> </u>			
12															
SAN	 PLE TYPE:						<u> </u>	CONTA	I NNER	l	PRES	SERVAT	VES & P	REPARATION	
	SW = surfa WW = was		DW = drinking : TIS = tissue	water	PROD = product SOIL = soil			P = plastic NP = nothing added OH = sodium hyd			OH = sodium hydroxid HA = hydrochloric &	e			
	GW = grou	ındwater	AIR = air		SED = sediment			V = glas B = pla	ss vial	.	N = n	nitric acid	d	ascorbic acid H = hydrochloric acid	
	describe	others						l	ihe othe					F = field filtered	
CO	_LECTED BY (sig	ınatures)						CL	JSTOD	Y SEAL	NO. (IF	ANY)	DATE/I	IME	
	Den	1/1/										2-12	- 91/	ISON pur	
REL	INQUISHED BY	(signature)	There is		RECEIVED B	Y (signature)							DATE/	IME '	
REI	INQUISHED BY	(signature)			RECEIVED B	Y (signature)					-		DATE/T	IME	
DIS	PATCHED BY (si	ignature)			METHOD OF	TRANSPORT	Г						DATE/I	IME	
								l							
RECEIVED AT NLS BY (signature) DATE/TIME 13 13 94					v.J	12:30	CONE	DITION					TEMP.	115/3	
SEAL # REMARKS & OTHER INFORMATION															
	YES "	NO													
	Jano C	1	word los	1, 4	35.										
VIII.	итали ⁴ . то і	MEET REGUL	ATORY REQUIREME	NTS, THIS F	ORM MUST BE C	COMPLETED	N DETAIL AND	INCLU	DED IN	THE SH	IIPPER	CONTA	ININGT	HE SAMPLES DESCRI	BED.
			IE LINE PER SAMPLÉ. ORM WITH SAMPLES			OPY.									
	_ .													UPLICATE COPY	

NORTHERN LAKE SERVICE, INC.

CRANDON, WI 54520 (715)478-2777

RESULTS ORDERED BY:

ORDER OF ANALYSIS

CHAIN OF CUSTODY RECORD NUMBER:

Midwest Environmental Management Company			QUOTATION NUMBER:				
Indwest Environ	mentar management	Company					
	Street - Suite 304		94068				
La Crosse, WI	54601	!	ANALYZE FOR DISSOLVED OR TOTAL PARAMETERS?				
:		1	Minus on	TOR BIBOUVED FOR TOTAL PARAMETERS?			
SEND RESULTS TO:			SEND INV	OICE TO:			
123 North 4th S	mental Management Street - Suite 304	Company	123 N	ST ENVIRONMENTAL MANAGEMENT CON 144 ST. SUITE 304			
La Crosse, WI	24601		e CPO	155E, WI 54601			
1							
Note "L" for low	level ICP analysi	s, and " <u>F</u> "	for fur:	nace analysis.			
Samples on line #s	:	to 1	e analyz	ed for the parameters checked below:			
Alkalinity, total Alkalinity, bicaro. Aluminum	Cyanide, total Amenable Elworide	Phenols Phosphorus Totarea	•	Acid Extractables by 625/8270 gase/Neutral Extractables by 625/8270 BNAs by 625/8270			
Ancimony	☐ Haroness	Dis. res		Chlorinated Hydrocarbons by 612			
☐ Arsenic	☐ lron	2 Potassium		☐ Haloethers by 511			
🗒 Barium	Lead	Selenium 🔲		☐ Nitrosamines by 507			
⊒i 3eryllium	Hagnesium	Silica		Pesticides-Organochlorine by 608/8080			
_ 3.0.05	Hanganese	Silver		Pesticides-Organochoschate by 8141			
Boron	Hercury	Socium		PC3s by 608/8080			
Cadmium	Molyoperum	O Solids, to		Phenols by SC 564/8040			
Calcium	☐ Nickel	iot. dis		Phenoxy Acid Herbicides by 8150			
Chloride	☐ Mitrogen, total ☐ Ammonia	☐ Sulface	penoed	TCLP-metals TCLP-VOCs TCLP-SNAs			
7 Chromium	☐ Nitrate	☐ Sulfide		70Cs by EPA 601+602 or 3010+8020			
Chromium, hexavalent	Nitrite	Surfactant	< (NRAS)	TO STY EPA 8021			
! Copalt	Nitrate - Mitrite	Thallium	2 (UON3)	-by EPA 624/8240/8260			
Colifor to al	Total Kjeldahl	F in		by EPA 524.2 (SOUA)			
	Total Organic	T.o.c.	•	STEX 57 8020			
Calor Caroustivity	Oil & Grease	☐ Turbidity		PVOCs by 8020			
☐ Coccer	∏ pH	☐ Varusoium	£	GRO-PVOCS			
<u> </u>		☐ Zinc		ORO-VI Nogified			
		☐ Hunic.Slud	ge, WI List	PAHS by 510LC/8310			
Samples on line #s	Cyanide, cotal	to	be analy	zed for the parameters checked below:			
Alkalinity, bicarb.	() Amenaiole	Phosphorus	roral	Base/Heutral Extractables by 625/8270			
Aluminum	Fluoride	Tot. read		BhAs by 625/8270			
Antimony	Haroness	Ois. read		Chlorinated Hydrocarbons by 612			
Acsenic	Iron	Potassium		Haloethers by 611			
☐ Barium	Leed	C Selenium		☐ Nitrosamines by 607			
☐ Beryllium	☐ Hagnesium	☐ Silica		Pesticioes-Organochlorine by 608/8080			
☐ 8.0.0.·5	∐ Hanganese :	∐ Silver		Pesticides-Organophosphate by 8141			
Boron	☐ Hercary	Sodium	- •	PC9s by 608/8080			
Cacmium Calcium	Holyotenun	Solids, to		Phenols by GC 604/8040 Phenoxy Acid Herpicides by 8150			
Calcium C.o.o.	☐ Nickel	Tot. dis:		TCLP-metals TCLP-vocs TCLP-SHAS			
Chloride	Hitrogen, total	Sulfate	ZEI NES	TCLP-pesticides/herbicides			
Chromium	Hitrate	Sulfide		VOCS by EPA 601+602 or 8010+8020			
Chromium hexavaleur	☐ Nitrite	Surfactants	(XBAS)	-by EPA 8021			
Cobalt Caliform, fecal	☐ Nitrate - Nitrite	☐ Thallium	•	-by EPA 624/8240/8250			
Caliform, fecal	☐ Total Kjeldanl	🔲 Tin		-by EPA 524.2 (SDWA)			
Color Color	Total Organic	🔲 r.a.c.		☐ 8TEX by 8020			
Conductivity	Oil & Grease	Turbidity		PVOCs by 8020			
H Cacer	H PH	Variacium Zine		GRO-VI Modified			
법 <u></u>	H	Hunic.Slug	se.Willist	ORO-UL Modified PAHS DV 610LC/8310			
			, . ,				
CHEATAL THOMBUCHTO	11C.						



Wisconsin Department of Industry, Labor and Human Relations

Complete one form for each site closure:

CHECKLIST FOR UNDERGROUND TANK CLOSURE

The information you provide may be used by other government agency programs [Privacy Law, s. 15.04.(1) (m)].

RETURN COMPLETED CHECKUST TO: Safety & Buildings Division Fire Prevention & Underground Storage Tank Section P. O. Box 7969, Madison, Whishard,

						1. 127 01.1.	- Community
A. IDENTIFICATION: (P) 1. Site Name	lease Print)	Indicate whether	r closure is for: [[] 2. Owner Ni		Tank On	ly Piping On	ly
Site Street Address (not P.O.	Cleans	• 1 <	Alm	raia H	F-5-		
			Owner Stree		3		
	lage egal	Town at:		Box 77	oh State	Zip Code	,
		CAMPALL		China	Rell W	54602	=723
State	Zip Code	County	County	1 :	ora No. (includa 18) 784	area cooe)	-
3. Closure Company Name (\$4603 (Print)	1 An (egg	sure Company Street A		18 1 184	1-7517	Maritanna .
Swanton Ca	ust			Ica St			
Closure Company Telephone (608) 784-76		· · · · · · · · · · · · · · · · · · ·	sure Company City, Sta		663	Francisco Francisco	. ;
4 Name of Company Perform	ning Closure Asse	ssment As	sessment Company Stre				
		D to				· · · · · · · · · · · · · · · · · · ·	1.
Telephone # (include area c	ode) Certified Ass	sessor Name (Print)	A358560	r Signatura		Assessor Certification N	10.
Tank ID #	Closure	Temp. Closure	Closure in Place	Tank Capacity	Contents 2	Closure Assessm	ent
1	DX.	-		300	13	VI DYI OA	
3				300	13.	DY ON	
2.	- <u> - - - - - - - - - - - - - </u>	n	П			J DY DN	
4. And the manufacture of the second of the						DY DN	
<u> </u>		П	П	K.—.—himme		DY DN	· ;;;
6		n	n			NO YO	
* Indicate which product by 11-Weste oil; 13-Chemic	numeric code:	01-Diese; 02-Les	ided: 03-Unleaded: 0	A-Fuel Oil: 05-Gas	ohol; 08-Other		mlx;
11-Waste oll; 13-Chemic	al (Indicate the	chemical name(3)	or numbers(s) _5/	ulat		4-Kerosene: 15-Aviati	01.
Written notification was pro	ocledit of ploc	al agent 15 days in	advance of closure.	date.	و درو درو درو درو ودرو درو درو درو		NA .
البالاختلاق والمنتيات فيداها فيدائه التناقية فيناسيها					_		NA .
Check applicable box a B. TEMPORARILY QUI	it right in resi I OF SERVIC	ponse to all stat	ements in Section	15 & - E.		nover inspector intied	NA
Written inspector appro	val of temporar	y closike obtained	, which				N
is affective until (provid 1. Product Removed	(e) (a) (a)					/	LA
a. Froduct lines dra	ined into tank (d	or other container)					ď
 Ali product remove Ali product remove 			\		=		H
2. Fill pipe, gauge pipe	, tank truck vap	or recovery fittings	s, and vapor return lin	nes cappad	🗖 '	Y DN D	
All product lines at t Dispensers/pumps le	he islands or pu eft in place but	urnps located elsev locked and nower	vhere are removed as disconnected	nd capped, OR	DY		H
5. Vent lines left open, 6. Inventory forth filed						/ Д и	己
5. Inventory forth filed	indicating temp	orary closure." :	11	2015 NO 40 BOOK	a Kada a J	AND MICHE CONTRACT	t)L
C. CLOSURE BY REM	``				,		_
 Product from piping Piping disconnected 							
3. All liquid and residue	e removed from	tank using explos	ion proof pumps or h	and pumps	🗔 \	/ 🔲 N · · · 🔘	
4 All pump motors and	tavolion hoses	bonded to tank or	atherwise grounded.		起始起。 黑		
NOTE: DROP TUB	E SHOULD NO	T BE REMOVED I	THE TANK IS TO	DE PURGED THRO	DOGH CONTRACT	4 El 14 . Br	u
6. Vent lines left conne		a nurned			ים	r on o	n
7. Tank openings temp	orarily plugged	I so vapors exit thro	ough vent		💽 \		ğ
O Tool, elmandare	A 1 (- 1 / 0)	-4 44- 1	-bio 41 C1 \	- ON F	<i>~</i> 1	Y DN D	
a. Tank amosphere re Innihit Tankirampyad Innihit to prevent moyemer					, <u></u>		ם"
10) Tank cleaned before					<u> </u>	Y 🗆 N 🔛	

	變者		1111.0000.12		A Jan
Ψ1	Ċ.	CLOSURE BY REMOVAL (continued)	Verified	Verified	MALACE
		1. Tank labeled in 2" high letters after removal but before being moved from site	NOA		
	4	NOTE: COMPLETE TANK LABELING SHOULD INCLUDE WARNING AGAINST REUSE;		. —	
ï.	11.	FORMER CONTENTS; VAPOR STATE: VAPOR FREEING TREATMENT; DATE: THE STATE OF THE STATE		s i a a a a sa	
•	1	2. Tank vent hole (1/8 th " in uppermost part of tank) installed prior to moving the tank from site	EX Div		
	1	3. Inventory form filed by owner with Safety and Buildings Division Indicating closure by removal	M N N	THE STATE OF	닐
	1	4. Site security is provided while the excavation is open.	QY □ N		
	D.	CLOSURE IN PLACE			
		NOTE: CLOSURES IN PLACE ARE ONLY ALLOWED WITH THE PRIOR WRITTEN APPROVAL	•		
.		OF THE DEPARTMENT OF INDUSTRY, LABOR AND HUMAN RELATIONS OR LOCAL AGENT. 1. Product from pipiling drained into tank for other container).	· Control Con-	1 1	· · · · ·
		1. Pybauct from plantig drained into tank (ar other container).	- ·	_	_4.
		2. Piping discennected from tank and removed.	HÃ Hũ	Ц	
		3. All liquid and residue removed from tank using explosion proof pumps or hand pumps		님	H
		4. All pump motors and suction hoses bonded to tank or otherwise grounded	DY DN	H	H
		MOTE. DOOD TUDE QUOLUD NOT BE DEMOVED IS THE TANK IS TO BE SUBGED TUDOUGU		, \Box	4
		THE USE OF AN EDUCTOR - EDUCTOR OUTPUT 12 FT ABOVE GRADE.	t. 10°		,, (
i ·		THE USE OF AN EDUCTOR - EDUCTOR OUTPUT 12 FT ABOVE GRADE. 6. Vent lines left connected until tanks purged.	N Y Y		
		7. Tank openings temporarily plugged so vapors exit through vent.			
		8. Tank atmosphere reduced to 10% of the lower flammable lange (LEL) - see Section F			40
		9. Tank properly cleaned to remove all sludge and residue.	ПАПИ		Ш
6	. 1	0. Solid inert material (sand, cyclone boller slag, pea gravel recommended) introduced and tank filled.			Щ
		1. Vent line disconnected or removed.		. Ц.	
• ;		2. tryantory:form filad by owner with Safety and Buildings Division indicating closure in place	N: N: N		X
	E.	CLOSURE ASSESSMENTS			
		NOTE: DETERMINE IF A CLOSURE ASSESSMENT IS REQUIRED BY REFERRING TO ILHR 10.	•		
		1. Individual conducting the assessment has a closure assessment plan (written) which			
		is used as the basis for their work on the site.			Q
		2. Do points of obvious contamination exist?	□Y QN		ZEDENERE
		3. Are there strong odors in the solls? 4. Was a field screening instrument used to pre-screen soil sample locations?	HA NA	🙀	闵
·		9. Yeas a lively screening instrument used to pre-screen soli sample locations?		\vdash	없
		5. Was a closure assessment omitted because of obvious contamination?		H	黑
		Agency, office and person contacted			rÀ
		7. Contamination suspected because of: Odor Soil Staining Free Product Sheen On Groundwa	er Field	Instrument '	Test
<u>, .</u> .	r.	METHOD OF ACHIEVING 10% LEVEL DESCRIPTION	机色谱	:	
•		Educator or suprassed Air Blower Educator driven by compressed air, bonded and drop tube left in place; vapors discharged minimum of	f 12 feet abo	ve around	
		Diffused air blower bonded and drop tube removed. Air pressure not exceeding 5 psig.	· · · ico: abo	ground.	
		Dry Ice.		•	
•	•	Dry ice introduced at 1.5 pounds per 100 gallons of tank capacity. Dry ice crushed and distributed of	ver the great	idieecq feel	e tank
		area. Dry ice evaporated before proceeding.		•	
		Inert Gas (CO/2 or N/2). NOTE: INERT GASSES PRODUCE AN OXYGEN DEFICIENT ATMOSPHER	E. THE TAN	NK MAY NO	OT BE
•		ENTERED IN THIS STATE WITHOUT SPECIAL EQUIPMENT			
		Gas introduced through a single opening at a point near the bottom of the tank at the end of the tank			
		Gas introduced under low pressure not to exceed 5 psig to reduce static electricity. Gas introducing	gevice Broni	naea.	
		Tank atmosphere monitored for flammable or combustible vapor levels. Calibrate combustible gas indicator. Drop tube removed prior to checking atmosphere. Tank space	monitored a	A hallam a	منطظام
		and upper portion of tank. Readings of 10% or less of the lower flammable range (LEL) obtained bel			
		graphic transfer in the second			
		NOTE SPECIFIC PROBLEMS OR NONCOMPLIANCE ISSUES BELOW		·····	
	a.	NOTE SPECIFIC PROBLEMS OF NOTCOMM LIMITE ISSUES BELOW			
	_				
	H.	REMOVER/CLEANER INFORMATION			
			511 (a.ph	٠.٠٠٠ ١	. 1
		mily the founding is the man construction of the first of the construction of the first of the construction of the first of the construction of th		1 1-1	9_
		Remover Name, (print) 3 Remover Signature 23 Remover Certif	ication No.	Date Signe	d
	ī.	INSPECTOR INFORMATION / /			
					,
		GREG BAVER PLITANI	0016	23	
, •		Inspector Name (print) Inspector Signature	nspector Cer	rtification N	0. ,.,
		attitillita asta atti ili kandanda attitudi attita attita attita atti ili atti ili attita attita attita attita	12-7	7-94	
	-	FDID # For Location Where Inspection Performed Inspector Telephone Number	Date Signed		

OWNER

Wisconsin Department of Industry, Labor and Human Relations For Office Use Only:

UNDERGROUND PETROLEUM PRODUCT TANK INVENTORY



gen / Completed Form To: 1914 & Buildings Division 10 Pox 7969 (Yadisan, WI 53707

For Office Use Only:	TANI	INVENTORY		Box 7969 disan, WI 53707				
Tank ID #		ed By Sec. 102.142, Wis	. Stats. Tele	phone: (608) 267-5280				
Underground tanks in Wisconsin that have stored or currently store petroleum or regulated substances must be registered. Please see the reverse side for additional information on this program. An underground storage tank is defined as any tank with at least 10 percent of its total volume (included piping) located below ground level. A separate form is needed for each tank. Send each completed form to the agency designated in the top right corner. Have you previously registered this tank by submitting a form? YES NO if yes, are you correcting/updating information only? Yes No The information you provide may be used by other government agency programs (Privacy Law, s. 15.04 (1) (m)].								
This registration applies to a tank that is (check	A		Fire Department P	roviding Fire Coverage				
•	Closed - Tank Removed		Where Tank Locat	ed:				
2 Abandoned With Product 6. 3. Abandoned No Product (empty)	Closed - Filled With Inert Material	(indicate new owner below)						
	☐ Out of Service - Provide Da	•	CAMPA	8811_				
A. IDENTIFICATION: (Please Print)				/ Co. (2-2)				
1. Tank Site Name	Site Add		سنيدي	Site Telephone No.				
City Olliage	: 夕く 図 Town of:	1645 CAROLE	v &. > '	((xx5) 7614-1549				
Ср	MPBELL	WI	59603	LA CHOSTAL				
2. Owner Name (mail sent here unless indicat	ad otherwise in #3 below)	OwnerMailing Address (ma	1 1 3	dicated otherwise in #3)				
□ City □ Village	Town of:	State	0 Code 402-0773	County of Change				
3. Alternate Mailing Name If Different Than		Alternate Mailing Street Ad	dress if Different Fro	m #2				
☐ City ☐ Village	☐ Town of:	State 2	ip Cod e	County				
4. Tank Age (date installed, if known: or year Not لاماروندی ما	s old) 5. Tank Capacity (gal うぐる		ar's Name (if known) Kawwa					
B. TYPE OF USER (check one): 1. Gas Station 2. B	ulk Storage	3. Utility	A 172	Mercantile				
5. 🔲 Industrial 6. 🗀 G	overnment	7. School		Residentia				
9 Agricultural 10. O C. TANK CONSTRUCTION:	ther (specify):		· ·					
1. 😡 Bare Steel 2. 🗆 Co	athodically Protected and Coa	ted Steel (A. 🔲 Sacrificial A	nodes or B. 🗌 Impr	essed Current)				
3 ☐ Coated Steel 4. ☐ Fi 6. ☐ Relined - Date 7. ☐ \$1	bergiass Icel - Fiberglass Reinforced Pla	5, Other	er (specify):					
	Other:	Accessification 11 CD original	Is Tank Doub!	e Walled? Yes (T No				
Overfill Protection Provided? Yes No	if yes, identify type:		Spill Containing	nent? 🔲 Yes 😫 No				
Tank leak detection method: 1. Automatic tightness testing 5. Interstitial monitorial				4. Inventory control and anks of 1,000 gallons or less)				
D. PIPING CONSTRUCTION 1. SC Bare Steel 2. Cathodically Protect 4. Fiberglass 5. Other (specify):				9 🗍 Haknown				
Piping System Type: 1. Pressurized piping was 3. Suction piping with	rith: A. 🗀 auto shutoff; B. 🗍 check valve at pump and inspe	alarm; or C. I flow restricto	ir 2. 🔯 Suction pi	ping with check valve at tank				
Piping leak detection method; used if pressurize	ed or check valve at tank: 1. (Vapor monitoring 2	. 🔲 interstitial moni . 😭 Not Required	toring				
· · · · · · · · · · · · · · · · · · ·	Other:		Double Wailed:	☐ Yes ②XNo				
E. TANK CONTENTS								
1. Diesel 2. D.L.	aaded	3. Unleaded	_	Fuel Oil				
5. ☐ Gasohol 6. ☐ O 9. ☐ Unknown 10. ☐ P		7. ☐ Empty 11. ☐ Waste Oil	=) Sand/Grave//Slurry) Propane				
13. 1 Chemical & Aller I	***	14. Merosene	. =	Aviation				
A If # 13 is checked, indicate the chemical nam	e(s) or number(s) of the chemi	ical or waste.						
If Tank Closed, Give Date (mo/day/yr):		Has a site assessment been	completed? (reare	verse side (oc details)				
12-7-49	/	a site assessing it been	Yes Mo	verse side to) details)				
		tallation in an area.						
If installation of a new tank is being reported, in 1. Fire Department 2. D		3. Other (identify)						
Name of Owner or Operator (please print):			Whether:					
	32	X	Owner or !	☐ Operator				
Signature of Owner or Operator:		Date Si						
almina M He	cin	Х	12-7-	94				
SBD-7437 (R. 05/94) IMPORTANT:	Complete as many iter	ns on this form as poss	ible. Failure to	provide sufficient				



WELL/DRILLHOLE/BOREHOLE ABANDONMENT FORMS

State of Wisconsin Department of Natural Resources

WELL/DRILLHOLE/BOREHOLE ABANDONMENT Form 3300-5B Rev. 7-89

All abandonment work shall be performed in accordance with the provisions of Chapters NR 111, NR 112 or NR 141, Wis. Admin. Code, whichever is applicable. Also, see instructions on back.

(1) GENERAL INFORMATION	(2) FACILITY NAME
Weil/Drillhole/Borehole County Location Lo. Crosses	Original Well Owner (If Known)
La Crosse	D as ANY HAD
SE was NW was 19 and 105 and 7	Present Well Owner Joliyatta Clanners & Launders
SE 1/4 of NW 1/4 of Sec. 19; T. 105 N; R. 7 W	Jolivette Cleaners & Laundry Street or Route
(If applicable)	1645 Caroline Street
Grid Location Gov't Lot Grid Number	City, State, Zip Code
n. 🗆 N. 🗆 S.,n. 🗀 E. 🗆 W.	La Crosse, Wisconsin 54603
Civil Town Name	Facility Well No. and/or Name (If Applicable) WI Unique Well No.
Street Address of Well	Reason For Abandonment
1645 Caroline Street	Hand Auger for soil sample collection
City, Village	Date of Abandonment
La Crosse	12-12-94
WELL/DRILLHOLE/BOREHOLE INFORMATION	
(3) Original Well/Drillhole/Borehole Construction Completed On	(4) Depth to Water (Feet)
(Date) <u>12-12-94</u>	Pump & Piping Removed? Yes No Not Applicable
	Liner(s) Removed? Yes No Not Applicable
Monitoring Well Construction Report Available?	Screen Removed? Yes No Not Applicable
☐ Water Well ☐ Yes ■ No	Casing Left in Place? Yes No
Drillhole Borehole	If No, Explain
Dotelloie	Was Casing Cut Off Below Surface? Yes No
Construction Type:	Did Sealing Material Rise to Surface? Yes No
☐ Drilled ☐ Driven (Sandpoint) ☐ Dug	Did Material Settle After 24 Hours? Yes No
Other (Specify) Hand Auger	If Yes, Was Hole Retopped? Yes No
Formation Type:	(5) Required Method of Placing Sealing Material
Unconsolidated Formation Bedrock	Conductor Pipe-Gravity Conductor Pipe-Pumped
TALLEY U.S. AL (64)	Dump Baller Other (Explain) Gravity from Surface (6) Sealing Materials For monitoring wells and
Total Well Depth (ft.) Casing Diameter (ins.)	Neat Cement Group monitoring well boreholes only
"	Sand-Cement (Concrete) Grout
Casing Depth (ft.)	Concrete Bentonite Pellets
	Clay-Sand Slurry Granular Bentonite Bentonite-Sand Slurry Bentonite - Cement Grout
Was Well Annular Space Grouted?	Chipped Bentonite
(7)	No. Yards,
Sealing Material Used	From (Ft.) To (Ft.) Sacks Sealant Mix Ratio or Mud Weight or Volume
Granular Bentonite	Surface 7 17 LBs
(8) Comments:	
(9) Name of Person or Firm Doing Sealing Work	(LD) ASSESSMENT DINITYOUTE PROPERTY OF THE SECONDARY
Midwest Environmental Management Company	Date Received/hispocles
Signature of Person Doing Work Date Signed	
Street or Route Telephone Number	
1,000, 704, 7000	
	Collow-up (codess)
City, State, Zip Code	
La Crosse Wisconsin 54601	



RECEIVED

DEC 19 1994

DNR La Crosse Area

December 16, 1994

Mr. John Storlie Hydrogeologist Wisconsin Department of Natural Resources 3550 Mormon Coulee Road La Crosse, Wisconsin 54601

Subject: Borehole Abandonment Forms - Jolivette Cleaners & Laundry, La Crosse, Wisconsin

Dear Mr. Storlie:

Enclosed please find Midwest Environmental Management Company's completed Borehole Abandonment Forms 3300-5B for the one hand auger boring for the late Site Assessment investigation (performed on December 12, 1994) for the 300 gallon 142 Solvent 66/3 (dry cleaning solvent) underground storage tank which was removed from the Jolivette Cleaners & Laundry property on December 7, 1994. The Jolivette Cleaners & Laundry property (tank site address) is located at 1645 Caroline Street, City of La Crosse, La Crosse County, Wisconsin.

If you should require further information or have any questions concerning this project, please feel free to contact me at your convenience.

Sincerely,

Midwest Environmental Management Company

Dean Ellefson

Environmental Technician

State of Wisconsin Department of Natural Resources

WELL/DRILLHOLE/BOREHOLE ABANDONMENT Form 3300-5B Rev. 7-89

All abandonment work shall be performed in accordance with the provisions of Chapters NR 111, NR 112 or NR 141, Wis. Admin. Code, whichever is applicable. Also, see instructions on back.

(1) GENERAL INFORMATION	(2) FACILITY NAME					
Well/Drillhole/Borehole County Location Location Location	Original Well Owner (If Known)					
La Clusse	Present Well Owner					
\underline{SE} 1/4 of \underline{NW} 1/4 of Sec. $\underline{19}$; T. $\underline{105}$ N; R. $\underline{7}$ \blacksquare W	Jolivette Cleaners & Laundry					
	Street or Route					
(If applicable)	1645 Caroline Street					
Grid Location Gov't Lot Grid Number	City, State, Zip Code					
ft. \[\scale \text{N.} \] S., \[\left[\text{ft.} \] E. \[\scale \text{W.} \]	La Crosse, Wisconsin 54603					
Civil Town Name	Facility Well No. and/or Name (If Applicable) WI Unique Well I	No.				
	, , , , , , , , , , , , , , , , , , , ,					
Street Address of Well	Reason For Abandonment					
1645 Caroline Street	Hand Auger for soil sample collection					
City, Village	Date of Abandonment					
La Crosse	12-12-94					
WELL/DRILLHOLE/BOREHOLE INFORMATION	10 10 71					
(3) Original Well/Drillhole/Borehole Construction Completed On	(4) Depth to Water (Feet)					
(Date) 12-12-94	Pump & Piping Removed? Yes No Not App	licable				
	Liner(s) Removed?	licable				
Monitoring Well Construction Report Available?	Screen Removed? Yes No Not App	licable				
☐ Water Well ☐ Yes ■ No	Casing Left in Place? Yes No					
Drillhole Baselele	If No, Explain					
Borehole	Was Casing Cut Off Below Surface? Yes No					
Construction Type:	Did Sealing Material Rise to Surface? Yes No					
☐ Drilled ☐ Driven (Sandpoint) ☐ Dug	Did Material Settle After 24 Hours? Yes No					
Other (Specify) Hand Auger	If Yes, Was Hole Retopped?					
The state of the s	(5) Required Method of Placing Sealing Material Conductor Pipe-Gravity Conductor Pipe-Pumped					
Formation Type: Unconsolidated Formation Bedrock						
Checonsolidated Pormation Bedrock	☐ Dump Bailer ☐ Other (Explain) Gravity from	Surfac				
Total Well Depth (ft.) Casing Diameter (ins.)	(6) Sealing Materials For monitoring wells and monitoring well boreholes	only				
(From groundsurface)	☐ Neat Cement Group monitoring well boreholes ☐ Sand-Cement (Concrete) Grout	omy				
Casing Depth (ft.)	Concrete ! Bentonite Pellets					
	Clay-Sand Slurry Granular Bentonite					
Was Well Annular Space Grouted? Yes No Unknown	☐ Bentonite-Sand Slurry ☐ Bentonite - Cement G	rout				
If Yes, To What Depth? Feet	Chipped Bentonite					
(7) Sealing Material Used	From (Ft.) To (Ft.) No. Yards, Sacks Sealant Mix Ratio or Mud Weig	ght				
Granular Bentonite	Surface 7 17 LBs					
,						
(8) Comments:						
(9) Name of Person or Firm Doing Sealing Work	(10) FOR DNR OR COUNTY USE ONLY					
Midwest Environmental Management Company	Date Received/Inspected District/County					
Signature of Person Doing Work Date Signed	District County					
- 10 0.1	Reviewer/Inspector					
Street or Route Telephone Number	activities and a second					
	Follow-up Necessary					
123 N. 4th St Suite 304 (608) 784-5688 City, State, Zip Code						
La Crosse, Wisconsin 54601						
La Cioud, Hibbolibili JTOOI						

REGEIVED
DEC 1 9 1994

JNR - a Crosse Area