K P R G

ENVIRONMENTAL CONSULTATION & REMEDIATION

KPRG and Associates, Inc.

STATUS REPORT, ADDITIONAL WORK PLAN and BUDGET REQUEST (REVISED)

February 16, 2017

Mr. David Volkert
Wisconsin Department of Natural Resources
141 NW Barstow Street, Room 180
Waukesha, WI 53188

VIA Email and US Mail

KPRG Project 10009

Re: Status Report, Additional Work Plan and Budget Request – January 2017 (Revised 2/16/17)
Former Bask Dry Cleaners – Waukesha, WI
BRRTS# 02-68-297669, FID# 268188800

Dear Mr. Volkert:

Results from the most recent round of groundwater sampling, indoor air sampling and soil vapor sampling have been completed. The groundwater data are summarized in Tables 1 and 2. The indoor air data are summarized in Table 3 and the soil vapor data are summarized in Table 4. Each is discussed separately below followed by a proposed additional scope of work and budget based on our telephone discussion on October 27, 2016.

Groundwater Evaluation

Three new monitoring wells have been installed and sampled since the last data summary report. These wells are indentified as MW-14, MW-15 and MW-16 and are included on Figure 1. Copies of the boring logs and well construction summaries are provided in Attachment 1.

The most recent rounds of groundwater samples were collected on June 1st through 3rd and September 20th through 23rd, 2016. The groundwater elevation measurements are included in Table 1 and the data are summarized in Table 2 which includes historical data. Figure 1 provides the most recent groundwater flow map (consistent with historic trends) and Figure 2 provides extent of impact contours based on that data for tetrachloroethene (PCE) and trichloroethene (TCE). There was only one detection of cis-1,2 dichloroethene (DCE) above the enforcement standard (ES) which was at location MW-6, immediately down gradient of the source area. The only vinyl chloride detection in the most recent sampling was 8.9 ug/l at well MW-5 which is within the source area. An evaluation of Figure 2 indicates that the leading edge of the impacted groundwater plume has not yet been defined. Based on discussions with WDNR, three additional downgradient monitoring wells are proposed as further discussed in the Additional Work Plan Scope of Work section below.

Soil Vapor Intrusion Evaluation

Indoor Air Sampling
Since the previous submittal, a sub-slab depressurization system (SSDS) was installed at 2156 Rambling Rose on December 16, 2015. At the request of the homeowner, a pre-installation indoor air sample was collected on December 2, 2015. A follow-up, post-installation indoor air sample was collected on March 31, 2016 in accordance with the previously approved Work Plan. The samples were analyzed for chlorinated volatile organic compounds (CVOCs) using Method TO15. The data are summarized in Table 3. A review of Table 3 indicates that there were no detections of CVOCs in either sample above established guidelines/standards.

Soil Vapor Probe Sampling
Three additional soil vapor probes (SV-13, SV-14 and SV-15) were installed in March 2016 per the previously approved Work Plan. Locations of the vapor probe locations are shown on Figure 3. A complete round of soil vapor samples was collected on March 31, 2016. Table 4 summarizes all soil vapor sampling data to date including the most recent round of sampling. Figure 3 provides an isoconcentration contour map of soil vapor impacts. Based on this sampling, the extent of soil vapor impacts appears to be adequately defined, however, as noted below, the WDNR has requested to resample three vapor probe locations (see Task 4).

ADDITIONAL WORK PLAN SCOPE OF WORK

For budget estimating purposes, the additional work discussed below is divided into the following tasks:

- Task 1 – Additional Requested Work Planning/Coordination
- Task 2 – New Well Installations
- Task 3 – Additional Groundwater Sampling
- Task 4 – Vapor Probe Sampling
- Task 5 – Additional Reporting
- Task 6 – Operation and Maintenance

Each task is discussed separately below.

Task 1 – Additional Requested Work Planning/Coordination

Three new monitoring wells (MW-17, MW-18 and MW-19) are being proposed at locations shown on Figure 4. Two of these wells (MW-17 and MW-18) will be on private commercial property and the other well (MW-19) will be located along a road right-of-way. The scope of this task includes the project management and planning that will be required for the successful completion of the additional work. This includes negotiating a property access agreement for two

PATHWAY TO CLOSURE

It is our understanding that once the extent of groundwater impacts has been sufficiently defined, the site will be ready for conditional closure consideration. If the data indicate that additional work is necessary, discussions will be held with WDNR to define further scope.

COST ESTIMATE

Costs are summarized in Table 5 and detailed on the costing sheets in Attachment 2. The additional requested budget for the above defined scope of work is $58,690. The unit rates used in this cost estimate are consistent with previous KPRG rates.

Only those costs incurred will be billed. All billing will be performed on a monthly basis using the unit rates. No additional work will be performed until formal WDNR approval of the proposed budget is received. If there are any questions, please contact me at 262-781-0475.

Sincerely,
KPRG and Associates, Inc.

Richard R Gnat

Richard R. Gnat, P.G.
Principal

cc: Mr. Greg Butts, former Bask Dry Cleaners
Ms. Michelle Williams, Husch Blackwell, LLP.
Mr. Donald Gallo, Husch Blackwell, LLP

FIGURES

N

LEGEND

- MW-12 — MONITORING WELL, PIEZOMETER LOCATION
- GROUNDWATER CONTOUR
- GROUNDWATER DETAIL CONTOUR
- GROUNDWATER FLOW DIRECTION

MW-11 914.43
MW-12 915.10
915.24 MW-7
914.04 MW-5
PZ-2
914.73 MW-1
913.75 MW-4
PZ-1
914.85 MW-2
MW-3 914.13
912.19 MW-6
911.31 MW-13
MW-8 909.50
PZ-3
MW-10 902.70
MW-14 860.27
MW-15 860.13
MW-16 860.17
MW-9 911.74

915
910
900
890
880
870
860

KOHL'S DEPARTMENT STORE BUILDING
STORAGE ROOM
FORMER BASK DRY CLEANERS
LAUNDROMAT
PAYLESS SHOE SOURCE
COMMERCIAL
COMMERCIAL
ASPHALT
2129 SUNNYSIDE DR. SAGER RESIDENCE
2008 CAPELLA CT. JOHNSON RESIDENCE
2004 CAPELLA CT. HO RESIDENCE
2000 CAPELLA CT. ZEITLER RESIDENCE
2003 CAPELLA CT. ANDREAS RESIDENCE
2011 CAPELLA CT. BLANCHARD RESIDENCE
2007 CAPELLA CT. FALVEY RESIDENCE
2151 RAMBLING ROSE RD. STOCKINGER RESIDENCE
2157 RAMBLING ROSE RD. LEX RESIDENCE
2150 RAMBLING ROSE ZATORSKI RESI
2156 RAMBLING ROS SCHNEIDER RESIDE
SUNNYSIDE DRIVE
CAPELLA COURT
RAMBLING ROSE
SPRINGDALE ROAD
GRASS
CONCRETE WALK
GRASS MEDIAN
Springdale Rd

0 70'
APPROXIMATE SCALE

ENVIRONMENTAL CONSULTATION & REMEDIATION

KPRG and Associates, Inc.

14665 West Lisbon Road, Suite 2B Brookfield, Wisconsin 53005 Telephone 262-781-0475 Facsimile 262-781-0478

414 Plaza Drive, Suite 106 Westmont, Illinois 60559 Telephone 630-325-1300 Facsimile 630-325-1593

GROUNDWATER CONTOURS--SEPTEMBER 2016

WESTBROOK SHOPPING CENTER
WAUKESHA, WISCONSIN

Scale: 1" = 70' | Date: October 5, 2016

KPRG Project No. 10009 | FIGURE 1

N

KOHL'S DEPARTMENT STORE BUILDING

FORMER BASK DRY CLEANERS

STORAGE ROOM

LAUNDROMAT

PAYLESS SHOE SOURCE

COMMERCIAL

COMMERCIAL

ASPHALT

2129 SUNNYSIDE DR. SAGER RESIDENCE

2008 CAPELLA CT. JOHNSON RESIDENCE

2004 CAPELLA CT. HO RESIDENCE

2000 CAPELLA CT. ZEITLER RESIDENCE

2003 CAPELLA CT. ANDREAS RESIDENCE

2007 CAPELLA CT. FALVEY RESIDENCE

2011 CAPELLA CT. BLANCHARD RESIDENCE

2151 RAMBLING ROSE RD. STOCKINGER RESIDENCE

2157 RAMBLING ROSE RD. LEX RESIDENCE

2150 RAMBLING ROSE RD. ZATORSKI RESIDENCE

2156 RAMBLING ROSE RD. SCHNEIDER RESIDENCE

CAPELLA COURT

SUNNYSIDE DR

RAMBLING ROSE

SPRINGDALE ROAD

GRASS MEDIAN

GRASS

CONCRETE WALK

MW-1 ND ND

MW-2 NS

MW-3 0.53 ND

MW-4 0.88 ND

MW-5 6.2 5.4

MW-6 96 13

MW-7 2.1 7.8

MW-8 2.9 ND

MW-9 ND ND

MW-10 16 4.4

MW-11 1.1 ND

MW-12 12 0.89

MW-13 36 3.9

MW-14 2.4 ND

MW-15 130 2.8

MW-16 54 0.92

PZ-1

PZ-2

PZ-3

5

10

100

LEGEND

- MW-12 — MONITORING WELL, PIEZOMETER LOCATION
- 5 — PCE CONCENTRATION CONTOUR
- 5 — TCE CONCENTRATION CONTOUR
- GROUNDWATER FLOW DIRECTION
- PCE ENFORCEMENT STANDARD = 5 µg/L
- TCE ENFORCEMENT STANDARD = 5 µg/L

0 70' APPROXIMATE SCALE

ENVIRONMENTAL CONSULTATION & REMEDIATION

KPRG

KPRG and Associates, Inc.

14665 West Lisbon Road, Suite 2B Brookfield, Wisconsin 53005 Telephone 262-781-0475 Facsimile 262-781-0478

414 Plaza Drive, Suite 106 Westmont, Illinois 60559 Telephone 630-325-1300 Facsimile 630-325-1593

EXTENT OF GROUNDWATER IMPACTS

WESTBROOK SHOPPING CENTER
WAUKESHA, WISCONSIN

Scale: 1" = 70' | Date: October 31, 2016

KPRG Project No. 10009 | FIGURE 2



ENVIRONMENTAL CONSULTATION & REMEDIATION
KPRG and Associates, Inc.
K P R G
14665 West Lisbon Road, Suite 2B Brookfield, Wisconsin 53005 Telephone 262-781-0475 Facsimile 262-781-0478
414 Plaza Drive, Suite 106 Westmont, Illinois 60559 Telephone 630-325-1300 Facsimile 630-325-1593

EXTENT OF SOIL VAPOR IMPACTS

WESTBROOK SHOPPING CENTER
WAUKESHA, WISCONSIN

Scale: 1" = 70'
Date: October 31, 2016
KPRG Project No. 10009
FIGURE 3



LEGEND

- MW-12 — EXISTING MONITORING WELL, PIEZOMETER LOCATION
- MW-17 — PROPOSED MONITORING WELL LOCATION
- SV-1A — SOIL VAPOR PROBE
- 5 — PCE CONCENTRATION CONTOUR
- 5 — TCE CONCENTRATION CONTOUR
- PCE ENFORCEMENT STANDARD = 5 µg/L
- TCE ENFORCEMENT STANDARD = 5 µg/L

ENVIRONMENTAL CONSULTATION & REMEDIATION

KPRG and Associates, Inc.

14665 West Lisbon Road, Suite 2B Brookfield, Wisconsin 53005 Telephone 262-781-0475 Facsimile 262-781-0478

414 Plaza Drive, Suite 106 Westmont, Illinois 60559 Telephone 630-325-1300 Facsimile 630-325-1593

PROPOSED ADDITIONAL MONITORING WELLS LOCATIONS

WESTBROOK SHOPPING CENTER
WAUKESHA, WISCONSIN

Scale: 1" = 120' | Date: November 28, 2016

KPRG Project No. 10009 | FIGURE 4

TABLES

Table 1. Water Level Elevation Table - Former Bask Dry Cleaners, Westbrook Shopping Center, Waukesha, WI

WELL	USGS Datum Elevations		3/23/2005		10/19/2005		6/19/2008		8/25/2008		8/20/2009		12/7/2009		3/10/2010		6/4/2010	
	Ground	Top of Casing	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev
MW-1	941.64	941.25	27.46	913.79	28.11	913.14	24.31	916.94	24.22	917.03	24.51	916.74	25.10	916.15	25.23	916.02	25.03	916.22
MW-2	942.41	942.07	28.45	913.62	29.17	912.90	26.25	915.82	25.20	916.87	25.48	916.59	26.07	916.00	26.21	915.86	24.97	917.10
MW-3	937.79	937.32	24.07	913.25	24.90	912.42	20.80	916.52	21.33	915.99	21.68	915.64	22.11	915.21	22.11	915.21	21.86	915.46
MW-4	932.33	931.89	19.18	912.71	20.05	911.84	15.54	916.35	16.30	915.59	16.37	915.52	17.00	914.89	16.97	914.92	16.71	915.18
MW-5	934.42	934.08	20.82	913.26	21.35	912.73	17.62	916.46	18.15	915.93	18.25	915.83	18.76	915.32	19.90	914.18	19.15	914.93
MW-6	925.93	925.65	13.96	911.69	15.15	910.50	10.21	915.44	11.61	914.04	>11.8	NV	11.98	913.67	11.87	913.78	11.91	913.74
MW-7	935.95	935.58	21.98	913.60	23.17	912.41	18.85	916.73	19.22	916.36	18.35	917.23	18.89	916.69	18.30	917.28	17.85	917.73
MW-8	923.36	922.92	12.58	910.34	14.96	907.96	11.01	911.91	12.88	910.04	12.93	909.99	12.91	910.01	12.90	910.02	12.58	910.34
MW-9	919.56	919.23	8.18	911.05	9.50	909.73	4.34	914.89	5.83	913.40	5.81	913.42	6.11	913.12	5.75	913.48	5.90	913.33
MW-10	918.24	917.88	15.31	902.57	17.40	900.48	8.24	909.64	12.52	905.36	12.35	905.53	12.51	905.37	11.43	906.45	11.78	906.10
MW-11	NS	NS	NM	NS	NM	NS	19.42	NS	19.15	NS	19.45	NS	20.00	NS	19.75	NS	19.55	NS
MW-12	NS	NS	NM	NS	NM	NS	17.55	NS	17.99	NS	17.96	NS	18.55	NS	17.30	NS	18.34	NS
MW-13	NS	NS	NM	NS	NM	NS	9.84	NS	10.93	NS	10.88	NS	11.03	NS	10.43	NS	10.78	NS
PZ-1	932.34	931.82	40.51	891.31	41.20	890.62	40.92	890.90	40.90	890.92	40.46	891.36	40.74	891.08	39.00	892.82	40.25	891.57
PZ-2	934.27	933.79	DRY	NV	NM	NV	59.14	874.65	59.30	874.49	58.96	874.83	59.05	874.74	59.00	874.79	58.98	874.81
PZ-3	NS	922.99	DRY	NV	NM	NV	DRY	NV	DRY	NV	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY

WELL	USGS Datum Elevations		12/16/2010		6/21/2011		6/20/2012		1/18/2013		10/22/2014		6/30/2015		6/1/2016		9/20/2016	
	Ground	Top of Casing	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev	Depth to Water	Water Elev
MW-1	941.64	941.34	25.33	915.92	24.96	916.29	26.58	914.67	27.51	913.74	26.29	914.96	27.13	914.12	26.42	914.92	26.61	914.73
MW-2	942.41	942.15	26.24	915.83	25.92	916.15	27.34	914.73	NM	NM	27.04	915.03	27.91	914.16	27.14	915.01	27.30	914.85
MW-3	937.79	937.48	22.40	914.92	21.87	915.45	23.26	914.06	23.88	913.44	23.12	914.20	23.50	913.82	23.13	914.35	23.35	914.13
MW-4	932.33	932.09	17.33	914.56	16.73	915.16	DRY	DRY	DRY	DRY	17.90	913.99	DRY	DRY	17.94	914.15	18.34	913.75
MW-5	934.42	934.19	18.94	915.14	18.51	915.57	20.18	913.90	21.02	913.06	20.02	914.06	20.68	913.40	19.93	914.26	20.15	914.04
MW-6	925.93	925.78	12.43	913.22	11.71	913.94	13.32	912.33	14.18	911.47	13.35	912.30	13.99	911.66	13.14	912.64	13.59	912.19
MW-7	935.95	935.90	19.40	916.18	18.24	917.34	20.85	914.73	21.96	913.62	20.56	915.02	21.27	914.31	20.56	915.34	20.66	915.24
MW-8	923.36	923.05	13.56	909.36	12.78	910.14	13.88	909.04	14.09	908.83	13.84	909.08	14.09	908.83	14.61	908.44	13.75	909.30
MW-9	919.56	919.44	7.59	911.64	5.76	913.47	7.55	911.68	8.43	910.80	7.11	912.12	8.21	911.02	7.30	912.14	7.70	911.74
MW-10	918.24	917.99	13.73	904.15	12.30	905.58	14.15	903.73	16.02	901.86	14.86	903.02	15.15	902.73	13.82	904.17	15.29	902.70
MW-11	NS	935.81	20.30	NS	19.77	NS	21.32	NS	22.23	NS	21.21	NS	22.00	NS	21.22	914.59	21.38	914.43
MW-12	NS	935.15	18.75	NS	18.46	NS	19.84	NS	20.96	NS	19.65	NS	20.69	NS	19.95	915.20	20.05	915.10
MW-13	NS	922.36	11.53	NS	10.62	NS	11.50	NS	12.13	NS	11.72	NS	11.72	NS	11.42	910.94	11.05	911.31
MW-14	NS	908.25	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	47.69	860.56	47.98	860.27
MW-15	NS	903.57	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	43.14	860.43	43.44	860.13
MW-16	NS	903.61	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	43.15	860.46	43.44	860.17
PZ-1	932.34	933.97	39.18	892.64	40.35	891.47	40.08	891.74	41.23	890.59	39.95	891.87	40.38	891.44	40.14	893.83	39.21	894.76
PZ-2	934.27	932.02	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY
PZ-3	NS	923.13	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY	DRY

Notes: All USGS elevation data in feet above mean sea level.
All depth to water data in feet below top of casing.

KPRG and Associates, Inc. data begins 8/20/09.
Wells resurveyed for the 6/1/16 sampling.

NS- Not Surveyed
NM- Not Measured

NI - Not Installed
DRY- Well was dry

Table 2. Summary of Groundwater Analytical Results - former Bask Dry Cleaners

Sample	WDNR NR 140 Standards		MW-1													MW-3												
Parameter Date	PAL	ES	06/19/08	08/20/09	12/07/09	03/10/10	06/04/10	12/16/10	06/22/11	06/18/12	01/18/13	10/22/14	06/30/15	06/01/16	09/20/16	06/19/08	08/21/09	12/07/09	03/10/10	06/04/10	12/16/10	06/22/11	06/18/12	01/18/13	10/22/14	06/30/15	06/02/16	09/22/16
cis-1,2-Dichloroethene	7.0	70	<0.83	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.12	<0.12	<0.12	<0.12	<0.41	<0.41	<0.83	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.12	<0.12	<0.12	<0.12	<0.41	<0.41
trans-1,2-Dichloroethene	20	100	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	<0.25	<0.25	<0.35	<0.35	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	<0.25	<0.25	<0.35	<0.35
Tetrachloroethene	0.5	5.0	<0.45	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.17	<0.17	<0.17	<0.17	<0.37	<0.37	<0.45	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	0.77 J	1.6	<0.17	<0.17	<0.37	0.53
Trichloroethene	0.5	5.0	<0.48	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.19	<0.19	<0.19	<0.19	<0.16	<0.16	<0.48	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.19	<0.19	<0.19	<0.19	<0.16	<0.16
Vinyl Chloride	0.02	0.2	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	<0.10	<0.10	<0.20	<0.20	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	<0.10	<0.10	<0.20	<0.20
Dissolved Oxygen (mg/l)	NE	NE	U	4.99	3.76	4.55	5.01	5.27	6.04	5.18	5.13	4.38	6.15	6.97	5.55	U	0.10	0.75	0.02	0.03	0.30	0.13	0.02	0.07	0.12	0.50	1.37	0.13
Oxidation-Reduction Potential	NE	NE	U	37.2	285	273	287.2	49.9	267.9	212.8	87.7	181.9	201.3	77.8	150.5	U	-130	97.7	-162.5	54.2	-34.1	33.6	142.3	73.4	43.7	54.7	256.4	147.8

Sample	WDNR NR 140 Standards		MW-4													MW-5												
Parameter Date	PAL	ES	06/19/08	08/21/09	12/07/09	03/10/10	06/04/10	12/16/10	06/22/11	06/21/12	01/18/13	10/23/14	06/30/15	06/01/16	09/23/16	06/19/08	08/21/09	12/07/09	03/18/10	06/04/10	12/17/10	06/22/11	06/21/12	01/18/13	10/22/14	07/01/15	06/02/16	09/23/16
cis-1,2-Dichloroethene	7.0	70	<0.83	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	NS	NS	<0.12	NS	<0.41	<0.41	54.6	<4.0	3.6 J	170	17	1,500	1,300	470	370	100	39	7.2	7.2
trans-1,2-Dichloroethene	20	100	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	NS	NS	<0.25	NS	<0.35	<0.35	<17.8	<4.0	<2.0	<0.20	<1.0	15	18 J	5.0	3.2	2.1	2.8	3.9	1.6
Tetrachloroethene	0.5	5.0	217	<0.50	3.2	3.2	0.69 J	<0.50	1.8 J	NS	NS	1.4	NS	<0.37	0.88	1,840	180	180	660	96	200	46	2.3	3.6	1.3	0.64	8.4	5.3
Trichloroethene	0.5	5.0	<0.48	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	NS	NS	<0.19	NS	<0.16	<0.16	16.7	<1.6	2.9	49	6.6	38	60	1.1	1.7	0.26	4.3	1.4	6.2
Vinyl Chloride	0.02	0.2	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	NS	NS	<0.10	NS	<0.20	<0.20	U	<1.6	<0.80	<0.80	<0.40	12	9.0 J	7.3	2.5	0.89	8.9	1.1	1.2
Dissolved Oxygen (mg/l)	NE	NE	U	2.75	1.31	5.20	1.10	1.67	NM	NS	NS	1.66	NS	3.64	5.21	U	3.18	0.66	NM	5.03	1.77	0.15	0.43	0.16	0.16	0.73	0.86	0.09
Oxidation-Reduction Potential	NE	NE	U	-82	209	-1.7	143.5	-4.6	NM	NS	NS	78.4	NS	240.0	49.6	U	30	-158	NM	-27.8	-13.7	-116.1	-71.4	-50.7	-56.9	-73.6	-96.7	-88.2

Sample	WDNR NR 140 Standards		MW-6													MW-7												
Parameter Date	PAL	ES	06/19/08	08/21/09	12/07/09	03/10/10	06/04/10	12/17/10	06/22/11	06/21/12	01/18/13	10/22/14	06/30/15	06/03/16	09/22/16	06/19/08	08/21/09	12/07/09	03/10/10	06/04/10	12/17/10	06/22/11	06/21/12	01/18/13	10/22/14	06/30/15	06/02/16	09/23/16
cis-1,2-Dichloroethene	7.0	70	44.5	NS	21 J	26 J	26 J	3,400	1,900	240	82	190	35	19	76	2.5	0.86 J	<0.50	<0.50	<0.50	0.62 J	<0.50	4.3	3.4	1.3	<0.12	<0.41	0.84
trans-1,2-Dichloroethene	20	100	<4.4	NS	<20	<16	<8.0	37	60	11	3.9	9.2	1.6	1.0	3.5	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	1.8	0.74	<0.35	<0.35
Tetrachloroethene	0.5	5.0	653	NS	1,700	1,400	500	430	400	320	260	220	140	70	96	48.5	22	30	35	30	34	29	1.7	1.2	<0.17	<0.17	1.5	2.1
Trichloroethene	0.5	5.0	8.9	NS	8.4 J	690	640	450	230	160	57	69	22	6.5	13	4.7	3.2	1.9	1.4	2.0	11	2.8	18	10	6.0	2.3	2.2	7.8
Vinyl Chloride	0.02	0.2	U	NS	<8.0	<6.4	<3.2	<2.0	<4.0	<0.10	<0.10	<0.10	<0.10	<0.20	<0.20	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	<0.10	0.28	<0.20	<0.20
Dissolved Oxygen (mg/l)	NE	NE	U	NS	2.43	0.64	1.20	0.33	0.46	0.77	3.74	0.08	0.94	1.93	0.24	U	2.84	2.10	1.86	1.80	0.61	0.05	0.38	0.00	0.21	0.64	1.83	0.55
Oxidation-Reduction Potential	NE	NE	U	NS	-46.7	-171.2	-117.8	-30.7	13.1	-18.1	75.2	92.2	78.5	100.3	81.8	U	-53.4	-194	-199.9	-142.9	-90.6	-196.8	-106.3	-36.7	-62.8	-71.6	-70.7	-48.8

Sample	WDNR NR 140 Standards		MW-8													MW-9												
Parameter Date	PAL	ES	06/19/08	08/20/09	12/07/09	03/10/10	06/04/10	12/16/10	06/22/11	06/21/12	01/18/13	10/22/14	06/30/15	06/03/16	09/22/16	06/19/08	08/20/09	12/07/09	03/10/10	06/04/10	12/16/10	06/22/11	06/18/12	01/18/13	10/22/14	06/30/15	06/02/16	09/22/16
cis-1,2-Dichloroethene	7.0	70	<0.83	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.12	<0.12	<0.12	<0.12	<0.41	<0.41	<0.83	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.12	<0.12	<0.12	<0.12	<0.41	<0.41
trans-1,2-Dichloroethene	20	100	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	<0.25	<0.25	<0.35	<0.35	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	<0.25	<0.25	<0.35	<0.35
Tetrachloroethene	0.5	5.0	<0.45	<0.50	<0.50	<0.50	<0.50	1.2 J	<0.50	1.3	1.7	1.8	2.7	1.8	2.9	<0.45	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.17	<0.17	<0.17	<0.17	<0.37	<0.37
Trichloroethene	0.5	5.0	<0.48	<0.20	<0.20	<0.20	<0.20	0.58 J	<0.20	0.62	0.41	0.36	<0.19	<0.16	<0.16	<0.48	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.19	<0.19	<0.19	<0.19	<0.16	<0.16
Vinyl Chloride	0.02	0.2	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	<0.10	<0.10	<0.20	<0.20	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	<0.10	<0.10	<0.20	<0.20
Dissolved Oxygen (mg/l)	NE	NE	U	2.57	4.96	3.91	6.00	1.86	7.05	3.92	1.44	1.80	3.09	4.89	2.11	U	4.93	3.83	5.84	4.91	4.80	4.98	4.27	4.71	3.65	5.61	6.06	3.94
Oxidation-Reduction Potential	NE	NE	U	-60.7	143	212.9	80.5	-1.2	127.07	61.5	76.5	137.7	123.3	240.2	195.1	U	-67.9	60	-44.1	26.2	18.5	74.13	159.2	70.6	74.7	73.3	63.2	117.7

Sample	WDNR NR 140 Standards		MW-10													MW-11												
Parameter Date	PAL	ES	06/19/08	08/20/09	12/07/09	03/18/10	06/04/10	12/16/10	06/22/11	06/21/12	01/18/13	10/22/14	06/30/15	06/03/16	09/22/16	06/19/08	08/20/09	12/07/09	03/10/10	06/04/10	12/16/10	06/22/11	06/21/12	01/18/13	10/22/14	06/30/15	06/02/16	09/22/16
cis-1,2-Dichloroethene	7.0	70	<0.83	2.5	2.2	<0.50	1.0 J	1.5 J	1.1 J	0.77 J	<0.12	**12.0**	4.3	2.8	**7.7**	<0.83	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.12	<0.12	<0.12	<0.12	<0.41	<0.41
trans-1,2-Dichloroethene	20	100	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	<0.25	<0.25	<0.35	<0.35	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	<0.25	<0.25	<0.35	<0.35
Tetrachloroethene	0.5	5.0	**2.8**	**15**	**11**	**7.4**	**13**	**13**	**13**	**13**	**12**	**11**	**14**	**9.6**	**16**	**6.5**	**2.9**	**1.8**	**3.1**	**3.9**	**1.7 J**	**4.6**	**1.4**	**2.5**	**1.1**	**1.5**	**1.4**	**1.1**
Trichloroethene	0.5	5.0	<0.48	**0.94**	**1.2**	0.41 J	**0.85 J**	**1.7 J**	**0.93 J**	**0.89**	**0.85**	**4.0**	**3.5**	**1.9**	**4.4**	<0.48	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.19	<0.19	<0.19	<0.19	<0.16	<0.16
Vinyl Chloride	0.02	0.2	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	**<0.10**	**<0.10**	<0.20	<0.20	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	<0.10	<0.10	<0.20	<0.20
Dissolved Oxygen (mg/l)	NE	NE	U	5.19	4.24	NM	5.01	3.46	6.46	5.15	7.25	4.67	7.85	7.19	7.33	U	2.66	2.31	5.82	3.55	1.81	2.23	1.77	2.43	1.78	3.15	4.13	4.27
Oxidation-Reduction Potential	NE	NE	U	-60.7	154	NM	145.9	14.1	155.3	103.3	74.9	**136.9**	**114.0**	275.2	180.9	U	-84.2	155	121.1	-23.4	-9.0	59.7	184.9	69.7	118.9	79.0	147.3	144.0

Sample	WDNR NR 140 Standards		MW-12													MW-13												
Parameter Date	PAL	ES	06/19/08	08/20/09	12/07/09	03/10/10	06/04/10	12/17/10	06/22/11	06/21/12	01/18/13	10/22/14	06/30/15	06/03/16	09/23/16	06/19/08	08/20/09	12/07/09	03/10/10	06/04/10	12/17/10	06/22/11	06/21/12	01/18/13	10/22/14	06/30/15	06/03/16	09/22/16
cis-1,2-Dichloroethene	7.0	70	2.0	2.1	2.6	1.4 J	1.3 J	2.2	1.3 J	2.9	1.7	NS	2.5	1.4	1.9	**34.8**	**26**	**25**	**24**	**17**	**16**	**40**	**23**	**9.7**	**16**	**16**	**16**	**20**
trans-1,2-Dichloroethene	20	100	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	NS	**<0.25**	<0.35	<0.35	1.1	1.7	0.80 J	1.6 J	0.79 J	0.74 J	1.30 J	1.1	0.62	<0.25	0.95	0.86	1.1
Tetrachloroethene	0.5	5.0	**48.7**	**54**	**34**	**31**	**51**	**19**	**49**	**23**	**29**	NS	**22**	**12**	**12**	**13.8**	**63**	**58**	**54**	**41**	**39**	**60**	**40**	**32**	**21**	**32**	**27**	**36**
Trichloroethene	0.5	5.0	**4.3**	**4.6**	**2.8**	**3.5**	**4.6**	**2.3**	**3.8**	**2.5**	**1.9**	NS	**1.5**	**0.96**	**0.89**	**1.7**	**2.6**	**2.4**	**3.1**	**2.1**	**6.5**	**18**	**11**	**6.5**	**3.9**	**4.1**	**3.2**	**3.9**
Vinyl Chloride	0.02	0.2	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	NS	<0.10	<0.20	<0.20	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	<0.10	<0.10	<0.20	<0.20
Dissolved Oxygen (mg/l)	NE	NE	U	2.98	2.34	7.14	2.97	1.25	2.67	2.35	3.78	NS	3.61	4.52	2.53	U	0.09	1.23	0.45	0.31	0.39	0.52	1.04	0.36	0.37	1.07	0.95	0.09
Oxidation-Reduction Potential	NE	NE	U	-70.4	**175**	144.7	126.6	-16.0	56.36	22.9	79.6	NS	86.3	223.2	189.3	U	-117	56.9	53.6	47.2	-13.2	21.1	-18.1	57.0	36.8	22.8	51.3	-53.9

Sample	WDNR NR 140 Standards		MW-14		MW-15		MW-16		PZ-1													
Parameter Date	PAL	ES	06/01/16	09/20/16	06/01/16	09/20/16	06/02/16	09/22/16	06/19/08	08/21/09	12/07/09	03/10/10	06/04/10	12/16/10	06/22/11	06/21/12	01/18/13	10/22/14	07/01/15	06/01/16	09/23/16
cis-1,2-Dichloroethene	7.0	70	<0.41	<0.41	4.1	**13**	1.2	1.0	**0.97**	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.12	<0.12	<0.12	<0.12	<0.41	<0.41
trans-1,2-Dichloroethene	20	100	<0.35	<0.35	<0.35	<0.35	<0.35	<0.35	<0.89	<0.50	<0.50	<0.50	<0.50	<0.50	<0.50	<0.25	<0.25	<0.25	<0.25	<0.35	<0.35
Tetrachloroethene	0.5	5.0	**0.7**	**2.4**	**57**	**130**	**49**	**54**	**0.54**	<0.50	<0.50	<0.50	<0.50	**1.4 J**	<0.50	<0.17	**1.6**	<0.17	<0.17	<0.37	<0.37
Trichloroethene	0.5	5.0	<0.16	<0.16	**0.99**	**2.8**	**0.8**	**0.92**	<0.48	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.19	<0.19	<0.19	<0.19	<0.16	<0.16
Vinyl Chloride	0.02	0.2	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	U	<0.20	<0.20	<0.20	<0.20	<0.20	<0.20	<0.10	<0.10	<0.10	<0.10	<0.20	<0.20
Dissolved Oxygen (mg/l)	NE	NE	5.75	5.26	4.70	4.56	5.41	7.06	U	4.31	1.82	5.64	1.45	0.71	1.12	4.33	4.64	2.80	2.43	4.68	4.14
Oxidation-Reduction Potential	NE	NE	-29.1	0.3	-3.7	22.5	-39.2	102.1	U	-69.9	183	-76.8	71.8	-11.3	5.83	101	43.4	117.2	54.0	260.4	78.5

Notes: All values are in µg/l unless otherwise noted.
PAL - Preventative Action Limit
ES - Enforcement Standard
NE - Standard Not Established

NS - Not Sampled
NM - Not Measured
U Pre Injection Data (unknown)

BOLD - Result exceeds the PAL
BOLD - Result exceeds the ES

ET - Endpoint timeout caused by matrix interference.
J - Estimated value. Result between method detection limit and limit of quantification.
M - The MS and or MSD were outside control limits.
pH - The pH was outside range and the sample was adjusted.

Table 3 - Summary of Indoor Air Data for Detected Chlorinated Compounds Only - 2156 Rambling Rose

Sample Name	WDNR Residential VAL	2156 Rambling Rose	
Parameter Date	Indoor Air	12/02/15	03/31/16
1,2-Dichloroethane	1.1	<0.81	NA
cis-1,2-Dichloroethene	NS	<0.793	<0.793
trans-1,2-Dichloroethene	NS	<0.793	<0.793
Tetrachloroethene	42	5.30	4.84
Trichloroethene	2.1	<1.07	<1.07

Notes : All values in ug/m^3.
VAL - Vapor Action Level
NA - Not Analyzed
NS - No Standard
BOLD - Result exceeds the VAL

Table 4 - Summary of Soil Vapor Data for Chlorinated Compounds Only - Former Bask Dry Cleaners

Sample Name	WDNR Residential VRSL		SV-1	SV-1A	SV-1B					SV-2	SV-2A				
Parameter Date	Sub-Slab	Deep Soil	03/02/05	11/02/12	12/11/12	10/01/14	12/27/14	06/25/15	03/31/16	03/02/05	11/02/12	10/01/14	12/27/14	06/25/15	03/31/16
1,1-Dichloroethene	7,000	21,000	ND	16	<0.79	<7.9	<0.79	<0.79	NA	ND	<0.79	<16	<0.79	1.3	NA
cis-1,2-Dichloroethene	NC	NC	ND	<0.79	<0.79	<7.9	<0.79	<0.79	<0.79	ND	<0.79	<16	<0.79	<0.79	<0.79
trans-1,2-Dichloroethene	NC	NC	ND	<0.79	<0.79	<7.9	<0.79	<0.79	<0.79	ND	<0.79	<16	<0.79	<0.79	<0.79
Tetrachloroethene	1,400	4,200	29.64	2,000	880	2,800	600	1,200	621	5.03	3.3	**4,500**	390	3.5	1,790
Trichloroethene	70	210	ND	12	1.7	<11	<1.1	1.2	<0.51	ND	<1.1	**460**	29	<1.1	81.5

Sample Name	WDNR Residential VRSL		SV-3				SV-4				SV-5			
Parameter Date	Sub-Slab	Deep Soil	09/30/14	12/27/14	06/25/15	03/31/16	09/30/14	12/27/14	06/25/15	03/31/16	09/30/14	12/27/14	06/25/15	03/31/16
1,1-Dichloroethene	7,000	21,000	<3.2	<0.79	<0.79	NA	<40	<0.79	<3.2	NA	3.3	<0.79	<0.79	NA
cis-1,2-Dichloroethene	NC	NC	<3.2	<0.79	<0.79	<0.79	270	11	520	46.3	<0.79	<0.79	<0.79	<0.79
trans-1,2-Dichloroethene	NC	NC	<3.2	<0.79	<0.79	<0.79	310	10	120	<0.79	<0.79	<0.79	<0.79	<0.79
Tetrachloroethene	1,400	4,200	**7,500**	3,500	3,100	1,470	**81,000**	1,100	**16,000**	**8,870**	4.5	<1.4	2,700	6.07
Trichloroethene	70	210	120	35	14	15.4	**6,400**	160	**1,200**	**478**	<1.1	<1.1	120	1.73

Sample Name	WDNR Residential VRSL		SV-6				SV-7				SV-8			
Parameter Date	Sub-Slab	Deep Soil	09/30/14	12/27/14	06/25/15	03/31/16	09/30/14	12/27/14	06/25/15	03/31/16	09/30/14	12/27/14	06/25/15	03/31/16
1,1-Dichloroethene	7,000	21,000	1.3	<0.79	<0.79	NA	<20	<0.79	<0.79	NA	<7.9	<0.79	<0.79	NA
cis-1,2-Dichloroethene	NC	NC	<0.79	<0.79	<0.79	<0.79	<20	<0.79	<0.79	<0.79	<7.9	<0.79	<0.79	<0.79
trans-1,2-Dichloroethene	NC	NC	<0.79	<0.79	<0.79	<0.79	<20	<0.79	<0.79	<0.79	<7.9	<0.79	<0.79	<0.79
Tetrachloroethene	1,400	4,200	8.8	1.5	<1.4	3.69	750	110	68	10.9	<14	<1.4	5.0	1.73
Trichloroethene	70	210	<1.1	<1.1	<1.1	<1.1	140	27	17	1.17	<11	<1.1	<1.1	1.36

Sample Name	WDNR Residential VRSL		SV-9			SV-10			SV-11			SV-12			SV-13	SV-14	SV-15
Parameter Date	Sub-Slab	Deep Soil	12/27/14	06/25/15	03/31/16	12/27/14	06/25/15	03/31/16	12/27/14	06/25/15	03/31/16	06/25/15	07/28/15	03/31/16	03/31/16	03/31/16	03/31/16
1,1-Dichloroethene	7,000	21,000	<6.3	<0.79	NA	<0.79	<0.79	NA	<0.79	<0.79	NA	<3.2	< 0.79	NA	NA	NA	NA
cis-1,2-Dichloroethene	NC	NC	180	<0.79	<0.79	6.3	22	<0.79	<0.79	<0.79	<0.79	14	15	37.2	<0.79	<0.79	<0.79
trans-1,2-Dichloroethene	NC	NC	<6.3	<0.79	<0.79	1.3	1.3	<0.79	<0.79	<0.79	<0.79	4.4	5.2	<0.79	<0.79	<0.79	<0.79
Tetrachloroethene	1,400	4,200	**5,000**	81	5.79	750	3,900	2,200	3.2	5.3	2.46	**11,000**	**27,000**	**5,370**	407	5.98	47.9
Trichloroethene	70	210	91	<1.1	<1.1	33	190	27.0	<1.1	<1.1	<1.1	75	140	77.1	<1.1	<1.1	<1.1

Notes : All values in ug/m^3.
It is noted that 111-TCA was detected below standard at SV-7 on 12/27/14.
It is noted that Methylene Chloride was detected below standard at SV-4, SV-5 and SV-6 on 9/30/14.
VRSL - Vapor Risk Screening Level
BOLD - Result exceeds the Deep Soil VRSL

NA - Not Analyzed
NC - Not Calculated
ND - Not Detected

Table 5. Additional Well Install and Sampling Budget Summary - Former Bask Dry Celaners, Waukesha WI
16-Feb-17

			Contractors				
Task	KPRG Labor	Expenses	Analytical	Driller	IDW Disposal	Surveyor	Totals
1) Additional Requested Work Planning and Coordination	$1,941	$300	$0	$0	$0	$0	$2,241
2) New Well Installation Costs	$6,070	$1,080	$0	$22,500	$1,750	$1,200	$32,600
3) Additional Groundwater Sampling (2 Rounds)	$7,430	$2,210	$2,860	$0	$0	$0	$12,500
4) Additional Soil Vapor Sampling	$724	$185	$705	$0	$0	$0	$1,614
5) Additional Reporting	$2,772	$50	$0	$0	$0	$0	$2,822
6) Operation and Maintenance	$1,403	$60	$0	$5,450	$0	$0	$6,913
Totals	$20,340	$3,885	$3,565	$27,950	$1,750	$1,200	$58,690

ATTACHMENT 1
WELL LOGS AND CONSTRUCTION SUMMARIES

State of Wisconsin
Department of Natural Resources

SOIL BORING LOG INFORMATION

Form 4400-122 Rev. 7-98

Route To: Watershed / Wastewater ☐ Waste Management ☐
Remediation / Redevelopment ☑ Other ☐ _____

Facility/Project Name	License/Permit/Monitoring Number	Boring Number
former Bask Dry Cleaners		MW-14S

Boring Drilled By: Name of crew chief (first,last) and Firm	Date Drilling Started	Date Drilling Completed	Drilling Method
First Name: Adam Last Name: Sweet Firm: Horizon	12/01/2015	12/02/2015	Sonic

WI Unique Well No.	DNR Well ID No.	Well Name	Final Static Water Level	Surface Elevation	Borehole Diameter
		MW-14S	_____ Feet MSL	_____ Feet MSL	6 inches

Local Grid Origin (estimated:) or Boring Location
State Plane _____ N, _____ E
NE 1/4 of NE 1/4 of Section 36, T 7 N, R 19 E
Lat _____ Long _____

Local Grid Location
___ N ___ E
_____ Feet ___ S _____ Feet ___ W

Facility ID	County	County Code	Civil Town / City / or Village
268188800	Waukesha	68	Waukesha

Sample Number and Type	Sample Length Att. & Recovered (in)	Blow Counts	Depth in Feet (below ground surface)	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties: Compressive Strength	Moisture Content	Liquid Limit	Plasticity Index	P 200	RQD / Comments
				Grass over Dark Brown Top Soil, clayey,				0						
				some sand anad gravel.				0						
			2	Brown Silty Sand, fine to medium, trace										
				gravel, moist.				0						
			4					0						
								0						
			6					0						
								0						
			8					0						
								0						
			10	Brown Silty Sand, meduim, some clay, moist.				0						
								0						
			12	- increase gravel				0						
								0						
			14					0						
								0						
			16					0						
			18					0						
								0						
			20					0						
				- gravel and boulders, refusal										
			22	End of Boring at 22 feet. Refusal.										

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature	Firm
	KPRG and Associates, Inc.

State of Wisconsin
Department of Natural Resources

SOIL BORING LOG INFORMATION

Form 4400-122 Rev. 7-98

Route To: Watershed / Wastewater ☐ Waste Management ☐
Remediation / Redevelopment ☑ Other ☐ _____

Facility/Project Name	License/Permit/Monitoring Number	Boring Number
former Bask Dry Cleaners		MW-15S

Boring Drilled By: Name of crew chief (first,last) and Firm	Date Drilling Started	Date Drilling Completed	Drilling Method
First Name: Adam Last Name: Sweet Firm: Horizon	12/02/2015 (m m/d d/y y y y)	12/03/2015 (m m/d d/y y y y)	Sonic

WI Unique Well No.	DNR Well ID No.	Well Name	Final Static Water Level	Surface Elevation	Borehole Diameter
		MW-15S	_____ Feet MSL	_____ Feet MSL	6 inches

Local Grid Origin (estimated:) or Boring Location
State Plane _____ N, _____ E
NE 1/4 of NE 1/4 of Section 36, T 7 N, R 19 E
Lat _____ Long _____

Local Grid Location
___ N ___ E
_____ Feet ___ S _____ Feet ___ W

Facility ID	County	County Code	Civil Town / City / or Village
268188800	Waukesha	68	Waukesha

Sample Number and Type	Sample Length Att. & Recovered (in)	Blow Counts	Depth in Feet (below ground surface)	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties: Compressive Strength	Moisture Content	Liquid Limit	Plasticity Index	P 200	RQD / Comments
			0	Grass over Dark Brown Top Soil, clayey, some sand and gravel.				0						
			2	Brown Silty Sand, fine to medium, trace gravel, moist.				0						
			4					0						
			6	- increase gravel				0						
			8					0						
			10					0						
			12	Light Brown Fine Sand and Silt, v moist.				0						
			14					0						
			16					0						
			18					0						
			20					0						
			22	- gravel and boulders, refusal										
				End of Boring at 22 feet. Refusal.										

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature	Firm
	KPRG and Associates, Inc.

State of Wisconsin
Department of Natural Resources

SOIL BORING LOG INFORMATION

Form 4400-122 Rev. 7-98

Route To: Watershed / Wastewater ☐ Waste Management ☐
Remediation / Redevelopment ☑ Other ☐ _____

Facility/Project Name	License/Permit/Monitoring Number	Boring Number
former Bask Dry Cleaners		MW-14

Boring Drilled By: Name of crew chief (first,last) and Firm	Date Drilling Started	Date Drilling Completed	Drilling Method
First Name: Randy Last Name: Radke Firm: Cascade Drilling, L.P.	05/16/2016	05/17/2016	Sonic

WI Unique Well No.	DNR Well ID No.	Well Name	Final Static Water Level	Surface Elevation	Borehole Diameter
		MW-14	_____ Feet MSL	_____ Feet MSL	6 inches

Local Grid Origin (estimated:) or Boring Location
State Plane _____ N, _____ E
NE 1/4 of NE 1/4 of Section 36, T 7 N, R 19 E
Lat _____ Long _____

Local Grid Location
_____ Feet ___ N _____ Feet ___ E
_____ Feet ___ S _____ Feet ___ W

Facility ID	County	County Code	Civil Town / City / or Village
268188800	Waukesha	68	Waukesha

Sample Number and Type	Sample Length Att. & Recovered (in)	Blow Counts	Depth in Feet (below ground surface)	Soil/Rock Description And Geologic Origin For Each Major Unit	USCS	Graphic Log	Well Diagram	PID/FID	Soil Properties: Compressive Strength	Moisture Content	Liquid Limit	Plasticity Index	P 200	RQD / Comments
			2	Boring blind drilled.										
			4	See log for MW-14.										
			6											
			8											
			10											
			12											
			14											
			16											
			18											
			20											
			22											

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature	Firm
	KPRG and Associates, Inc.

Sample Number and Type	Sample Length Att. & Recovered (in)	Blow Counts	Depth in Feet (below ground surface)	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties: Compressive Strength	Soil Properties: Moisture Content	Soil Properties: Liquid Limit	Soil Properties: Plasticity Index	Soil Properties: P 200	RQD / Comments
			24											
			26	Boring blind drilled. See log for MW-14.										
			28											
			30											
			32	Brown, fine to coarse SAND and GRAVEL, trace cobbles, occasional more fine and more coarse seams, slightly moist.										
			34											
			36											
			38											
			40											
			42											
			44											
			46											
			48											
			50	Brown, medium to coarse SAND, trace GRAVEL, wet.										
			52	Brown, coarse SAND and fine to coarse sand, wet.										
			54											
			56	Brown, fine to medium SAND, trace silt and gravel, wet.										
			58											
			60											
			62	End of Boring at 60 feet.										

State of Wisconsin
Department of Natural Resources

SOIL BORING LOG INFORMATION

Form 4400-122 Rev. 7-98

Route To: Watershed / Wastewater ☐ Waste Management ☐
Remediation / Redevelopment ☑ Other ☐ _____

Facility/Project Name	License/Permit/Monitoring Number	Boring Number
former Bask Dry Cleaners		MW-15

Boring Drilled By: Name of crew chief (first,last) and Firm	Date Drilling Started	Date Drilling Completed	Drilling Method
First Name: Randy Last Name: Radke Firm: Cascade Drilling, L.P.	05/18/2016	05/18/2016	Sonic

WI Unique Well No.	DNR Well ID No.	Well Name	Final Static Water Level	Surface Elevation	Borehole Diameter
		MW-15	_____ Feet MSL	_____ Feet MSL	6 inches

Local Grid Origin (estimated:) or Boring Location
State Plane _____ N, _____ E
NE 1/4 of NE 1/4 of Section 36, T 7 N, R 19 E
Lat _____ Long _____

Local Grid Location
_____ Feet ___ N ___ Feet ___ E
_____ Feet ___ S _____ Feet ___ W

Facility ID	County	County Code	Civil Town / City / or Village
268188800	Waukesha	68	Waukesha

Sample Number and Type	Sample Length Att. & Recovered (in)	Blow Counts	Depth in Feet (below ground surface)	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties: Compressive Strength	Moisture Content	Liquid Limit	Plasticity Index	P 200	RQD / Comments
			2	Boring blind drilled to 25 feet.										
			4	See log for MW-15.										
			6											
			8											
			10											
			12											
			14											
			16											
			18											
			20											
			22											

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature	Firm
	KPRG and Associates, Inc.

This form is authorized by Chapters 281, 283, 289, 291, 293, 295, and 299, Wis. Stats. Completion of this form is mandatory. Failure to file this form may result in forfeiture of between $10 and $25,000, or inprisonment for up to one year, depending on the program and consuct invloved. Personally identifiable information on this form is not intended to be used for any other purpose. NOTE: See instructions for more information, including where the completed form should be sent.

Sample Number and Type	Sample Length Att. & Recovered (in)	Blow Counts	Depth in Feet (below ground surface)	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties: Compressive Strength	Soil Properties: Moisture Content	Soil Properties: Liquid Limit	Soil Properties: Plasticity Index	Soil Properties: P 200	RQD / Comments
			24	Boring blind drilled to 25 feet. See log for MW-15.										
			26	Brown, medium SAND to coarse GRAVEL trace sand and cobbles, slightly moist.										
			28											
			30											
			32											
			34											
			36											
			38											
			40											
			42											
			44	- moist										
			46	- increase moisture to very moist										
			48											
			50											
			52	Brown medium to coarse SAND and fine to coarse GRAVEL, trace fines, wet.										
			54											
			56	End of Boring at 55 feet.										
			58											
			60											
			62											

State of Wisconsin
Department of Natural Resources

SOIL BORING LOG INFORMATION

Form 4400-122 Rev. 7-98

Route To: Watershed / Wastewater ☐ Waste Management ☐
Remediation / Redevelopment ☑ Other ☐ _____

Facility/Project Name	License/Permit/Monitoring Number	Boring Number
former Bask Dry Cleaners		MW-16

Boring Drilled By: Name of crew chief (first,last) and Firm	Date Drilling Started	Date Drilling Completed	Drilling Method
First Name: Randy Last Name: Radke Firm: Cascade Drilling, L.P.	05/17/2016	05/17/2016	Sonic

WI Unique Well No.	DNR Well ID No.	Well Name	Final Static Water Level	Surface Elevation	Borehole Diameter
		MW-16	_____ Feet MSL	_____ Feet MSL	6 inches

Local Grid Origin (estimated:) or Boring Location
State Plane _____ N, _____ E
NE 1/4 of NE 1/4 of Section 36, T 7 N, R 19 E
Lat _____ Long _____

Local Grid Location
___ N ___ E
_____ Feet ___ S _____ Feet ___ W

Facility ID	County	County Code	Civil Town / City / or Village
268188800	Waukesha	68	Waukesha

Sample Number and Type	Sample Length Att. & Recovered (in)	Blow Counts	Depth in Feet (below ground surface)	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties: Compressive Strength	Moisture Content	Liquid Limit	Plasticity Index	P 200	RQD / Comments
			0	Grass and dark brown clayey top soil, sl moist.										
			2	Dark Brown, SILTY CLAY, some sand / gravel.										
			4	Brown SILTY CLAY, trace sand and gravel, moist.										
			6											
			8											
			10											
			12	Brown SILTY CLAY, some sang/gravel, sl moist.										
			14											
			16	Light Brown SILTY SAND, fine to medium, trace gravel, sl moist.										
			18	Light Brown SILT, sl moist.										
			20	Light Brown SAND and GRAVEL, fine to coarse, trace cobbles, sl moist. - occasional layers of coarser and finer matrix										
			22											

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature _____ Firm KPRG and Associates, Inc.

This form is authorized by Chapters 281, 283, 289, 291, 293, 295, and 299, Wis. Stats. Completion of this form is mandatory. Failure to file this form may result in forfeiture of between $10 and $25,000, or inprisonment for up to one year, depending on the program and consuct invloved. Personally identifiable information on this form is not intended to be used for any other purpose. NOTE: See instructions for more information, including where the completed form should be sent.

Sample		Blow Counts	Depth in Feet (below ground surface)	Soil/Rock Description And Geologic Origin For Each Major Unit	U S C S	Graphic Log	Well Diagram	PID/FID	Soil Properties					RQD / Comments
Number and Type	Length Att. & Recovered (in)								Compressive Strength	Moisture Content	Liquid Limit	Plasticity Index	P 200	
			24											
			26											
			28											
			30											
			32	Brown, fine to coarse SAND and GRAVEL, trace cobbles, occasional more fine and more coarse seams, slightly moist.										
			34											
			36											
			38											
			40											
			42											
			44											
			46											
			48											
			50											
			52	Brown, SAND, fine to medium, some silt. wet.										
			54											
			56											
			58	Brown medium SAND to medium GRAVEL layered with GRAVEL, wet.										
			60											
			62	End of Boring at 60 feet.										

State of Wisconsin
Department of Natural Resources

Route to: Watershed/Wastewater ☐ Waste Management ☐
Remediation/Redevelopment ☒ Other ☐ _____

MONITORING WELL CONSTRUCTION
Form 4400-113A Rev. 7-98

Facility/Project Name: former Bask Dry Cleaners	Local Grid Location of Well: ____ ft. ☐N ☐S, ____ ft. ☐E ☐W	Well Name: MW-14S
Facility License, Permit or Monitoring No.	Local Grid Origin ☐ (estimated: ☐) or Well Location ☐ Lat. ° ' " Long. ° ' " or	Wis. Unique Well No. / DNR Well ID No.
Facility ID: 268188800	St. Plane ____ ft. N, ____ ft. E. S/C/N	Date Well Installed: 12/02/2015 (m m d d y y y y)
Type of Well: Well Code 11 / mw	Section Location of Waste/Source: NE 1/4 of NE 1/4 of Sec. 36, T. 7 N, R. 19 ☒E ☐W	Well Installed By: Name (first, last) and Firm: Adam Sweet / Horizon
Distance from Waste/Source ____ ft. / Enf. Stds. Apply ☐	Location of Well Relative to Waste/Source: u ☐ Upgradient s ☐ Sidegradient d ☐ Downgradient n ☐ Not Known	Gov. Lot Number: ____

A. Protective pipe, top elevation ____ ft. MSL
B. Well casing, top elevation ____ ft. MSL
C. Land surface elevation ____ ft. MSL
D. Surface seal, bottom ____ ft. MSL or 1 ft.

12. USCS classification of soil near screen:
GP ☐ GM ☐ GC ☐ GW ☐ SW ☐ SP ☒
SM ☐ SC ☐ ML ☐ MH ☐ CL ☐ CH ☐
Bedrock ☐

13. Sieve analysis performed? ☐ Yes ☒ No

14. Drilling method used: Rotary ☐ 50; Hollow Stem Auger ☐ 41; Other ☒ (Sonic)

15. Drilling fluid used: Water ☐ 02; Air ☐ 01; Drilling Mud ☐ 03; None ☒ 99

16. Drilling additives used? ☐ Yes ☒ No
Describe ____

17. Source of water (attach analysis, if required): ____

E. Bentonite seal, top ____ ft. MSL or 1 ft.
F. Fine sand, top ____ ft. MSL or 13 ft.
G. Filter pack, top ____ ft. MSL or 13 ft.
H. Screen joint, top ____ ft. MSL or 15 ft.
I. Well bottom ____ ft. MSL or 30 ft.
J. Filter pack, bottom ____ ft. MSL or 30 ft.
K. Borehole, bottom ____ ft. MSL or 30 ft.
L. Borehole, diameter 6 in.
M. O.D. well casing ____ in.
N. I.D. well casing 2 in.



1. Cap and lock? ☒ Yes ☐ No
2. Protective cover pipe:
a. Inside diameter: 8 in.
b. Length: 1 ft.
c. Material: Steel ☒ 04; Other ☐ ____
d. Additional protection? ☐ Yes ☐ No
If yes, describe: ____
3. Surface seal: Bentonite ☐ 30; Concrete ☒ 01; Other ☐ ____
4. Material between well casing and protective pipe: Bentonite ☐ 30; Other ☐ ____
5. Annular space seal: a. Granular/Chipped Bentonite ☒ 33
b. ____ Lbs/gal mud weight . . . Bentonite-sand slurry ☐ 35
c. ____ Lbs/gal mud weight . . . . . Bentonite slurry ☐ 31
d. ____ % Bentonite . . . . . Bentonite-cement grout ☐ 50
e. ____ Ft^3 volume added for any of the above
f. How installed: Tremie ☐ 01; Tremie pumped ☐ 02; Gravity ☒ 08
6. Bentonite seal: a. Bentonite granules ☐ 33
b. ☐1/4 in. ☒3/8 in. ☐1/2 in. Bentonite chips ☒ 32
c. ____ Other ☐ ____
7. Fine sand material: Manufacturer, product name & mesh size
a. ____
b. Volume added ____ ft^3
8. Filter pack material: Manufacturer, product name & mesh size
a. ____
b. Volume added ____ ft^3
9. Well casing: Flush threaded PVC schedule 40 ☒ 23; Flush threaded PVC schedule 80 ☐ 24; Other ☐ ____
10. Screen material: PVC - Sch 40
a. Screen type: Factory cut ☒ 11; Continuous slot ☐ 01; Other ☐ ____
b. Manufacturer ____
c. Slot size: 0.010 in.
d. Slotted length: 15 ft.
11. Backfill material (below filter pack): None ☒ 14; Other ☐ ____

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature: [signature] Firm: KPRG and Associates, Inc.

Please complete both Forms 4400-113A and 4400-113B and return them to the appropriate DNR office and bureau. Completion of these reports is required by chs. 160, 281, 283, 289, 291, 292, 293, 295, and 299, Wis. Stats., and ch. NR 141, Wis. Adm. Code. In accordance with chs. 281, 289, 291, 292, 293, 295, and 299, Wis. Stats., failure to file these forms may result in a forfeiture of between $10 and $25,000, or imprisonment for up to one year, depending on the program and conduct involved. Personally identifiable information on these forms is not intended to be used for any other purpose. NOTE: See the instructions for more information, including where the completed forms should be sent.

State of Wisconsin
Department of Natural Resources

Route to: Watershed/Wastewater ☐ Waste Management ☐
Remediation/Redevelopment [x] Other ☐ _____

MONITORING WELL CONSTRUCTION
Form 4400-113A Rev. 7-98

Facility/Project Name: former Bask Dry Cleaners	Local Grid Location of Well: _____ ft. ☐N. ☐S. _____ ft. ☐E. ☐W.	Well Name: MW-15S
Facility License, Permit or Monitoring No.	Local Grid Origin ☐ (estimated: ☐) or Well Location ☐ Lat. ° ' " Long. ° ' " or	Wis. Unique Well No. / DNR Well ID No.
Facility ID: 268188800	St. Plane _____ ft. N, _____ ft. E. S/C/N	Date Well Installed: 12/03/2015 (m m d d y y y y)
Type of Well: Well Code 11 / mw	Section Location of Waste/Source: NE 1/4 of NE 1/4 of Sec. 36, T. 7 N, R. 19 ☒E ☐W	Well Installed By: Name (first, last) and Firm: Adam Sweet / Horizon
Distance from Waste/Source _____ ft. / Enf. Stds. Apply ☐	Location of Well Relative to Waste/Source: u ☐ Upgradient s ☐ Sidegradient d ☐ Downgradient n ☐ Not Known / Gov. Lot Number	

A. Protective pipe, top elevation _____ ft. MSL
B. Well casing, top elevation _____ ft. MSL
C. Land surface elevation _____ ft. MSL
D. Surface seal, bottom _____ ft. MSL or 1 ft.

12. USCS classification of soil near screen:
GP ☐ GM ☐ GC ☐ GW ☐ SW ☐ SP ☒
SM ☐ SC ☐ ML ☐ MH ☐ CL ☐ CH ☐
Bedrock ☐

13. Sieve analysis performed? ☐ Yes ☒ No

14. Drilling method used: Rotary ☐ 50 / Hollow Stem Auger ☐ 41 / Other ☒ (SONIC)

15. Drilling fluid used: Water ☐ 02 / Air ☐ 01 / Drilling Mud ☐ 03 / None ☒ 99

16. Drilling additives used? ☐ Yes ☒ No
Describe _____

17. Source of water (attach analysis, if required):

E. Bentonite seal, top _____ ft. MSL or 1 ft.
F. Fine sand, top _____ ft. MSL or 8 ft.
G. Filter pack, top _____ ft. MSL or 9 ft.
H. Screen joint, top _____ ft. MSL or 10 ft.
I. Well bottom _____ ft. MSL or 25 ft.
J. Filter pack, bottom _____ ft. MSL or 25 ft.
K. Borehole, bottom _____ ft. MSL or 35 ft.
L. Borehole, diameter 6 in.
M. O.D. well casing _____ in.
N. I.D. well casing 2 in.



1. Cap and lock? ☒ Yes ☐ No
2. Protective cover pipe:
a. Inside diameter: 8 in.
b. Length: 1 ft.
c. Material: Steel ☒ 04 / Other ☐ _____
d. Additional protection? ☐ Yes ☐ No
If yes, describe: _____
3. Surface seal: Bentonite ☐ 30 / Concrete ☒ 01 / Other ☐ _____
4. Material between well casing and protective pipe: Bentonite ☐ 30 / Other ☐ _____
5. Annular space seal: a. Granular/Chipped Bentonite ☒ 33
b. _____ Lbs/gal mud weight . . . Bentonite-sand slurry ☐ 35
c. _____ Lbs/gal mud weight . . . . . Bentonite slurry ☐ 31
d. _____ % Bentonite . . . . . Bentonite-cement grout ☐ 50
e. _____ Ft^3 volume added for any of the above
f. How installed: Tremie ☐ 01 / Tremie pumped ☐ 02 / Gravity ☒ 08
6. Bentonite seal: a. Bentonite granules ☐ 33
b. ☐1/4 in. ☒3/8 in. ☐1/2 in. Bentonite chips ☒ 32
c. _____ Other ☐ _____
7. Fine sand material: Manufacturer, product name & mesh size
a. _____
b. Volume added _____ ft^3
8. Filter pack material: Manufacturer, product name & mesh size
a. _____
b. Volume added _____ ft^3
9. Well casing: Flush threaded PVC schedule 40 ☒ 23 / Flush threaded PVC schedule 80 ☐ 24 / Other ☐ _____
10. Screen material: PVC - Sch 40
a. Screen type: Factory cut ☒ 11 / Continuous slot ☐ 01 / Other ☐ _____
b. Manufacturer _____
c. Slot size: 0.010 in.
d. Slotted length: 15 ft.
11. Backfill material (below filter pack): NATIVE HEAVE — None ☐ 14 / Other ☐ _____

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature	Firm
[signature]	KPRG and Associates, Inc.

Please complete both Forms 4400-113A and 4400-113B and return them to the appropriate DNR office and bureau. Completion of these reports is required by chs. 160, 281, 283, 289, 291, 292, 293, 295, and 299, Wis. Stats., and ch. NR 141, Wis. Adm. Code. In accordance with chs. 281, 289, 291, 292, 293, 295, and 299, Wis. Stats., failure to file these forms may result in a forfeiture of between $10 and $25,000, or imprisonment for up to one year, depending on the program and conduct involved. Personally identifiable information on these forms is not intended to be used for any other purpose. NOTE: See the instructions for more information, including where the completed forms should be sent.

State of Wisconsin
Department of Natural Resources

Route to: Watershed/Wastewater ☐ Waste Management ☐
Remediation/Redevelopment ☒ Other ☐ _____

MONITORING WELL CONSTRUCTION

Form 4400-113A Rev. 7-98

Facility/Project Name: former Bask Dry Cleaners	Local Grid Location of Well: _____ ft. ☐N. ☐S. _____ ft. ☐E. ☐W.	Well Name: MW-14
Facility License, Permit or Monitoring No.	Local Grid Origin ☐ (estimated: ☐) or Well Location ☐ Lat. ° ' " Long. ° ' " or	Wis. Unique Well No. / DNR Well ID No.
Facility ID: 268188800	St. Plane _____ ft. N, _____ ft. E. S/C/N	Date Well Installed: 05/17/2016 (m m d d y y y y)
Type of Well: Well Code 11 / mw	Section Location of Waste/Source: NE 1/4 of NE 1/4 of Sec. 36, T. 7 N, R. 19 ☒E ☐W	Well Installed By: Name (first, last) and Firm: Randy Radke / Cascade Drilling
Distance from Waste/Source _____ ft. / Enf. Stds. Apply ☐	Location of Well Relative to Waste/Source: u ☐ Upgradient s ☐ Sidegradient d ☐ Downgradient n ☐ Not Known	Gov. Lot Number: _____



A. Protective pipe, top elevation _____ ft. MSL
B. Well casing, top elevation _____ ft. MSL
C. Land surface elevation _____ ft. MSL
D. Surface seal, bottom _____ ft. MSL or 1 ft.

12. USCS classification of soil near screen:
GP ☐ GM ☐ GC ☐ GW ☐ SW ☐ SP ☒
SM ☐ SC ☐ ML ☐ MH ☐ CL ☐ CH ☐
Bedrock ☐

13. Sieve analysis performed? ☐ Yes ☒ No

14. Drilling method used: Rotary ☐ 50 / Hollow Stem Auger ☐ 41 / Other ☒ SONIC

15. Drilling fluid used: Water ☐ 02 / Air ☐ 01 / Drilling Mud ☐ 03 / None ☒ 99

16. Drilling additives used? ☐ Yes ☒ No
Describe _____

17. Source of water (attach analysis, if required):
_____

E. Bentonite seal, top _____ ft. MSL or 1 ft.
F. Fine sand, top _____ ft. MSL or 47 ft.
G. Filter pack, top _____ ft. MSL or 47 ft.
H. Screen joint, top _____ ft. MSL or 49 ft.
I. Well bottom _____ ft. MSL or 59 ft.
J. Filter pack, bottom _____ ft. MSL or 59 ft.
K. Borehole, bottom _____ ft. MSL or 59 ft.
L. Borehole, diameter 6 in.
M. O.D. well casing _____ in.
N. I.D. well casing 2 in.

1. Cap and lock? ☒ Yes ☐ No
2. Protective cover pipe:
a. Inside diameter: 8 in.
b. Length: 1 ft.
c. Material: _____ Steel ☒ 04 / Other ☐
d. Additional protection? ☐ Yes ☐ No
If yes, describe: _____
3. Surface seal: _____ Bentonite ☐ 30 / Concrete ☒ 01 / Other ☐
4. Material between well casing and protective pipe: _____ Bentonite ☐ 30 / Other ☐
5. Annular space seal: a. Granular/Chipped Bentonite ☒ 33
b. _____ Lbs/gal mud weight . . . Bentonite-sand slurry ☐ 35
c. _____ Lbs/gal mud weight . . . . . Bentonite slurry ☐ 31
d. _____ % Bentonite . . . . . Bentonite-cement grout ☐ 50
e. _____ Ft^3 volume added for any of the above
f. How installed: Tremie ☐ 01 / Tremie pumped ☐ 02 / Gravity ☒ 08
6. Bentonite seal: a. Bentonite granules ☐ 33
b. ☐1/4 in. ☒3/8 in. ☐1/2 in. Bentonite chips ☒ 32
c. _____ Other ☐
7. Fine sand material: Manufacturer, product name & mesh size
a. _____
b. Volume added _____ ft^3
8. Filter pack material: Manufacturer, product name & mesh size
a. _____
b. Volume added _____ ft^3
9. Well casing: Flush threaded PVC schedule 40 ☒ 23 / Flush threaded PVC schedule 80 ☐ 24 / Other ☐
10. Screen material: PVC Sch 40
a. Screen type: Factory cut ☒ 11 / Continuous slot ☐ 01 / Other ☐
b. Manufacturer _____
c. Slot size: 0.010 in.
d. Slotted length: 10 ft.
11. Backfill material (below filter pack): _____ None ☒ 14 / Other ☐

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature _____ Firm: KPRG and Associates, Inc.

Please complete both Forms 4400-113A and 4400-113B and return them to the appropriate DNR office and bureau. Completion of these reports is required by chs. 160, 281, 283, 289, 291, 292, 293, 295, and 299, Wis. Stats., and ch. NR 141, Wis. Adm. Code. In accordance with chs. 281, 289, 291, 292, 293, 295, and 299, Wis. Stats., failure to file these forms may result in a forfeiture of between $10 and $25,000, or imprisonment for up to one year, depending on the program and conduct involved. Personally identifiable information on these forms is not intended to be used for any other purpose. NOTE: See the instructions for more information, including where the completed forms should be sent.

State of Wisconsin
Department of Natural Resources

Route to: Watershed/Wastewater ☐ Waste Management ☐
Remediation/Redevelopment ☒ Other ☐ _____

MONITORING WELL CONSTRUCTION

Form 4400-113A Rev. 7-98

Facility/Project Name: former Bask Dry Cleaners	Local Grid Location of Well: _____ ft. ☐N. ☐S. _____ ft. ☐E. ☐W.	Well Name: MW-15
Facility License, Permit or Monitoring No.	Local Grid Origin ☐ (estimated: ☐) or Well Location ☐ Lat. ° ' " Long. ° ' " or	Wis. Unique Well No. / DNR Well ID No.
Facility ID: 268188800	St. Plane _____ ft. N, _____ ft. E. S/C/N	Date Well Installed: 05/18/2016 (m m d d y y y y)
Type of Well: Well Code 11 / mw	Section Location of Waste/Source: NE 1/4 of NE 1/4 of Sec. 36, T. 7 N, R. 19 ☐E ☐W	Well Installed By: Name (first, last) and Firm: Randy Radke / Cascade Drilling
Distance from Waste/Source _____ ft. / Enf. Stds. Apply ☐	Location of Well Relative to Waste/Source: u ☐ Upgradient s ☐ Sidegradient d ☐ Downgradient n ☐ Not Known	Gov. Lot Number

A. Protective pipe, top elevation _____ ft. MSL
B. Well casing, top elevation _____ ft. MSL
C. Land surface elevation _____ ft. MSL
D. Surface seal, bottom _____ ft. MSL or 1 ft.

12. USCS classification of soil near screen:
GP ☐ GM ☐ GC ☐ GW ☐ SW ☐ SP ☒
SM ☐ SC ☐ ML ☐ MH ☐ CL ☐ CH ☐
Bedrock ☐

13. Sieve analysis performed? ☐ Yes ☒ No

14. Drilling method used: Rotary ☐ 50
Hollow Stem Auger ☐ 41
SONIC Other ☒

15. Drilling fluid used: Water ☐ 02 Air ☐ 01
Drilling Mud ☐ 03 None ☒ 99

16. Drilling additives used? ☐ Yes ☒ No

Describe _____

17. Source of water (attach analysis, if required):

E. Bentonite seal, top _____ ft. MSL or 1 ft.
F. Fine sand, top _____ ft. MSL or 44 ft.
G. Filter pack, top _____ ft. MSL or 44 ft.
H. Screen joint, top _____ ft. MSL or 46 ft.
I. Well bottom _____ ft. MSL or 56 ft.
J. Filter pack, bottom _____ ft. MSL or 56 ft.
K. Borehole, bottom _____ ft. MSL or 56 ft.
L. Borehole, diameter _____ in.
M. O.D. well casing _____ in.
N. I.D. well casing _____ in.



1. Cap and lock? ☒ Yes ☐ No
2. Protective cover pipe:
a. Inside diameter: 8 in.
b. Length: 1 ft.
c. Material: Steel ☒ 04 Other ☐
d. Additional protection? ☐ Yes ☐ No
If yes, describe: _____
3. Surface seal: Bentonite ☐ 30 Concrete ☒ 01 Other ☐
4. Material between well casing and protective pipe: Bentonite ☐ 30 Other ☐
5. Annular space seal: a. Granular/Chipped Bentonite ☒ 33
b. _____ Lbs/gal mud weight . . . Bentonite-sand slurry ☐ 35
c. _____ Lbs/gal mud weight . . . . . Bentonite slurry ☐ 31
d. _____ % Bentonite . . . . . Bentonite-cement grout ☐ 50
e. _____ Ft^3 volume added for any of the above
f. How installed: Tremie ☐ 01 Tremie pumped ☐ 02 Gravity ☒ 08
6. Bentonite seal: a. Bentonite granules ☐ 33
b. ☐1/4 in. ☐3/8 in. ☐1/2 in. Bentonite chips ☒ 32
c. _____ Other ☐
7. Fine sand material: Manufacturer, product name & mesh size
a. _____
b. Volume added _____ ft^3
8. Filter pack material: Manufacturer, product name & mesh size
a. _____
b. Volume added _____ ft^3
9. Well casing: Flush threaded PVC schedule 40 ☒ 23 Flush threaded PVC schedule 80 ☐ 24 Other ☐
10. Screen material: PVC Sch 40
a. Screen type: Factory cut ☒ 11 Continuous slot ☐ 01 Other ☐
b. Manufacturer _____
c. Slot size: 0.010 in.
d. Slotted length: 10 ft.
11. Backfill material (below filter pack): None ☒ 14 Other ☐

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature _____ Firm: KPRG and Associates, Inc.

Please complete both Forms 4400-113A and 4400-113B and return them to the appropriate DNR office and bureau. Completion of these reports is required by chs. 160, 281, 283, 289, 291, 292, 293, 295, and 299, Wis. Stats., and ch. NR 141, Wis. Adm. Code. In accordance with chs. 281, 289, 291, 292, 293, 295, and 299, Wis. Stats., failure to file these forms may result in a forfeiture of between $10 and $25,000, or imprisonment for up to one year, depending on the program and conduct involved. Personally identifiable information on these forms is not intended to be used for any other purpose. NOTE: See the instructions for more information, including where the completed forms should be sent.

State of Wisconsin
Department of Natural Resources

Route to: Watershed/Wastewater ☐ Waste Management ☐
Remediation/Redevelopment ☒ Other ☐

MONITORING WELL CONSTRUCTION

Form 4400-113A Rev. 7-98

Facility/Project Name: former Bask Dry Cleaners	Local Grid Location of Well ☐ N. ☐ S. ft. ☐ E. ☐ W. ft.	Well Name: MW-16
Facility License, Permit or Monitoring No.	Local Grid Origin ☐ (estimated: ☐) or Well Location ☐ Lat. ° ' " Long. ° ' " or	Wis. Unique Well No. / DNR Well ID No.
Facility ID: 268188800	St. Plane ft. N, ft. E. S/C/N	Date Well Installed: 05 / 18 / 2016 (m m / d d / y y y y)
Type of Well: Well Code 11 / mw	Section Location of Waste/Source: NE 1/4 of NE 1/4 of Sec. 36, T. 7 N, R. 19 ☐ E ☐ W	Well Installed By: Name (first, last) and Firm: Randy Radke / Cascade Drilling
Distance from Waste/Source ft. / Enf. Stds. Apply ☐	Location of Well Relative to Waste/Source: u ☐ Upgradient s ☐ Sidegradient d ☐ Downgradient n ☐ Not Known	Gov. Lot Number

A. Protective pipe, top elevation ft. MSL
B. Well casing, top elevation ft. MSL
C. Land surface elevation ft. MSL
D. Surface seal, bottom ft. MSL or 1 ft.

12. USCS classification of soil near screen:
GP ☐ GM ☐ GC ☐ GW ☐ SW ☐ SP ☒
SM ☐ SC ☐ ML ☐ MH ☐ CL ☐ CH ☐
Bedrock ☐

13. Sieve analysis performed? ☐ Yes ☒ No

14. Drilling method used: Rotary ☐ 50 Hollow Stem Auger ☐ 41 Other ☒
Sonic

15. Drilling fluid used: Water ☐ 02 Air ☐ 01 Drilling Mud ☐ 03 None ☒ 99

16. Drilling additives used? ☐ Yes ☒ No
Describe

17. Source of water (attach analysis, if required):

E. Bentonite seal, top ft. MSL or 1 ft.
F. Fine sand, top ft. MSL or ft.
G. Filter pack, top ft. MSL or 47.5 ft.
H. Screen joint, top ft. MSL or 50 ft.
I. Well bottom ft. MSL or 60 ft.
J. Filter pack, bottom ft. MSL or 60 ft.
K. Borehole, bottom ft. MSL or 60 ft.
L. Borehole, diameter 6 in.
M. O.D. well casing in.
N. I.D. well casing 2 in.

1. Cap and lock? ☒ Yes ☐ No
2. Protective cover pipe:
a. Inside diameter: 8 in.
b. Length: 1 ft.
c. Material: Steel ☒ 04 Other ☐
d. Additional protection? ☐ Yes ☐ No
If yes, describe:
3. Surface seal: Bentonite ☐ 30 Concrete ☒ 01 Other ☐
4. Material between well casing and protective pipe: Bentonite ☐ 30 Other ☐
5. Annular space seal: a. Granular/Chipped Bentonite ☒ 33
b. Lbs/gal mud weight . . . Bentonite-sand slurry ☐ 35
c. Lbs/gal mud weight . . . . . Bentonite slurry ☐ 31
d. % Bentonite . . . . . Bentonite-cement grout ☐ 50
e. Ft³ volume added for any of the above
f. How installed: Tremie ☐ 01 Tremie pumped ☐ 02 Gravity ☒ 08
6. Bentonite seal: a. Bentonite granules ☐ 33
b. ☐ 1/4 in. ☒ 3/8 in. ☐ 1/2 in. Bentonite chips ☒ 32
c. Other ☐
7. Fine sand material: Manufacturer, product name & mesh size
a.
b. Volume added ft³
8. Filter pack material: Manufacturer, product name & mesh size
a.
b. Volume added ft³
9. Well casing: Flush threaded PVC schedule 40 ☒ 23 Flush threaded PVC schedule 80 ☐ 24 Other ☐
10. Screen material: PVC Sch 40
a. Screen type: Factory cut ☒ 11 Continuous slot ☐ 01 Other ☐
b. Manufacturer
c. Slot size: 0.010 in.
d. Slotted length: 10 ft.
11. Backfill material (below filter pack): None ☒ 14 Other ☐

I hereby certify that the information on this form is true and correct to the best of my knowledge.

Signature: Todd Orff Firm: KPRG and Associates, Inc.

Please complete both Forms 4400-113A and 4400-113B and return them to the appropriate DNR office and bureau. Completion of these reports is required by chs. 160, 281, 283, 289, 291, 292, 293, 295, and 299, Wis. Stats., and ch. NR 141, Wis. Adm. Code. In accordance with chs. 281, 289, 291, 292, 293, 295, and 299, Wis. Stats., failure to file these forms may result in a forfeiture of between $10 and $25,000, or imprisonment for up to one year, depending on the program and conduct involved. Personally identifiable information on these forms is not intended to be used for any other purpose. NOTE: See the instructions for more information, including where the completed forms should be sent.

State of Wisconsin
Department of Natural Resources

MONITORING WELL DEVELOPMENT

Form 4400-113B Rev. 7-98

Route to: Watershed/Wastewater ☐ Waste Management ☐
Remediation/Redevelopment ☒ Other ☐ _____

Facility/Project Name	County Name	Well Name
Former Bask Dry Cleaners	Waukesha	MW 140
Facility License, Permit or Monitoring Number	**County Code**	**Wis. Unique Well Number**	**DNR Well ID Number**
	68	_____	___

1. Can this well be purged dry? ☐ Yes ☒ No

2. Well development method

surged with bailer and bailed	☐ 41
surged with bailer and pumped	☐ 61
surged with block and bailed	☐ 42
surged with block and pumped	☒ 62
surged with block, bailed and pumped	☐ 70
compressed air	☐ 20
bailed only	☐ 10
pumped only	☐ 51
pumped slowly	☐ 50
Other _____	☐

3. Time spent developing well 55 min.

4. Depth of well (from top of well casing) 59.3 ft.

5. Inside diameter of well 2.06 in.

6. Volume of water in filter pack and well casing ___.__ gal.

7. Volume of water removed from well 55.0 gal.

8. Volume of water added (if any) 0.0 gal.

9. Source of water added _____

10. Analysis performed on water added? (If yes, attach results) ☐ Yes ☒ No

	Before Development	After Development
11. Depth to Water (from top of well casing)	a. 47.75 ft.	47.75 ft.
Date	b. 5/19/2016 (m m d d y y y y)	05/19/2016 (m m d d y y y y)
Time	c. 10:00 ☒ a.m. ☐ p.m.	10:55 ☒ a.m. ☐ p.m.
12. Sediment in well bottom	___.__ inches	___.__ inches
13. Water clarity	Clear ☐ 10 Turbid ☒ 15 (Describe) Turbid Br.	Clear ☒ 20 Turbid ☐ 25 (Describe) Clear
Fill in if drilling fluids were used and well is at solid waste facility:		
14. Total suspended solids	_____.__ mg/l	_____.__ mg/l
15. COD	_____.__ mg/l	_____.__ mg/l

16. Well developed by: Name (first, last) and Firm
First Name: Randy Last Name: Radke
Firm: Cascade Drilling

17. Additional comments on development:

Name and Address of Facility Contact/Owner/Responsible Party
First Name: _____ Last Name: _____
Facility/Firm: _____
Street: _____
City/State/Zip: _____

I hereby certify that the above information is true and correct to the best of my knowledge.
Signature: Randy Radke
Print Name: Randy Radke
Firm: Cascade Drilling.

NOTE: See instructions for more information including a list of county codes and well type codes.

State of Wisconsin
Department of Natural Resources

MONITORING WELL DEVELOPMENT

Form 4400-113B Rev. 7-98

Route to: Watershed/Wastewater ☐ Waste Management ☐
Remediation/Redevelopment ☒ Other ☐ _____

Facility/Project Name	County Name	Well Name
Former Bost Dry Cleaners	Waukesha	MW-15D
Facility License, Permit or Monitoring Number	**County Code**	**Wis. Unique Well Number**	**DNR Well ID Number**
	68	_____	___

1. Can this well be purged dry? ☐ Yes ☒ No

2. Well development method

surged with bailer and bailed	☐ 41
surged with bailer and pumped	☐ 61
surged with block and bailed	☐ 42
surged with block and pumped	☒ 62
surged with block, bailed and pumped	☐ 70
compressed air	☐ 20
bailed only	☐ 10
pumped only	☐ 51
pumped slowly	☐ 50
Other _____	☐

3. Time spent developing well _____ min.

4. Depth of well (from top of well casing) 56.0 ft.

5. Inside diameter of well 2.06 in.

6. Volume of water in filter pack and well casing ____.__ gal.

7. Volume of water removed from well 55.0 gal.

8. Volume of water added (if any) 00.0 gal.

9. Source of water added _____

10. Analysis performed on water added? (If yes, attach results) ☐ Yes ☒ No

	Before Development	After Development
11. Depth to Water (from top of well casing)	a. 43.21 ft.	43.21 ft.
Date	b. 05/19/2016 (m m d d y y y y)	05/19/2016 (m m d d y y y y)
Time	c. 9:00 ☒ a.m. ☐ p.m.	9:46 ☒ a.m. ☐ p.m.
12. Sediment in well bottom	0.1 inches	0.0 inches
13. Water clarity	Clear ☐ 10 Turbid ☒ 15 (Describe) Turbid/br	Clear ☒ 20 Turbid ☐ 25 (Describe) clear
14. Total suspended solids	____.__ mg/l	____.__ mg/l
15. COD	____.__ mg/l	____.__ mg/l

Fill in if drilling fluids were used and well is at solid waste facility:

16. Well developed by: Name (first, last) and Firm
First Name: Randy Last Name: Radke
Firm: Cascade Drilling

17. Additional comments on development:

Name and Address of Facility Contact/Owner/Responsible Party
First Name: _____ Last Name: _____
Facility/Firm: _____
Street: _____
City/State/Zip: _____

I hereby certify that the above information is true and correct to the best of my knowledge.
Signature: Randy Radke
Print Name: Randy Radke
Firm: Cascade Drilling.

NOTE: See instructions for more information including a list of county codes and well type codes.

State of Wisconsin
Department of Natural Resources

MONITORING WELL DEVELOPMENT

Form 4400-113B Rev. 7-98

Route to: Watershed/Wastewater ☐ Waste Management ☐
Remediation/Redevelopment ☒ Other ☐ _____

Facility/Project Name	County Name	Well Name
Former Bask Dry Cleaners	Waukesha	MW-16
Facility License, Permit or Monitoring Number	**County Code**	**Wis. Unique Well Number**	**DNR Well ID Number**
	68		

1. Can this well be purged dry? ☐ Yes ☒ No

2. Well development method

surged with bailer and bailed	☐	41
surged with bailer and pumped	☐	61
surged with block and bailed	☐	42
surged with block and pumped	☒	62
surged with block, bailed and pumped	☐	70
compressed air	☐	20
bailed only	☐	10
pumped only	☐	51
pumped slowly	☐	50
Other _____	☐	

3. Time spent developing well 1hr 10 min.

4. Depth of well (from top of well casing) 59.9 ft.

5. Inside diameter of well 2.06 in.

6. Volume of water in filter pack and well casing ___.__ gal.

7. Volume of water removed from well 53.0 gal.

8. Volume of water added (if any) 0.0 gal.

9. Source of water added _____

10. Analysis performed on water added? ☐ Yes ☒ No
(If yes, attach results)

	Before Development	After Development
11. Depth to Water (from top of well casing)	a. 43.18 ft.	43.23 ft.
Date	b. 05/19/2016 (m m d d y y y y)	05/19/2016
Time	c. 7:10 ☐ a.m. ☒ p.m.	8:40 ☒ a.m. ☐ p.m.
12. Sediment in well bottom	0.2 inches	0.0 inches
13. Water clarity	Clear ☐ 10 Turbid ☒ 15	Clear ☒ 20 Turbid ☐ 25
	(Describe) Turbid, brn	(Describe) clear

Fill in if drilling fluids were used and well is at solid waste facility:

14. Total suspended solids	____.__ mg/l	____.__ mg/l
15. COD	____.__ mg/l	____.__ mg/l

16. Well developed by: Name (first, last) and Firm
First Name: Randy Last Name: Radke
Firm: Cascade Drilling

17. Additional comments on development:

Name and Address of Facility Contact/Owner/Responsible Party
First Name: _____ Last Name: _____
Facility/Firm: _____
Street: _____
City/State/Zip: _____

I hereby certify that the above information is true and correct to the best of my knowledge.
Signature: Randy Radke
Print Name: Randy Radke
Firm: Cascade Drilling

NOTE: See instructions for more information including a list of county codes and well type codes.

ATTACHMENT 2
DETAILED COSTING SHEETS

KPRG TASK COSTING SHEET

Project: Former Bask Dry Cleaner - Westbrook Shopping Center - Waukesha, WI

Task: 1 Additional Requested Work Planning/Coordination

Professional Labor	Rate ($/Hr.)	Units	Total
Principal/Proj. Mgr.	$135	8	$1,080.00
Field Eng./Sci.	$68	12	$816.00
CADD	$60	0	$0.00
Admin. Asst/ Word Proc.	$45	1	$45.00
		Total Labor	$1,941.00

External Expenses	Rate	Type	Units	Total
Reproduction	$50	Est.	0	$0.00
Field Vehicle	$60	Daily	0	$0.00
Sampling Supplies	$20	Daily	0	$0.00
Waukesha Fees	$300	Est.	1	$300.00
PPE - Modified Level D	$15	Daily	0	$0.00
PPE - Level C	$35	Daily	0	$0.00
			Total Expenses	$300.00

Contractors	Rate	Type	Units	Total
None.				$0.00
			Total Contractors	$0.00

TASK TOTAL:	$2,241.00

KPRG TASK COSTING SHEET

Project: Former Bask Dry Cleaner - Westbrook Shopping Center - Waukesha, WI

Task: 2 New Well Installation Costs

Professional Labor	Rate ($/Hr.)		Units	Total
Principal/Proj. Mgr.	$135		4	$540.00
Field Eng./Sci.	$68		80	$5,440.00
CADD	$60		0	$0.00
Admin. Asst/ Word Proc.	$45		2	$90.00
			Total Labor	$6,070.00

External Expenses	Rate	Type	Units	Total
PID	$75	Daily	8	$600.00
Field Vehicle	$60	Daily	8	$480.00
Sampling Supplies	$20	Daily	0	$0.00
Drums	$55	Each	0	$0.00
Waukesha Permit	$300	Est.	0	$0.00
PPE - Level C	$35	Daily	0	$0.00
			Total Expenses	$1,080.00

Contractors	Rate	Type	Units	Total
Cascade	$22,500	Est.	1	$22,500.00
Surveyor	$1,200	Est.	1	$1,200.00
IDW Disposal	$175	per Drum	10	$1,750.00
		Total Contractors		$25,450.00

TASK TOTAL:	$32,600.00

KPRG TASK COSTING SHEET

Project: Former Bask Dry Cleaner - Westbrook Shopping Center - Waukesha, WI

Task: 3 Additional Groundwater Sampling (2 Rounds)

Professional Labor	Rate ($/Hr.)	Units	Total
Principal/Proj. Mgr.	$135	4	$540.00
Field Eng./Sci.	$68	100	$6,800.00
CADD	$60	0	$0.00
Admin. Asst/ Word Proc.	$45	2	$90.00
		Total Labor	$7,430.00

External Expenses	Rate	Type	Units	Total
Reproduction	$50	Est.	0	$0.00
Field Vehicle	$60	Daily	6	$360.00
Water Quality Meter	$175	Daily	6	$1,050.00
Water Depth Meter	$25	Daily	6	$150.00
Disposable Bailers	$15	Ea.	40	$600.00
Shipping	$50	Est.	1	$50.00
			Total Expenses	$2,210.00

Contractors	Rate	Type	Units	Total
Analytical	$65	Est.	44	$2,860.00
		Total Contractors		$2,860.00
		TASK TOTAL:		$12,500.00

KPRG TASK COSTING SHEET

Project: Former Bask Dry Cleaner - Westbrook Shopping Center - Waukesha, WI

Task: 4 Additional Vapor Probe Sampling

Professional Labor	Rate ($/Hr.)		Units	Total
Principal/Proj. Mgr.	$135		1	$135.00
Field Eng./Sci.	$68		8	$544.00
CADD	$60		0	$0.00
Admin. Asst/ Word Proc.	$45		1	$45.00
			Total Labor	$724.00

External Expenses	Rate	Type	Units	Total
Reproduction	$50	Est.	0	$0.00
Field Vehicle	$60	Daily	1	$60.00
PID	$75	Daily	1	$75.00
Water Depth Meter	$25	Daily	0	$0.00
Disposable Bailers	$15	Ea.	0	$0.00
Shipping	$50	Est.	1	$50.00
			Total Expenses	$185.00

Contractors	Rate	Type	Units	Total
Analytical	$175	CVOC -A	3	$525.00
Summa Canister Rental	$60	Est	3	$180.00
		Total Contractors		$705.00

TASK TOTAL:	$1,614.00

KPRG TASK COSTING SHEET

Project: Former Bask Dry Cleaner - Westbrook Shopping Center - Waukesha, WI

Task: 5 Additional Reporting

Professional Labor	Rate ($/Hr.)		Units	Total
Principal/Proj. Mgr.	$135		6	$810.00
Field Eng./Sci.	$68		24	$1,632.00
CADD	$60		4	$240.00
Admin. Asst/ Word Proc.	$45		2	$90.00
			Total Labor	$2,772.00

External Expenses	Rate	Type	Units	Total
Reproduction	$50	Est.	0	$0.00
Field Vehicle	$60	Daily	0	$0.00
Water Quality Meter	$175	Daily	0	$0.00
Water Depth Meter	$25	Daily	0	$0.00
PPE - Modified Level D	$15	Daily	0	$0.00
Reproduction	$50	Est.	1	$50.00
			Total Expenses	$50.00

Contractors	Rate	Type	Units	Total
		Total Contractors		$0.00
		TASK TOTAL:		$2,822.00

KPRG TASK COSTING SHEET

Project: Former Bask Dry Cleaner - Westbrook Shopping Center - Waukesha, WI

Task: 6 Operation and Maintenance

Professional Labor	Rate ($/Hr.)		Units	Total
Principal/Proj. Mgr.	$135		2	$270.00
Field Eng./Sci.	$68		16	$1,088.00
CADD	$60		0	$0.00
Admin. Asst/ Word Proc.	$45		1	$45.00
			Total Labor	$1,403.00

External Expenses	Rate	Type	Units	Total
Reproduction	$50	Est.	0	$0.00
Field Vehicle	$60	Daily	1	$60.00
Water Quality Meter	$175	Daily	0	$0.00
Water Depth Meter	$25	Daily	0	$0.00
PPE - Modified Level D	$15	Daily	0	$0.00
Reproduction	$50	Est.	0	$0.00
			Total Expenses	$60.00

Contractors	Rate	Type	Units	Total
Driller	$5,450	Est	1	$5,450.00
		Total Contractors		$5,450.00
		TASK TOTAL:		$6,913.00