April 14, 2021 File #34283.000

Candace Sykora Wisconsin Department of Natural Resources 890 Spruce Street Baldwin, WI 54002

Re: National Presto Industries, Inc., Superfund Site, Eau Claire, Wisconsin Quarterly Discharge Monitoring Report for January through March 2021 USEPA CERCLIS ID WID 006196174 WDNR BRRTS 02-09-000267 and FID 609038320

Dear Candace:

On behalf of National Presto Industries, Inc. (NPI), Gannett Fleming, Inc. is providing NPI's quarterly discharge monitoring report (DMR) for the referenced period. The enclosed DMR provides flow and analytical data from Southwest Corner extraction well EW-6 and manhole MH-18. The groundwater pumped from EW-6 is treated by cascade aeration and discharged to the Chippewa River via the storm sewer and MH-18.

Submittal of this quarterly DMR is required by the Wisconsin Department of Natural Resources. Feel free to contact me if you have any questions or need additional information.

Sincerely,

GANNETT FLEMING, INC.

Clifford C. Wright, P.E., P.G. Project Engineer

CCW/jec Enc.

ecc: Howard Caine (USEPA)
Derrick Paul (NPI)
Chelsea Payne (Gannett Fleming)

NATIONAL PRESTO INDUSTRIES, INC. EAU CLAIRE, WISCONSIN

QUARTERLY DISCHARGE MONITORING RESULTS FOR 01/01/2021 - 03/31/2021

	Substance Concentration (μg/ℓ), Result Qualifier (RQ), and Percent Removal (% Removal)														Flow	
Sample	1,1,1-Trichloroethane			1,1-Dichloroethane			1,1-Dichloroethylene			Tetrachloroethylene			Trichloroethylene (TCE)			Rate ⁽¹⁾
Location	ug/L	RQ	% Removal	ug/L	RQ	% Removal	ug/L	RQ	% Removal	ug/L	RQ	% Removal	ug/L	RQ	% Removal	(MGD)
EW-1R ⁽²⁾	ns		na	ns		na	ns		na	ns		na	ns		na	0.0
EW-2 ⁽²⁾	ns		na	ns		na	ns		na	ns		na	ns		na	0.0
Influent 1	ns		na	ns		na	ns		na	ns		na	ns		na	0.0
Effluent 1	ns		na	ns		na	ns		na	ns		na	ns		na	0.0
EW-5 ⁽³⁾	ns		na	ns		na	ns		na	ns		na	ns		na	0.0
EW-6	1.2	A	na	0.27	UA	na	0.24	UA	na	0.33	UA	na	0.82	JA	na	0.225
Influent 2	1.2	A	na	0.27	UA	na	0.24	UA	na	0.33	UA	na	0.82	JA	na	0.225
Effluent 2	0.66	J	45	0.27	U		0.24	U		0.33	U		0.54	J	34	0.225
Manhole MH-18	0.66	J	na	0.27	U	na	0.24	U	na	0.33	U	na	0.54	J	na	0.225
Discharge Limit	NLE	`		NLE			50			50	`		100	·		NLE

NOTES:

Concentrations are in micrograms per liter ($\mu g/\ell$) or parts per billion (ppb).

Samples were collected for this reporting period from EW-6 and MH-18 on 03/16/21; flow rate data were compiled through 03/31/21.

Cascade aerator influent results (Influent 1 and Influent 2) were calculated based on the extraction well data (EW-1R, etc.), where applicable.

Influent 1 = Discharge (flow) from extraction wells EW-1R and EW-2.

Influent 2 = Discharge (flow and flow-weighted concentrations) from EW-5 and EW-6.

Manhole MH-18 = Effluent 1 (+) Effluent 2 for flow. Effluent 2 = MH-18 for concentrations because MH-18 and CAS-2R are less than 60 feet apart.

RQ = Result qualifiers.

A = Average of original sample and duplicate.

J = Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit (or flow-weighted value that includes J or U flagged data).

U = Parameter not detected at or above the indicated value, which is the detection limit for measured concentrations or a flow-weighted number for calculated levels.

na = Not applicable.

NLE = No limit established.

ns = No sample collected for discharge monitoring.

-- = % Removal not calculated because at least one influent concentration was less than the limit of detection.

FOOTNOTES:

- (1) Flow rate in millions of gallons per day (MGD) calculated based on metered volume (20,001,050 gallons) and pumping days (89).
- (2) Melby Road Disposal Site extraction wells EW-1R and EW-2 are currently shut down, as approved by the WDNR and USEPA.
- (3) Southwest Corner extraction well EW-5 is currently shut down, as approved by the WDNR and USEPA.