



AECOM
11425 West Lake Park Drive, Suite 100
Milwaukee, WI 53224

414.359.3030 tel
414.359.0822 fax

August 4, 2010

Mr. Hank Kuehling, P.G.
Wisconsin Department of Natural Resources
3911 Fish Hatchery Road
Fitchburg, WI 53711-5397

**Subject: Reedsburg Cleaners, 349 E. Main Street, Reedsburg, WI, BRRTS# 02-57-001682
AECOM Project No. 60139948.0**

Dear Mr. Kuehling:

As a follow-up to the WDNR e-mail dated July 15, 2010, this letter documents the recent completion of additional buffer and whey electron donor injection at the Reedsburg Cleaners site in Reedsburg, Wisconsin. Initial injection of whey and sodium bicarbonate buffer at this site occurred on December 1 and 2, 2009, as documented in the AECOM report dated December 11, 2009. The following provides a summary of the recently-completed buffer and electron donor injection tasks.

Injection of Additional Buffering Material

The production of hydrogen ion during reductive dechlorination, as well as production of volatile fatty acids from electron donor fermentation, tends to decrease the pH of the groundwater system. Based on information contained in AFCEE (2004) and ITRC (2008), pH values between 5 and 9 and total alkalinity values greater than 100 milligrams per liter (mg/L) are favorable for enhanced anaerobic bioremediation. Values of pH that are less than 5 indicate that a buffering agent may be required to sustain high rates of anaerobic dechlorination. At many sites, the natural buffering capacity of the aquifer matrix is adequate to prevent the development of acidic groundwater pH. The results of previous groundwater monitoring events reveal that the sandstone bedrock matrix at the Reedsburg Cleaners site may not have adequate natural buffering capacity, such that the injection of whey documented herein included the injection of additional aquifer buffer material.

Pursuant to the WDNR e-mail dated July 15, 2010, injection of additional aquifer buffer material through the on-site injection wells occurred on July 19, 2010. Specifically, injection of "Neutral Zone®" was completed, which is designed to duplicate the buffering capacity of a naturally calcareous soil. The product is a stable suspension of small-micron to sub-micron particles of calcium carbonate containing more than 500,000 mg/kg of total alkalinity (as CaCO₃ equivalents) and proprietary additives that produce a negative surface charge. The calcium carbonate is food grade and the additives are approved as secondary direct additives in food for human consumption. The desired mobility of Neutral Zone® is based on the small micron to sub-micron particle size and additives that maintain a negative zeta potential. Colloidal buffer systems with a low solubility (10 to 20 mg/L for CaCO₃) can be transported significant distances in the subsurface, yet can also have substantial retention in the soil or aquifer after injection. The insoluble calcium carbonate dissolves primarily by contact with the acidity of the environment and the maximum pH is



limited by the generation of bicarbonate to a value of 8.34, whereas highly soluble buffers can create adversely high pH near injection points (>13.0 for potassium hydroxide, for example).

A total of 1,200 lbs of Neutral Zone® was injected through six existing on-site injection wells as an approximate 1.6 percent (16,000 mg/kg) solution of CaCO₃ equivalents, such that a total of 4,500 gallons of Neutral Zone® and potable tap water solution was injected. Each of the six injection wells received the following Neutral Zone® buffer solution volumes:

- IW-1 – 568 gallons;
- IW-2 – 892 gallons;
- IW-3 – 630 gallons;
- IW-4 – 860 gallons;
- IW-5 – 850 gallons; and,
- IW-6 – 700 gallons.

Injection of Whey Electron Donor

The injection of additional buffer was followed by injection of whey electron donor on July 20 and 21, 2010. AECOM previously identified a supplier of whey in close proximity to the Reedsburg Cleaners site (Muscoda Protein Products of Muscoda, Wisconsin), that provided whey for the purpose of this groundwater remediation. The whey was delivered in bulk (6,000-gallon capacity tanker trucks), and injected through a portable manifold system into the six injection wells.

A log of the whey injection activities is provided as Attachment A, which identifies the 2-inch diameter injection wells as IW-1 through IW-6. As indicated in Attachment A, an estimated total of 12,040 gallons of whey was injected through the wells as follows:

- IW-1 – 660 gallons;
- IW-2 – 2,800 gallons;
- IW-3 – 1,650 gallons;
- IW-4 – 2,860 gallons;
- IW-5 – 2,580 gallons; and,
- IW-6 – 1,490 gallons.

The existing groundwater monitoring well network at the site will continue to be used for monitoring the effectiveness of the whey electron donor injection program. Ongoing groundwater monitoring data will be evaluated to document the progress of remediation and modify the electron donor injection program as appropriate.

Pursuant to the AECOM correspondence dated July 2, 2010, a groundwater monitoring event is scheduled to be conducted on August 9, 2010. As part of this monitoring event, the field parameters dissolved oxygen, ORP, and pH will be measured in all six injection wells (IW1 through IW6), and the following six monitoring wells: MW-2, MW-3R, MW-4, MW-5, MW-6, and MW-7. One groundwater sample will also be collected from monitoring well MW-7 for analysis of quantitative polymerase chain reaction (Q-PCR).


The results of the groundwater monitoring event to be conducted on August 9, 2010 will be used to evaluate groundwater conditions that are necessary to support bioaugmentation with commercially-available *Dehalococcoides* microbes. The Q-PCR testing will be used to evaluate and quantify existing dechlorinating bacteria for reduction of tetrachloroethene to non-toxic ethene. The results

of this upcoming groundwater monitoring event will be reported to the WDNR upon receipt. If you have any questions concerning the information contained herein, please feel free to contact us.

Yours sincerely,



Mark M. Mejac, PG, CGWP
Senior Hydrogeologist



Jeanne M. Tarvin, PG, CPG
Senior Principal/EH&S Practice Leader

Enclosure

cc: Mr. Wayne Butz

References Cited

Air Force Center for Environmental Excellence (AFCEE). 2004. "Principles and Practices of Enhanced Anaerobic Bioremediation of Chlorinated Solvents". Environmental Security Technology Certification Program, Arlington, Virginia.

ITRC (Interstate Technology & Regulatory Council). 2008. "In Situ Bioremediation of Chlorinated Ethene: DNAPL Source Zones," Washington, D.C.: Interstate Technology & Regulatory Council, Bioremediation of DNAPLs Team.

IW 1

INJECTION LOG						
REEDSBURG CLEANERS						
349 EAST MAIN STREET						
REEDSBURG, WI						
PROJECT REFERENCE #4646						
Point ID	Date	Start Time	Flow Rate (GPM)	Pressure Rate (PSI)	Completion Time	Gallons Injected
IW 1	7/19	9:35	4	15+		0
		10:05			276	
		10:35			277	
		11:05			278	
		11:45			201	
		12:15			212	
		12:35			253	
		1:05			294	
		1:35			332	
		2:05			385	
		2:35			415	
		3:05			482	
		3:15			550	
						568
	7/20	8:30	0.5	ferr		0
		9:00			15	
		9:30			30	
		10:00			45	
		10:30			60	
		11:00			75	
		11:30			100	
		12:00			105	
		12:30			120	
		1:00			120	
		1:30			135	
		2:00			145	
		2:30			160	
		3:00			185	
		3:30			200	
		4:00			230	
		4:30			270	
		5:00			300	
5:30	330					
						330
	7/21	7:15	0.5	ferr		0
		7:45			20	
		8:15			50	
		8:45			80	
		9:15			100	
		9:45			115	
		10:15			130	
		10:45			145	
		11:15			160	
		11:45			180	
		12:15			190	
		12:45			205	
		1:15			220	
		1:45			225	
		2:15			235	
2:45	245					
3:15	255					
3:45	270					
4:15	300					
5:00	390					

Running slow
blowout
off on
off blowout

off
on
stop

5685

off

B

I W 2

INJECTION LOG						
REEDSBURG CLEANERS						
349 EAST MAIN STREET						
REEDSBURG, WI						
PROJECT REFERENCE #4646						
Point ID	Date	Start Time	Flow Rate (GPM)	Pressure Rate (PSI)	Completion Time	Gallons Injected
IW 2	7/19	9:35 AM	4	15 #		0
		10:05				27
		10:35				72
		11:05				113
		11:35				157
		12:05				207
		12:35				298
		1:05				409
		1:35				501
		2:05				612
		2:35				719
		3:05				802
						892
					off	
	7/20	8:30	3 + 0'			0
		9:00				109
		9:30				174
		10:00				261
		10:30				348
		11:00				435
		11:30				522
		12:00				609
		12:30				696
		1:00				783
		1:30	2 + 0'			870
		2:00				957
		2:30				1044
		3:00				1130
		3:30				1217
		4:00				1304
		4:30				1391
		5:00				1478
		5:30				1565
		6:00				1652
						stop
	7/21	7:15	3 #			0
		7:45				96
		8:15				192
		8:45				288
		9:15				384
		9:45				480
		10:15				576
		10:45				672
		11:15				768
		11:45				864
		12:15				960
		12:45				1056
		1:15				1152
		1:45				1248
		2:15				1344
		2:45				1440
		3:15				1536
		3:45				1632
		4:15				1728
						off

slow leak
 F:\Excel\4500\Blank Injection Log
 fix

G

IW 4

INJECTION LOG						
REEDSBURG CLEANERS						
349 EAST MAIN STREET						
REEDSBURG, WI						
PROJECT REFERENCE #4646						
Point ID	Date	Start Time	Flow Rate (GPM)	Pressure Rate (PSI)	Completion Time	Gallons Injected
IW 4	7/19	9:35	34	154		0
		10:05				30
		10:25				94
		11:05				136
		11:35				212
		12:05				207
		12:35				421
		1:05				519
		1:35				610
		2:05				712
		2:35				809
		2:05				860
	7/20	8:30	2+			0
		8:00				30
		8:30				140
		10:00				210
		10:30				280
		11:00				350
		11:30				420
		12:00				490
		12:30				560
		1:00	3+			640
		1:30	3+			800
		2:00	3+			920
		2:30				1030
		3:00				1160
		3:30				1220
		4:00				1310
		4:30				1410
		5:00				1500
5:30				1590		
6:00				1620		
	7/21	7:15	3+			0
		7:45				115
		8:15				230
		8:45				330
		9:15				380
		9:45				430
		10:15				540
		10:45				640
		11:15				730
		11:45				800
		12:15				890
		12:45				930
		1:15				1030
		1:45				1150
		2:15				1240
		2:45				
3:15						
3:45						
4:15						
4:45						

off

1104

stop

off

wood slow leak

2100

IW 5

INJECTION LOG						
REEDSBURG CLEANERS						
349 EAST MAIN STREET						
REEDSBURG, WI						
PROJECT REFERENCE #4646						
Point ID	Date	Start Time	Flow Rate (GPM)	Pressure Rate (PSI)	Completion Time	Gallons Injected
IW 5	7/19	9:35	4	15.4		0
		10:01				39
		10:33				70
		11:03				112
		11:35				168
		12:03 AM				201
		12:35				289
		1:05				425
		1:35				587
		2:05				698
		2:35				772
		3:05				850
	7/20	8:30	1			0
		9:00	1			30
		9:30	1			60
		10:00	1			90
		10:30	1			120
		11:00	1			150
		11:30	2			210
		12:00	2			270
		12:30	2			330
		1:00	2			400
		1:30	2			470
		2:00	2			550
		2:30	2			600
		3:00	2			650
		3:30	2			700
		4:00	2			750
		4:30	2			800
		5:00	2			850
		5:30	2			900
		6:00	2			115
						1210
	7/21	7:15	3.4			0
		7:45				100
		8:15				200
		8:45				290
		9:15				340
		9:45				440
		10:15				550
		10:45				620
		11:15				710
		11:45				810
		12:15				900
		12:45				1000
		1:15				1090
		1:45				1180
		2:15				1270
		3:15				1370
		3:45				
		4:15				
		4:45				

off

?

206 R
110

stop

off

better throughout Good now

I W 6

INJECTION LOG						
REEDSBURG CLEANERS						
349 EAST MAIN STREET						
REEDSBURG, WI						
PROJECT REFERENCE #4646						
Point ID	Date	Start Time	Flow Rate (GPM)	Pressure Rate (PSI)	Completion Time	Gallons Injected
IW 6	7/19	9:35	4	15 F		0
		10:00			47	
		10:33			92	
		11:05			142	
		11:33			217	
		11:50			280	
		12:05pm			330	
		12:45			392	
		1:05			479	
		1:35			480	
		2:05			510	
		2:35			590	
		3:05			637	
					700	
	7/20	5:30	0.5 + or -			0
9:00		15				
9:30		30				
10:00		45				
10:30		60				
11:00		75				
11:30		90				
12:00		105				
12:30		120				
1:00		135				
1:30		150				
2:00		165				
2:30		180				
3:00		195				
3:30	210					
4:00	220					
4:30	230					
5:00	240					
5:30	240					
6:00	270					
	7/21	7:15	1+			0
7:45		50				
8:15		100				
8:45		150				
9:15		200				
9:45		250				
10:15		300				
10:45		350				
11:15		400				
11:45		450				
12:15		500				
12:45		550				
1:15		600				
1:45		650				
2:15	700					
2:45	750					
3:15	800					
3:45	850					
4:15	900					
4:45	920					
			slow			
			5.00			

Running slow
off on
Blow out
off

stop

off