

From: Schultz, Josie M - DNR
Sent: Tuesday, August 17, 2021 5:21 PM
To: Brian Youngwirth
Cc: Keegan Pries; Garritt R. Bader
Subject: RE: You Are My Sunshine Daycare-1324 South Webster Avenue

Hi Brian,

I've reviewed the abbreviated work plan, and recommend placing the 8-hour indoor air samplers within the classrooms that are most used, and to install the vapor ports within the areas in between the classrooms, if this is feasible. Please also reference [RR-986](#) for performing proper leak and shut-in testing prior to obtaining samples.

With my comments above, please proceed with vapor sampling this week.

Thank you,
Josie

We are committed to service excellence.

Visit our survey at <http://dnr.wi.gov/customersurvey> to evaluate how I did.

Josie Schultz

Cell Phone: (920) 366-5685
Josie.Schultz@Wisconsin.gov



From: Brian Youngwirth <byoungwirth@generalengineering.net>
Sent: Tuesday, August 17, 2021 2:28 PM
To: Schultz, Josie M - DNR <josie.schultz@wisconsin.gov>
Cc: Keegan Pries <keegan.pries@gmail.com>; Garritt R. Bader <GB@gb-re.com>
Subject: You Are My Sunshine Daycare-1324 South Webster Avenue

Hi Josie,

Below is a description of how the vapor sampling will be performed at You Are My Sunshine Daycare in Green Bay. We will be performing two 0.5-hour sub-slab tests and two 8-hour ambient air tests on Thursday August 19, 2021. I have attached a floor plan map with three blue circles on it. The classrooms have in floor heat; therefore no drilling will be performed in those areas. The sub-slab and ambient samples will be collected within 2 of the 3 areas circled on the map, which I will evaluate when I get there. I will likely use the northern location and one of the two southern locations.

Sub-slab vapor ports will be installed by drilling a 1.5-inch hole in the concrete floor to approximately 2 inches, followed by a 5/8-inch hole through the remainder of the concrete. GEC then utilizes a Cox-Colvin Vapor Kit to place the vapor points. A rubber vapor pin sleeve will be placed over a stainless-steel

pin, which is hammered into the hole to create a seal. The 1.5-inch hole and rubber seal will be used as a dam to ensure there were no leaks and a proper seal is in place. The plastic hose for the Summa[®] Canister will then be placed over the pin to ensure a sealed sample. The sub-slab vapor samples will be submitted for laboratory analysis for the presence of chlorinated volatile organic compounds. The results will be provided to the WDNR at the completion of the work.

Please let me know if you have any questions.

Thank you,

Brian L. Youngwirth

Environmental Project Manager | **General Engineering Company**

916 Silver Lake Drive | PO Box 340 | Portage, WI 53901

P 608-742-2169 | C 608-697-8010

byoungwirth@generalengineering.net

www.generalengineering.net

GENERAL ENGINEERING COMPANY DISCLAIMER

This email and any electronic media transmitted with it are provided solely for the use of the addressee. Data, plans, specifications, reports, documents, and other information recorded on or transmitted as electronic media are subject to undetectable alteration, either intentional or unintentional, due to, among other causes, transmission, conversion, media degradation, software error, or human alteration. Accordingly, all such documents recorded on or transmitted as electronic media are being provided to the addressee for informational purposes only, and not as an end product or as a record document. Any reliance on documents recorded on or transmitted as electronic media is deemed to be unreasonable and unenforceable. Neither the information contained nor the opinions expressed in this email are intended to be or shall be construed as legal or engineering advice. GENERAL ENGINEERING COMPANY accepts no liability or responsibility for the consequences of any actions taken on the basis of the information or opinions contained in this email.

If you have received this email in error please notify the system manager. Finally, the recipient should check this email and any attachments for the presence of viruses. The company accepts no liability for any damage caused by any virus transmitted by this email