



MONITORING WELL DECOMMISSIONING LOG



PROJECT NAME: 0 WIS DOT Winneconne		MONITORING WELL ID: TRC-11-1	
PROJECT NUMBER: 0-00254450		DATE: 9-22-17	LOCATION:
OBSERVED BY: 0 S. Sellwood		LOCATION COORDINATES:	
DRILLING CONTRACTOR: NA		N:	
CREW CHIEF:		E:	
		TOP OF CASING ELEV.: _____	SURFACE ELEV.: _____

PROTECTIVE COVER TYPE:	☐ STICK-UP	☒ FLUSH MOUNT	☐ TRAF. BOX	☐ OTHER _____
PROTECTIVE COVER DIAMETER:	☐ 4"	☒ 8"	☐ 9"	☐ 10"
WELL MATERIAL:	☒ PVC	☐ SS	☐ IRON	☐ GALVANIZED STEEL
WELL CASING DIAMETER:	☐ 1"	☒ 2"	☐ 4"	☐ 6"
WELL SCREEN MATERIAL:	☒ PVC	☐ SS	☐ IRON	☐ GALVANIZED STEEL
WELL SCREEN LENGTH:	☐ 5-FT	☒ 10-FT	☐ UNKNOWN	☐ OTHER _____
WELL SCREEN SLOT SIZE:	☒ 0.01"	☐ 0.02"	☐ UNKNOWN	☐ OTHER _____
DTW: _____				T/ PVC
DTB: _____				T/ PVC

ABANDONMENT PROCEDURE:
NOTES: Screened & poured bentonite chips (~ 25 lbs) removed flushmount well cover

GROUTING PROCEDURE:	NOTES:
GROUT TYPE:	
GROUT MIX:	
GROUT INTERVAL: _____ FT-BGS TO _____ FT-BGS	
BENTONITE SEAL:	
SEAL INTERVAL: _____ FT-BGS TO _____ FT-BGS	

ADDITIONAL COMMENTS:

	9-25-17		9/28/17
SIGNED	DATE	CHECKED	DATE



MONITORING WELL DECOMMISSIONING LOG

PROJECT NAME: 0 WISDOT Winneconne		MONITORING WELL ID: TRC-11-2	
PROJECT NUMBER: 000 254450	DATE: 9-22-17	LOCATION:	LOCATION COORDINATES:
OBSERVED BY: 0 S. Sellwood			N:
DRILLING CONTRACTOR: NA			E:
CREW CHIEF:		TOP OF CASING ELEV.: _____	SURFACE ELEV.: _____

PROTECTIVE COVER TYPE:	☐ STICK-UP	☒ FLUSH MOUNT	☐ TRAF. BOX	☐ OTHER _____		
PROTECTIVE COVER DIAMETER:	☐ 4"	☒ 8"	☐ 9"	☐ 10"	☐ 12"	☐ OTHER _____
WELL MATERIAL:	☒ PVC	☐ SS	☐ IRON	☐ GALVANIZED STEEL	☐ OTHER _____	
WELL CASING DIAMETER:	☐ 1"	☒ 2"	☐ 4"	☐ 6"	☐ 8"	☐ OTHER _____
WELL SCREEN MATERIAL:	☒ PVC	☐ SS	☐ IRON	☐ GALVANIZED STEEL	☐ OTHER _____	
WELL SCREEN LENGTH:	☐ 5-FT	☒ 10-FT	☐ UNKNOWN	☐ OTHER _____	DTW: _____	T/ PVC
WELL SCREEN SLOT SIZE:	☒ 0.01"	☐ 0.02"	☐ UNKNOWN	☐ OTHER _____	DTB: _____	T/ PVC

ABANDONMENT PROCEDURE:

NOTES:

Screened & poured bentonite chips (~30 lbs)

GROUTING PROCEDURE:

NOTES:

GROUT TYPE:
GROUT MIX:
GROUT INTERVAL: _____ FT-BGS TO _____ FT-BGS
BENTONITE SEAL:
SEAL INTERVAL: _____ FT-BGS TO _____ FT-BGS

ADDITIONAL COMMENTS:

removed flushmount well cover

S. Sellwood 9-25-17
SIGNED DATE

Alw Scler 9/28/17
CHECKED DATE



MONITORING WELL DECOMMISSIONING LOG


PROJECT NAME: 0 Wis DOT Winneconne		MONITORING WELL ID: TRC-12-2	
PROJECT NUMBER: 0-00 254450		DATE: 9-22-17	LOCATION:
OBSERVED BY: 0 S. Sellwood			LOCATION COORDINATES:
DRILLING CONTRACTOR: NA			N:
CREW CHIEF:			E:
		TOP OF CASING ELEV.: _____	SURFACE ELEV.: _____

PROTECTIVE COVER TYPE:	☐ STICK-UP	☒ FLUSH MOUNT	☐ TRAF. BOX	☐ OTHER _____
PROTECTIVE COVER DIAMETER:	☐ 4"	☒ 8"	☐ 9"	☐ 10"
WELL MATERIAL:	☒ PVC	☐ SS	☐ IRON	☐ GALVANIZED STEEL
WELL CASING DIAMETER:	☐ 1"	☒ 2"	☐ 4"	☐ 6"
WELL SCREEN MATERIAL:	☒ PVC	☐ SS	☐ IRON	☐ GALVANIZED STEEL
WELL SCREEN LENGTH:	☐ 5-FT	☒ 10-FT	☐ UNKNOWN	☐ OTHER _____
WELL SCREEN SLOT SIZE:	☒ 0.01"	☐ 0.02"	☐ UNKNOWN	☐ OTHER _____
				DTW: _____ T/ PVC
				DTB: _____ T/ PVC

ABANDONMENT PROCEDURE:
NOTES: Screened & poured bentonite chips (~30 lbs)

GROUTING PROCEDURE:	NOTES:
GROUT TYPE:	
GROUT MIX:	
GROUT INTERVAL: _____ FT-BGS TO _____ FT-BGS	
BENTONITE SEAL:	
SEAL INTERVAL: _____ FT-BGS TO _____ FT-BGS	

ADDITIONAL COMMENTS: left flushmount cover in place - will be removed when sidewalk is pulled up during roadway reconstruction

	9-25-17		9/28/17
SIGNED	DATE	CHECKED	DATE



MONITORING WELL DECOMMISSIONING LOG

PROJECT NAME: 0 WisDOT Winneconne		MONITORING WELL ID: TRC-12-3	
PROJECT NUMBER: 000 254450		DATE: 9-22-17	LOCATION:
OBSERVED BY: 0 S. Sellwood			LOCATION COORDINATES:
DRILLING CONTRACTOR: NA			N:
CREW CHIEF:			E:
		TOP OF CASING ELEV.: _____	SURFACE ELEV.: _____

PROTECTIVE COVER TYPE:	☐ STICK-UP	☒ FLUSH MOUNT	☐ TRAF. BOX	☐ OTHER _____
PROTECTIVE COVER DIAMETER:	☐ 4"	☒ 8"	☐ 9"	☐ 10"
WELL MATERIAL:	☒ PVC	☐ SS	☐ IRON	☐ GALVANIZED STEEL
WELL CASING DIAMETER:	☐ 1"	☒ 2"	☐ 4"	☐ 6"
WELL SCREEN MATERIAL:	☒ PVC	☐ SS	☐ IRON	☐ GALVANIZED STEEL
WELL SCREEN LENGTH:	☐ 5-FT	☒ 10-FT	☐ UNKNOWN	☐ OTHER _____
WELL SCREEN SLOT SIZE:	☒ 0.01"	☐ 0.02"	☐ UNKNOWN	☐ OTHER _____
				DTW: _____ T/ PVC
				DTB: _____ T/ PVC

ABANDONMENT PROCEDURE:	
NOTES: Screened & poured bentonite chips (~30 lbs)	

GROUTING PROCEDURE:		NOTES:
GROUT TYPE:		
GROUT MIX:		
GROUT INTERVAL: _____ FT-BGS TO _____ FT-BGS		
BENTONITE SEAL:		
SEAL INTERVAL: _____ FT-BGS TO _____ FT-BGS		

ADDITIONAL COMMENTS: removed flushmount well cover	
---	--

S. Sellwood 9-25-17
SIGNED DATE

A. Schuler 9/28/17
CHECKED DATE