## Jorgensen, Theadora O - DNR

From: Jeanne Tarvin < jtarvin@ramboll.com>
Sent: Monday, January 11, 2021 4:48 PM
To: Moll, John G - DNR (Gregory)

Cc:MThimke@foley.com; Kai Hansen; Snejana KarakisSubject:Scot Galena Street - SDS for Rust Preventative

Attachments: Standard GHS SDS Report (Benz Gard - Water Based Rust Preventative).pdf

Greg, As a follow up to our call this afternoon, I am sending a copy of the SDS for Scot's rust preventative product. According to Scot representatives, the product historically used was a Benz Oil Co., Benz Gard. The formulation has not changed according to the Benz oil contact. The product consists of heavy naphthenic hydrotreated distillates at a 20 to 30% concentration by weight in an aqueous based formulation. Regards, Jeanne

Jeanne Tarvin, PG, CPG Principal D +1 (262) 901-0085 M +1 (414) 326-5365 jtarvin@ramboll.com

# **Safety Data Sheet**

## Section 1 - Product and Company Identification

Product Name: BENZ GARD Product Code: 456001

Trade Name: Industrial Rust Preventative

**Benz Oil Company** 2724 W. Hampton Ave. Milwaukee, WI 53209

**Telephone Numbers** 

During normal business hours call (414)442-2900

Outside normal business hours call CHEMTREC (800)424-9300

Email Address msds@benz.com

Product Use: Industrial Lubricant

Not recommended for: Applications other than those intended. For application information see product Technical

Data Sheet or consult with a company representative.

## Section 2 - Hazards Identification

#### **Emergency Overview:**

In accordance with good industrial hygiene and industrial practices. Airborne exposures should be controlled to the lowest extent possible. Do not ingest. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash thoroughly after handling. Keep container closed.

GHS Ratings: This product is not hazardous according to OSHA 29CFR 1910.1200

### **GHS Hazards**

**GHS Precautions** 

There are no GHS ratings that apply to this product at this time.

### Section 3 - Composition

\*Proprietary additive(s) listed only if considered hazardous per OSHA regulations, at a 1% or greater concentration (0.1% for carcinogens)\*

Chemical Name	CAS number	Weight Concentration %
Heavy Naphthenic Hydrotreated Distillates	64742-52-5	20.00 - 30.00

### Section 4 - First Aid Measures

### Inhalation:

Remove from further exposure. For those providing assistance, avoid exposure to yourself. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, a trained individual should attempt to resuscitate while getting immediate medical aid.

### **Eye Contact:**

Flush eyes with water for 15 minutes. If irritation persists, get medical attention.

SDS for: 456001 Page 1 of 5

Printed: 6/3/2015 at 11:54:49AM

#### **Skin Contact:**

Prolonged or repeated contact may cause irritation. Good hygienic practices should be observed at all times. Wash exposed skin with soap and warm water.

#### Ingestion:

Do not induce vomiting. Seek medical attention.

## Section 5 - Fire Fighting Measures

Flash Point: N/A

#### **Extinguishing Media:**

Carbon Dioxide (CO2), dry chemical or foam. Water can be used to cool and protect exposed material.

#### **Unusual Fire Hazards:**

Flashpoint is not determined due to the water content of this product. Extreme exposure conditions may render this product combustible.

#### **Products of Combustion:**

Fumes, smoke, COx, SOx, NOx, when combusted.

#### Fire Fighting Instructions:

Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Fire fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water supply to cool fire exposed surfaces and to protect personnel.

## Section 6 - Accidental Release Measures

#### **Notification Procedures:**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulaions. US regulaions require reporting releases of this material to the environment which exceeds the applicable reportable quanity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at 1-800-424-8802.

#### **Spill Management:**

Shut off source of leak if it is safe to do so. Dike and contain spill.

### **Small Spills:**

While wearing suitable personal protective equipment (PPE), absorb spill with suitable material. Place in a non-leaking container and seal tightly for proper disposal.

#### Large Spills:

Ventilate the contaminated area. Wearing suitable PPE, pump into salvage vessels. Dispose of collected material according to regulations.

## Section 7 - Handling and Storage

### Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Do not take internally. For industrial use only. Use this product with adequate ventilation. Launder work clothes frequently. Always use good personal hygiene practices. Bring product to room temperature before use.

### Storage:

Keep properly labeled container tightly closed, and in a cool, well-ventilated place away from incompatible materials. Store away from heat, sparks and other ignition sources. Containers, even those have been emptied, can contain explosive vapors. Do not pressurize, cut, weld, drill or grind on or near containers. Do not reuse empty containers.

## Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits

SDS for: 456001 Page 2 of 5

Heavy Naphthenic	PEL: 5 mg/m3	TLV: 5 mg/m3 (Inhalable)	Not Determined
Hydrotreated Distillates			
64742-52-5			

#### **Ventilation Control:**

Provide adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

#### **Personal Protection:**

As prescribed in the OSHA Standard for Personal Protective Equipment (29CFR 1910.132), employers must perform a Hazard Assessment of all workplaces to determine the need for proper protective equipment for each employee.

#### **Eye Protection:**

Normal industrial eye protection practices should be employed.

#### **Skin Protection:**

In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

### Respiratory:

If airborne concentration limits are not met, an approved respirator must be worn.

#### **Contaminated Gear:**

Soiled work clothing should be laundered or dry-cleaned.

## Section 9 - Physical and Chemical Properties

Typical physical and chemical properties are given below. Consult the manufacturer in Section 1 for additional data.

Appearance: Milky Brown Liquid

Vapor Pressure: No Data Available

Vapor Density: No Data Available

Specific Gravity@60F 0.9

Freezing point: No Data Available

Flash point: N/A

Flammability: No Data Available

Partition coefficient (n-

octanol/water): No Data Available

**Decomposition temperature:** No Data Available

Odor: Slight Amine

Odor threshold: No Data Available

Hq 0.9 Hq

Melting point: No Data Available

Solubility: Soluble in Water

Evaporation rate: No Data Available

Explosive Limits: No Data Available

Autoignition temperature: No Data Available

Grams VOC less water: No Data Available

## Section 10 - Stability and Reactivity

### Stability:

Material is stable under normal conditions.

#### **Conditions to Avoid:**

Excessive heat. High energy sources of ignition.

### Material to Avoid:

Strong oxidizers. Because this product may contain alkanolamines, do not add nitrites.

### **Hazardous Decomposition Products:**

This material does not decompose at ambient temperatures.

#### **Hazardous Polymerization:**

Will not occur.

## Section 11 - Toxicological Information

#### **Mixture Toxicity**

Inhalation Toxicity LC50: 26mg/L

SDS for: 456001 Page 3 of 5

Printed: 6/3/2015 at 11:54:49AM

#### **Component Toxicity**

64742-52-5

Heavy Naphthenic Hydrotreated Distillates

Dermal LD50: >2,000 mg/kg (Rabbit) Inhalation LC50: 6 mg/L (Rat)

If applicable, the ingredient(s) listed above are considered hazardous per OSHA 1910.1200. Included are the corresponding LD50 ratings, if available. Hazardous ingredients are required to be listed if they are used in the final product at a 1% (0.1% for carcinogens) or greater concentration.

Routes of Entry: Eye contact. Dermal contact. Inhalation. Ingestion.

Target Organs: None Known

## Section 12 - Ecological Information

### **Ecotoxicity:**

No data available for this product.

## Section 13 - Disposal Considerations

#### **Disposal Instructions:**

Refer to the latest US EPA, state and local regulations regarding proper disposal.

## Section 14 - Transport Information

AgencyProper Shipping NameUN NumberPacking GroupHazard ClassDOTNot RegulatedN/AN/AN/A

## Section 15 - Regulatory Information

Prepared according to US OSHA 29CFR 1910.1200 regulations.

Additional regulatory listings, where applicable.

**California Prop 65:** The following chemicals are known to the State of California to cause cancer, birth defects, or other reproductive harm.

110-80-5 Ethylene glycol monoethyl ether

The following chemicals are listed under SARA 311/312:

64742-52-5 Heavy Naphthenic Hydrotreated Distillates Acute, Chronic

### **Toxic Substances Control Act (TSCA) Status:**

All components are listed on the EPA/TSCA Inventory of Chemical Substances unless listed below.

- None

## Section 16 - Other Information

**Hazardous Material Information System (HMIS)** 

National Fire Protection Association (NFPA)

SDS for: 456001 Page 4 of 5



HMIS & NFPA Hazard Rating Legend


\* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH



Date Prepared: 6/3/2015

Benz Oil Company has taken all reasonable steps to insure this data sheet and the information contained in it is accurate as of the date issued. No warranty is made as to the accuracy or completeness of the information in this data sheet. The information stated on this MSDS applies only to the intended applications. Do not use this product for any application other than the intended application.

Employers are responsible for communicating any hazards and precautions described in this sheet.

SDS for: 456001 Page 5 of 5

Printed: 6/3/2015 at 11:54:49AM