Well Construction Report
WISCONSIN UNIQUE WELL NUMBER: AAX742

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: DERRICK HOMES LLC	Phone #
Mailing Address: 1505 HWY 65 PO BOX 445	
City: NEW RICHMOND	State: WI — Zip Code: 54017
County: Burnett	Co. Permit #:
Notification #: 9121928401	Completed: 05-02-2023
Well Constructor (Business Name): BUTTERFIELD, TIM DRILLING INC	Lic. #: 6900
Facility ID # (Public Wells):	
Well Plan Approval #:	
Address: 395 REED ST, SOMERSET WI 54025	
Approval Date (mm-dd-yyyy):	
Hicap Permanent Well #:	Common Well #:
Specific Capacity: 1.3	

1. Well Location

Town of SWISS	Fire # (if avail.): 29890
Street Address or Road Name and Number: CRANBERRY LAKE DR	
Subdivision Name:	Lot #: — Block #:
Latitude / Longitude in Decimal Degree (DD): 45.9936 °N -92.3217 °W	Method Code: SCR002

SE	NE	Section	Township	Range
or Govt Lot #		35	41 N	16 W

2. Well Type New Well

of previous unique well # — constructed in

Reason for replaced or reconstructed well ?

Construction Type: Drilled

3. Well serves 1 # of HOME

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No
Hicap Property ? No
Hicap Potable ? No

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
6	Surface	60

Upper Enlarged Drillhole		Lower Open Bedrock
No	Rotary - Mud Circulation	No
No	Rotary - Air	No
No	Rotary - Air & Foam	No
No	Drill-Through Casing Hammer	
No	Reverse Rotary	
No	Cable-tool Bit ____in. dia...	No
No	Dual Rotary	Yes
No	Temp. Outer Casing ____in. dia	
No	Removed? ____depth ft. (If NO explain on back side)	

8. Geology

Geology Codes	Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
S	S-SAND	Surface	45
Y	Y-SAND & GRAVEL	45	60

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	NEW P&E BLK WELDED 18.97 LB/FT ASTM A53 NUCOR	Surface	56
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)
3	18 SLOT JOHNSON STAINLESS STEEL V-WIRE	56	60

7. Grout or Other Sealing Material

Method: MOUNDED

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
GRANULAR BENTONITE	Surface	20	2 S

9. Static Water Level

10 ft. below ground surface

10. Pump Test

Pumping level 25 ft. below surface

Pumping at 20 GP M for 1 Hrs.

Pumping Method ? Airlift

11. Well Is

18 in. above grade

Developed ? Yes
Disinfected ? Yes
Capped ? Yes

12. Notified Owner of need to fill & seal ? No

Filled & Sealed Well(s) as needed? No

13. Constructor / Supervisory Driller	Lic #	Date Signed
TB	6901	05-04-2023
Drill Rig Operator	Lic or Reg #	Date Signed
NS	8774	05-04-2023

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
POWTS holding component (also known as holding tank)	>	25	POWTS dispersal component (soil absorption unit or mound)	>	50

Comment:

Created On: 05-01-2023 Updated On: 07-13-2023 Review Status: APPROVED