

Well Construction Report WISCONSIN UNIQUE WELL NUMBER				ABR633		Drinking Water and Groundwater - DG/5 Department of Natural Resources, Box 7921 Madison WI 53707				Form 3300-077A					
Property Owner CAROL AND KURT LANING					Phone #		1. Well Location Fire # (if avail.) 2251								
Mailing Address 21473 N. PRESTWICK DR					Town of VERONA										
City BARRINGTON			State IL		Zip Code 60010		Street Address or Road Name and Number 2251 PRAIRIE VISTA DR								
County Dane		Co. Permit # 00212		Notification # 9374816701		Completed 01-05-2024		Subdivision Name TWIN ROCK			Lot # 15				
Well Constructor (Business Name) WEBSTER BRAD & SONS DRILLING INC				Lic. # 6574		Facility ID # (Public Wells)		Latitude / Longitude in Decimal Degree (DD) 42.9776 °N -89.5984 °W			Method Code GPS008				
Address 415 N MAIN ST POYNETTE WI 53955				Well Plan Approval #		NW SW Section Township Range or Govt Lot # 19 6 N 8 E		2. Well Type New Well of previous unique well # constructed in Reason for replaced or reconstructed well ? Construction Type Drilled							
				Approval Date (mm-dd-yyyy)											
Hicap Permanent Well #		Common Well #		Specific Capacity 0											
3. Well serves 1 # of HOME Private, potable Heat Exchange ___ # of drillholes				Hicap Well ? No Hicap Property ? No Hicap Potable ? No											
4. Potential Contamination Sources - ON REVERSE SIDE															
5. Drillhole Dimensions and Construction Method															
Dia. (in.)	From (ft.)	To (ft.)	Upper Enlarged Drillhole				Lower Open Bedrock		Geology Codes			Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)	
12.3	Surface	21	<u>Yes</u> Rotary - Mud Circulation				<u>No</u>					F C	F-FILL C-CLAYEY	Surface	4
8.8	21	180	<u>No</u> Rotary - Air				<u>Yes</u>					Z	Z-CLAY & GRAVEL	4	9
6	180	244	<u>No</u> Rotary - Air & Foam				<u>No</u>		T			L H	T-TAN/BROWN L-LIMESTONE/DOLOMITE H-SHALEY	9	24
			<u>No</u> Drill-Through Casing Hammer									H L	H-HARD/FIRM L-LIMESTONE/DOLOMITE	24	208
			<u>No</u> Reverse Rotary									H N	H-HARD/FIRM N-SANDSTONE	208	235
			<u>No</u> Cable-tool Bit ___ in. dia...				<u>No</u>					H L S	H-HARD/FIRM L-LIMESTONE/DOLOMITE S-SANDY	235	244
			<u>No</u> Dual Rotary				<u>No</u>								
			<u>Yes</u> Temp. Outer Casing 10in. dia												
			<u>Yes</u> Removed? 21depth ft. (If NO explain on back side)												
6. Casing, Liner, Screen												8. Geology			
Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly			From (ft.)	To (ft.)	9. Static Water Level 77 ft. below ground surface			11. Well Is 18 in. above grade						
6	WHEATLAND A53B PE .280 WALL			Surface	180	10. Pump Test Pumping level 240 ft. below surface Pumping at 35 GP M for 1 Hrs. Pumping Method ? Airlift			Developed ? Yes Disinfected ? Yes Capped ? Yes						
Dia. (in.)	Screen type, material & slot size			From (ft.)	To (ft.)										
7. Grout or Other Sealing Material												12. Notified Owner of need to fill & seal ? No			
Method BRADENHEAD															
Kind of Sealing Material		From (ft.)	To (ft.)	# Sacks Cement		Filled & Sealed Well(s) as needed? No									
NEAT CEMENT GROUT		Surface	180	35 S											
13. Constructor / Supervisory Driller															
RW		Lic # 6890		Date Signed 01-08-2024											
Drill Rig Operator		Lic or Reg #		Date Signed											

4a. Potential Contamination SourcesIs the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
POWTS holding component (also known as holding tank)	>	100	Building Drain - Sanitary	>	40
			Sewer - Building Sanitary	>	75
POWTS dispersal component (soil absorption unit or mound)	>	120	Ditch or Culvert	>	35

Comment:

Created On: 01-05-2024

Updated On: 02-19-2024

Review Status: APPROVED