Well Construction Report
WISCONSIN UNIQUE WELL NUMBER: ABS879

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: ANDY SCHOMER	Phone #
Mailing Address: 2208 21 STREET	
City: RICE LAKE	State: WI	Zip Code: 54868
County: Barron	Co. Permit #:	Notification #: 9144787901	Completed: 07-29-2023
Well Constructor (Business Name): RUTHERFORD WELL DRLG INC	Lic. #: 6764	Facility ID # (Public Wells):
Address: 2422 27 1/2 AVE RICE LAKE WI 54868	Well Plan Approval #:	Approval Date (mm-dd-yyyy):
Hicap Permanent Well #:	Common Well #:	Specific Capacity: 1.4

1. Well Location

Town of RICE LAKE				Fire # (if avail.): 2208
Street Address or Road Name and Number: 21 ST				
Subdivision Name:		Lot #:		Block #:
Latitude / Longitude in Decimal Degree (DD): 45.5241 °N -91.7237 °W				Method Code: GPS008
SW SW or Govt Lot #:	Section: 10	Township: 35 N	Range: 11 W	

2. Well Type Replacement

of previous unique well #: constructed in:

Reason for replaced or reconstructed well ?: LOW YIELD

Construction Type: Drilled

3. Well serves 1 # of HOME

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ? No

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
4	Surface	68

Upper Enlarged Drillhole		Lower Open Bedrock
No	Rotary - Mud Circulation	No
No	Rotary - Air	No
No	Rotary - Air & Foam	No
No	Drill-Through Casing Hammer	
No	Reverse Rotary	
Yes	Cable-tool Bit 4in. dia...	No
No	Dual Rotary	No
No	Temp. Outer Casing ____in. dia	
No	Removed? ____depth ft. (If NO explain on back side)	

8. Geology

Geology Codes				Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
T	Q	S		T-TAN/BROWN Q-CAVING S-SAND	Surface	28
G	V	C		G-GRAY V-NON-CAVING C-CLAY	28	34
T	M	S		T-TAN/BROWN M-MEDIUM S-SAND	34	68

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
4	WHEATLAND STEEL ASTM53 10.79LB PER FT	Surface	64
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)
4	STAINLESS 12SLOT	64	68

7. Grout or Other Sealing Material

Method MOUNDED

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
GRANULAR BENTONITE	Surface	28	2 S

9. Static Water Level

28 ft. below ground surface

10. Pump Test

Pumping level 40 ft. below surface

Pumping at 17 GP M for 2 Hrs.

Pumping Method ? Test Pump

11. Well Is

14 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

12. Notified Owner of need to fill & seal ? Yes

Filled & Sealed Well(s) as needed? Yes

13. Constructor / Supervisory Driller	Lic #	Date Signed
TR	4719	03-16-2024
Drill Rig Operator	Lic or Reg #	Date Signed

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
POWTS holding component (also known as holding tank)	>	78	POWTS dispersal component (soil absorption unit or mound)	=	65

Comment:

Created On: 03-16-2024 Updated On: 10-15-2026 Review Status: APPROVED