

Well Construction Report WISCONSIN UNIQUE WELL NUMBER				ACM692		Drinking Water and Groundwater - DG/5 Department of Natural Resources, Box 7921 Madison WI 53707				Form 3300-077A			
Property Owner RUDEK REV FAMILY TRUST, MARK & RENCIRIS						Phone #		1. Well Location				Fire # (if avail.)	
Mailing Address 814 HORSE LAKE LANE								Town of HUNTER				11151W	
City DRESSER						State WI		Zip Code 54009				Street Address or Road Name and Number	
County Sawyer						Co. Permit #		Notification # 10226525901				Completed 04-20-2026	
Well Constructor (Business Name) BUTTERFIELD INC						Lic. # 7115		Facility ID # (Public Wells)				Latitude / Longitude in Decimal Degree (DD) 45.98133 °N -91.24668 °W	
Address 14346 W ST RD 77 HAYWARD WI 54843-9790						Well Plan Approval #		SE NW Section Township Range or Govt Lot # 6 4 40 N 7 W				Method Code GPS008	
Hicap Permanent Well #						Common Well #		Specific Capacity 1.4				2. Well Type New Well	
3. Well serves 1 # of HOME						Hicap Well ? No		of previous unique well #				constructed in	
Private, potable						Hicap Property ? No		Reason for replaced or reconstructed well ?				Construction Type Drilled	
Heat Exchange ___ # of drillholes						Hicap Potable ? No							
4. Potential Contamination Sources - ON REVERSE SIDE													
5. Drillhole Dimensions and Construction Method													
Dia. (in.)		From (ft.)		To (ft.)		Upper Enlarged Drillhole			Lower Open Bedrock				
8.75		Surface		81		Yes Rotary - Mud Circulation No No Rotary - Air No No Rotary - Air & Foam No No Drill-Through Casing Hammer No Reverse Rotary No Cable-tool Bit ___ in. dia... No No Dual Rotary No No Temp. Outer Casing ___ in. dia No Removed? ___ depth ft. (If NO explain on back side)							
8. Geology													
Geology Codes		Type, Caving/Noncaving, Color, Hardness, etc...				From (ft.)		To (ft.)					
M Y		M-MEDIUM Y-SAND & GRAVEL				Surface		50					
A Y		A-COARSE Y-SAND & GRAVEL				50		81					
6. Casing, Liner, Screen													
Dia. (in.)		Material, Weight, Specification Manufacturer & Method of Assembly				From (ft.)		To (ft.)					
5		NAS PVC SDR17 250PSI ASTM F480				Surface		75					
Dia. (in.)		Screen type, material & slot size				From (ft.)		To (ft.)					
3		10 CONTINUOUS SLOT STAINLESS STEEL				75		81					
7. Grout or Other Sealing Material													
Method TREMIE PIPE - PUMPED													
Kind of Sealing Material		From (ft.)		To (ft.)		# Sacks Cement							
TD-16 BENTONITE GROUT		Surface		72		5 S							
9. Static Water Level													
46 ft. below ground surface													
10. Pump Test													
Pumping level 53 ft. below surface													
Pumping at 10 GP M for 1 Hrs.													
Pumping Method ? Test Pump													
11. Well Is													
14 in. above grade													
Developed ? Yes													
Disinfected ? Yes													
Capped ? Yes													
12. Notified Owner of need to fill & seal ? No													
Filled & Sealed Well(s) as needed? No													
13. Constructor / Supervisory Driller													
Lic #		Date Signed											
TAB		6349		04-27-2026									
Drill Rig Operator		Lic or Reg #		Date Signed									
JSM		7418		04-27-2026									

4a. Potential Contamination SourcesIs the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
Lake, Stream, River or Pond (Including Storm Water Detention Basin)	>	200	POWTS dispersal component (soil absorption unit or mound)	=	80
			Septic or Holding, or POWTS Tank	=	50

Comment:

Created On: 04-20-2026

Updated On: 05-22-2026

Review Status: APPROVED