# Well Construction Report
## *WISCONSIN UNIQUE WELL NUMBER* CJ739

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

| | |
|---|---|
| Property Owner: JAY PIERCE | Phone #: (608)339-3510 |
| Mailing Address: 2202 PINE ST | |
| City: FRIENDSHIP | State: WI — Zip Code: 53934 |
| County: Adams | Co. Permit #: — Notification #: — Completed: 07-28-1989 |
| Well Constructor (Business Name): QUINNELLS SEPTIC AND WELL SER INC | Lic. #: 97 — Facility ID # (Public Wells): |
| Address: RT 2 FRIENDSHIP WI 53934 | Well Plan Approval #: — Approval Date (mm-dd-yyyy): |
| Hicap Permanent Well #: | Common Well #: — Specific Capacity: |

**3. Well serves** 1 # of
Private,potable
Heat Exchange____# of drillholes

Hicap Well ? No
Hicap Property ? No
Hicap Potable ?

**1. Well Location**

Town of QUINCY

Fire # (if avail.): 2202

Street Address or Road Name and Number: PINE STREET

Subdivision Name: — Lot #: — Block #:

Latitude / Longitude in Decimal Degree (DD): 43.9367 °N -89.94551 °W

Method Code: GCD005

NW NE or Govt Lot # — Section: 19 — Township: 17 N — Range: 5 E

**2. Well Type** Replacement — XY266 replaces this well of previous unique well # — constructed in

Reason for replaced or reconstructed well ?
OLD WELL SLOW

Construction Type: Jetted

**4. Potential Contamination Sources - ON REVERSE SIDE**

**5. Drillhole Dimensions and Construction Method**

| Dia. (in.) | From (ft.) | To (ft.) |
|---|---|---|
| 6 | Surface | 5 |
| 2 | 5 | 45 |

Upper Enlarged Drillhole — Lower Open Bedrock

- Rotary - Mud Circulation .....
- Rotary - Air .....
- Rotary - Air & Foam .....
- Drill-Through Casing Hammer
- Reverse Rotary
- Cable-tool Bit ____in. dia...
- Dual Rotary .....
- Temp. Outer Casing ____in. dia
  - Removed? ____depth ft. (If NO explain on back side)

**8. Geology**

| Geology Codes | Type, Caving/Noncaving, Color, Hardness, etc... | From (ft.) | To (ft.) |
|---|---|---|---|
| S | SAND | Surface | 45 |

**6. Casing, Liner, Screen**

| Dia. (in.) | Material, Weight, Specification Manufacturer & Method of Assembly | From (ft.) | To (ft.) |
|---|---|---|---|
| 2 | CYCLOPS CORP. ASTM-A-589 IPS .154 WALL 3.75#/FTT@C | Surface | 42 |
| **Dia. (in.)** | **Screen type, material & slot size** | **From (ft.)** | **To (ft.)** |
| 1.25 | 3' CLAYTON MARK 60 GAUZE | 42 | 45 |

**7. Grout or Other Sealing Material**

Method

**9. Static Water Level**

22 ft. below ground surface

**10. Pump Test**

Pumping level 22 ft. below surface
Pumping at 10 GP for 1 Hrs.
Pumping Method ?

**11. Well Is**

12 in. above grade
Developed ? Yes
Disinfected ? Yes
Capped ? Yes

**12.** Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed? Yes

| **13.** Constructor / Supervisory Driller | Lic # | Date Signed |
|---|---|---|
| DQ | | |
| **Drill Rig Operator** | **Lic or Reg #** | **Date Signed** |
| JF | | |

**4a. Potential Contamination Sources** Is the well located in floodplain ? No

| Type | Qualifier | Distance | Type | Qualifier | Distance |
|---|---|---|---|---|---|
| POWTS dispersal component (soil absorption unit or mound) | | 61 | Building Overhang | | 7 |
| | | | Septic or Holding, or POWTS Tank | | 36 |

Comment:

| Abandonment Type | Abandonment Date | Procedure | Reason |
|---|---|---|---|
| | 09/13/2016 | PORTLAND CEMENT 0-45' 1/2 BAG USED | NO WATER |

Created On: 11-28-1989 Updated On: 07-12-2021 Review Status: