Well Construction Report
WISCONSIN UNIQUE WELL NUMBER DA143

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: DAN WALLACE			Phone #: (414)766-2439
Mailing Address: W4814 SCHMIDT RD			
City: KAUKAUNA	State: WI	Zip Code: 54130	
County: Calumet	Co. Permit #:	Notification #:	Completed: 12-29-1990

1. Well Location

Town of HARRISON

Fire # (if avail.):

Street Address or Road Name and Number: W4814 SCHMIDT RD

Subdivision Name: | Lot #: | Block #:

Well Constructor (Business Name): TIPLER WELL AND PUMP	Lic. #: 55	Facility ID # (Public Wells):	Latitude / Longitude in Decimal Degree (DD): 44.2293 °N -88.2789 °W
Address: 15260 LONG ST P O BO LAKEWOOD WI 54138		Well Plan Approval #:	Method Code: GCD013
		Approval Date (mm-dd-yyyy):	SE SW or Govt Lot #: Section: 6 Township: 20 N Range: 19 E
Hicap Permanent Well #:	Common Well #:	Specific Capacity: 0.1	

2. Well Type Replacement

of previous unique well #: constructed in:

Reason for replaced or reconstructed well ?: REPLACED OLD DRY WELL

3. Well serves 1 # of

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ?

Construction Type: Drilled

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
10	Surface	125
6	125	380

Upper Enlarged Drillhole / Lower Open Bedrock

Yes Rotary - Mud Circulation .....

Yes Rotary - Air .....

Rotary - Air & Foam .....

Drill-Through Casing Hammer

Reverse Rotary

Cable-tool Bit ____in. dia...

Dual Rotary .....

Temp. Outer Casing ____in. dia

Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes	Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
C	CLAY	Surface	115
P	HARD PAN	115	125
L	LIMESTONE	125	287
N	SANDSTONE	287	292
L	LIMESTONE	292	365
N	SANDSTONE	365	380

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	ASTM A-53 GR B NEWPORT STEEL WELDED JOINT WT18.97 PER FT	Surface	126
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)

9. Static Water Level

120 ft. below ground surface

10. Pump Test

Pumping level 250 ft. below surface

Pumping at 15 GP for 4 Hrs.

Pumping Method ?

11. Well Is

12 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

7. Grout or Other Sealing Material

Method

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
DRILLING MUD	Surface	125	

12. Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed?

NOTIFIED TO ABANDON

13. Constructor / Supervisory Driller	Lic #	Date Signed
AT		01-08-1991
Drill Rig Operator	**Lic or Reg #**	**Date Signed**
AT		01-08-1991

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance
POWTS dispersal component (soil absorption unit or mound)		80

Type	Qualifier	Distance
Building Overhang		12
Septic or Holding, or POWTS Tank		70

Comment:

Created On: 04-03-1991 Updated On: 08-13-2019 Review Status: