

Well Construction Report WISCONSIN UNIQUE WELL NUMBER				DO885		Drinking Water and Groundwater - DG/5 Department of Natural Resources, Box 7921 Madison WI 53707				Form 3300-077A			
Property Owner BERTIL-EKLUND Phone # (715)962-4191						1. Well Location						Fire # (if avail.)	
Mailing Address RT 3 BOX 105E						Town of COLFAX							
City COLFAX State WI Zip Code 54730						Street Address or Road Name and Number TOWN ROAD							
County Dunn		Co. Permit #		Notification #		Completed 11-26-1990		Subdivision Name				Lot #	Block #
Well Constructor (Business Name) ROBERT WETTSTEIN				Lic. # 506	Facility ID # (Public Wells)		Latitude / Longitude in Decimal Degree (DD) °N °W				Method Code		
Address RT 2 BOX 130C EAU CLAIRE WI 54703-9802				Well Plan Approval #		NW	NE	Section 29	Township 29 N		Range 11 W		
				Approval Date (mm-dd-yyyy)		or Govt Lot #							
Hicap Permanent Well #		Common Well #		Specific Capacity		2. Well Type Reconstruction of previous unique well # constructed in 87							
3. Well serves 1 # of Private, potable Heat Exchange ___ # of drillholes						Hicap Well ? No		Reason for replaced or reconstructed well ? SEDIMENT IN WATER					
						Hicap Property ? No							
						Hicap Potable ?		Construction Type Drilled					
4. Potential Contamination Sources - ON REVERSE SIDE													
5. Drillhole Dimensions and Construction Method													
Dia. (in.)	From (ft.)	To (ft.)	Upper Enlarged Drillhole Lower Open Bedrock Rotary - Mud Circulation Rotary - Air Rotary - Air & Foam Drill-Through Casing Hammer Reverse Rotary Cable-tool Bit ___ in. dia... Dual Rotary Yes Temp. Outer Casing 10in. dia Yes Removed? ___ depth ft. (If NO explain on back side)				Geology Codes		Type, Caving/Noncaving, Color, Hardness, etc...		From (ft.)	To (ft.)	
10	Surface	40						C	CLAY		Surface	7	
6	40	205					T	N	BROWN SANDROCK		7	205	
4	205	320					G	N	LIGHT GRAY SANDROCK		205	320	
6. Casing, Liner, Screen													
Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly				From (ft.)	To (ft.)	9. Static Water Level			11. Well Is			
6	NEW STEEL THREADED @ COUPLED 20 LBS PER FT ASTMA-120 1200 PSI VALLEY STEEL PIPE NEW STEEL THREADED @ COUPLED 11 LBS PER FT A53				Surface	40	210 ft. below ground surface			15 in. above grade			
4	VENEZUELA PIPE PLACED WITH 4X6 INCH PACKER				15	205	10. Pump Test			Developed ? Yes			
Dia. (in.)	Screen type, material & slot size				From (ft.)	To (ft.)	Pumping level 210 ft. below surface Pumping at 10 GP for 3 Hrs. Pumping Method ?			Disinfected ? Yes			
										Capped ? Yes			
7. Grout or Other Sealing Material													
Method PRESSURE TREMMIE LINE													
Kind of Sealing Material		From (ft.)	To (ft.)	# Sacks Cement		12. Notified Owner of need to fill & seal ? Filled & Sealed Well(s) as needed? Yes							
CLEAR CEMENT @		Surface	40	12									
13. Constructor / Supervisory Driller						Lic #		Date Signed					
NW								12-08-1990					
Drill Rig Operator						Lic or Reg #		Date Signed					
NW								12-08-1990					

4a. Potential Contamination SourcesIs the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
POWTS dispersal component (soil absorption unit or mound)		63	Building Overhang		16
			Septic or Holding, or POWTS Tank		40

Comment:

Created On: 04-01-1991

Updated On: 04-01-1991

Review Status: