Well Construction Report
WISCONSIN UNIQUE WELL NUMBER FX802

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: PICK CONSTRUCTION, BLOUNT, KEN	Phone #: (608)966-3450
Mailing Address: W8562 DAVIS RD	
City: BROWNTOWN	State: WI Zip Code: 53522-
County: Green	Co. Permit #:	Notification #:	Completed: 10-26-1993
Well Constructor (Business Name): NIFFENEGGER, ED JR	Lic. #: 135
Address: 902 2ND ST MONROE WI 53566	
Hicap Permanent Well #:	Common Well #:	Specific Capacity: 1.3
Facility ID # (Public Wells):	Well Plan Approval #:	Approval Date (mm-dd-yyyy):

1. Well Location

Town of SYLVESTER	Fire # (if avail.): N3963
Street Address or Road Name and Number: MEYER RD	
Subdivision Name:	Lot #:	Block #:
Latitude / Longitude in Decimal Degree (DD): 42.6484 °N -89.5747 °W	Method Code: GCD013
SW NE or Govt Lot #:	Section: 17	Township: 2 N	Range: 8 E

2. Well Type New Well
of previous unique well # constructed in
Reason for replaced or reconstructed well ?: WATER FOR NEW HOME
Construction Type: Drilled

3. Well serves 1 # of
Private,potable
Heat Exchange____# of drillholes

Hicap Well ? No
Hicap Property ? No
Hicap Potable ?

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
8.75	Surface	63
6	63	120

Upper Enlarged Drillhole / Lower Open Bedrock

- Rotary - Mud Circulation .....
- Yes — Rotary - Air ..... — No
- Rotary - Air & Foam .....
- Drill-Through Casing Hammer
- Reverse Rotary
- Cable-tool Bit ____in. dia...
- Dual Rotary .....
- Temp. Outer Casing ____in. dia
  Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes				Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
-	-	I	C	TOPSOIL & CLAY	Surface	3
-	-	B	L	BROKEN LIMESTONE	3	8
Y	-	L	-	BUFF GALENA LIMESTONE	8	35
U	-	L	-	BLUE PLATTEVILLE LIMESTONE	35	65
-	-	N	-	ST PETER SANDSTONE	65	120

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	STD WT ST .280 WALL 18.97# PER FT PL END-WELDED JT USA SAWHILL A53B ASTM	Surface	63
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)

9. Static Water Level
60 ft. below ground surface

10. Pump Test
Pumping level 75 ft. below surface
Pumping at 20 GP M for 2 Hrs.
Pumping Method ?

11. Well Is
24 in. above grade
Developed ? Yes
Disinfected ? Yes
Capped ? Yes

7. Grout or Other Sealing Material
Method PRESSURE

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
NEAT CEMENT	Surface	63	15 S

12. Notified Owner of need to fill & seal ?
Filled & Sealed Well(s) as needed?

13. Constructor / Supervisory Driller	Lic #	Date Signed
RN		11-29-1993
Drill Rig Operator	Lic or Reg #	Date Signed

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance
Building Overhang		10

Comment:

Created On: 10-03-2005 Updated On: 01-21-2020 Review Status: