Well Construction Report
WISCONSIN UNIQUE WELL NUMBER IW072

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: CASH, DENNIS	Phone #: (608)465-1011
Mailing Address: W9662 LEWIS RD	
City: ARGYLE	State: WI — Zip Code: 53504
County: Green	Co. Permit #:	Notification #:	Completed: 05-09-1995
Well Constructor (Business Name): ED NIFFENEGGER JR	Lic. #: 135	Facility ID # (Public Wells):
Address: 902 2ND ST MONROE WI 53566-1103	Well Plan Approval #:	Approval Date (mm-dd-yyyy):
Hicap Permanent Well #:	Common Well #:	Specific Capacity: 15

1. Well Location

Town of JORDAN	Fire # (if avail.): W9662
Street Address or Road Name and Number: LEWIS RD	
Subdivision Name:	Lot #:	Block #:
Latitude / Longitude in Decimal Degree (DD): 42.6615 °N -89.835 °W	Method Code: GCD013

SW	SW	Section	Township	Range
or Govt Lot #		7	2 N	6 E

2. Well Type Replacement

of previous unique well #: constructed in:

Reason for replaced or reconstructed well ?: OLD WELL DID NOT MEET COD

Construction Type: Drilled

3. Well serves # of

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ?

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
8.75	Surface	41.5
6	41.5	80

Upper Enlarged Drillhole — Lower Open Bedrock

Yes — Rotary - Mud Circulation .....

Rotary - Air .....

Rotary - Air & Foam .....

Drill-Through Casing Hammer

Reverse Rotary

Cable-tool Bit ____in. dia...

Dual Rotary .....

Temp. Outer Casing ____in. dia

Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes				Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
		I		TOPSOIL	Surface	2
T		C		BROWN CLAY	2	8
	S	N	C	SOFT ST PETER SANDSTONE @ CLAY	8	19
	H	N		HARD ST PETER SANDSTONE	19	70
		N	H	ST PETER SANDSTONE W SHALE	70	76
		L		LOWER MAGNESIUM PRAIRIE DU CHIEN DOLOMIT	76	80

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	STD WT ST 280 WALL 18 97 LB PER FT PL END WELDEDJTS SAWHILL A53B ASTM	Surface	41.5
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)

9. Static Water Level

19 ft. below ground surface

10. Pump Test

Pumping level 20 ft. below surface

Pumping at 15 GP M for 2 Hrs.

Pumping Method ?

11. Well Is

12 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

7. Grout or Other Sealing Material

Method: PRESSURE TREMIE PIPE PUMPED

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
NEAT CEMENT	Surface	41.5	12 S

12. Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed? Yes

13. Constructor / Supervisory Driller	Lic #	Date Signed
RN		07-27-1995
Drill Rig Operator	Lic or Reg #	Date Signed

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance
POWTS dispersal component (soil absorption unit or mound)		65

Type	Qualifier	Distance
Building Overhang		20
Septic or Holding, or POWTS Tank		50

Comment:

Created On: 01-08-1996 Updated On: 01-21-2020 Review Status: