Well Construction Report
WISCONSIN UNIQUE WELL NUMBER KK891

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: SCHOLZ, DUANE	Phone #: (715)386-3961
Mailing Address: 963 LABARGE RD	
City: HUDSON	State: WI — Zip Code: 54016
County: St. Croix	Co. Permit #: — Notification #: — Completed: 08-09-1995
Well Constructor (Business Name): DAVID L MCCULLOUGH	Lic. #: 72 — Facility ID # (Public Wells):
Address: 20335 FOREST BLVD N, FOREST LAKE MN 55025-9764	Well Plan Approval #: — Approval Date (mm-dd-yyyy):
Hicap Permanent Well #:	Common Well #: — Specific Capacity: 0.3

1. Well Location

Town of HUDSON

Fire # (if avail.):

Street Address or Road Name and Number: 963 MCCUTCHEON RD @ LABARGE RD

Subdivision Name: — Lot #: — Block #:

Latitude / Longitude in Decimal Degree (DD): °N °W — Method Code:

SW NE or Govt Lot #: — Section: 14 — Township: 29 N — Range: 19 W

2. Well Type Replacement

of previous unique well #: FM705 — constructed in: 95

Reason for replaced or reconstructed well ?: WELL WAS PUMPING FINE SAN

Construction Type: Drilled

3. Well serves 1 # of HOME

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ?

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
8.75	Surface	255
2	255	259

Upper Enlarged Drillhole — Lower Open Bedrock

Yes — Rotary - Mud Circulation .....

Rotary - Air .....

Rotary - Air & Foam .....

Drill-Through Casing Hammer

Reverse Rotary

Cable-tool Bit ____in. dia...

Dual Rotary .....

Temp. Outer Casing ____in. dia

Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes	Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
I	TOP SOIL	Surface	2
Y	SAND GRAVEL	2	105
Z	CLAY GRAVEL	105	170
C	CLAY	170	245
S	SAND	245	256
G	GRAVEL	256	259

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
4	ASTMA53 IPSCO CAMANCHE 237 TC 11 LB	Surface	255
Dia. (in.)	**Screen type, material & slot size**	**From (ft.)**	**To (ft.)**
2	STAINLESS STEEL SCREEN	253	259

9. Static Water Level

105 ft. below ground surface

10. Pump Test

Pumping level 145 ft. below surface

Pumping at 10 GP M for 1 Hrs.

Pumping Method ?

11. Well Is

12 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

7. Grout or Other Sealing Material

Method TREMIE

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
BENTONITE GROUT	Surface	20	2 S
DRIL MUD	20	255	

12. Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed? Yes

WELL WILL BE SEALD AROUND NOV

13. Constructor / Supervisory Driller	Lic #	Date Signed
DM		08-10-1995
Drill Rig Operator	**Lic or Reg #**	**Date Signed**
DB		08-10-1995

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
POWTS dispersal component (soil absorption unit or mound)		50	Building Overhang		14
			Septic or Holding, or POWTS Tank		25

Comment:

Variance ID	Variance or Exception Type	Date	Reason
	Casing Depth Variance	07/12/1995	< REQUIRED AMOUNT OF CASING IN A SPECIAL AREA

Created On: 10-31-1995 Updated On: 10-31-1995 Review Status: