Well Construction Report
WISCONSIN UNIQUE WELL NUMBER MH119

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: MARTIN, SCOTT	Phone #: (608)372-3003
Mailing Address: 1117 MARK AVE	
City: TOMAH	State: WI — Zip Code: 54660
County: Monroe	Co. Permit #:	Notification #:	Completed: 08-24-1998
Well Constructor (Business Name): NELSONS PLBG @ ELEC INC	Lic. #: 42	Facility ID # (Public Wells):
Address: RT 3 HWY 12 @ 16 TOMAH WI 54660-9803	Well Plan Approval #:	Approval Date (mm-dd-yyyy):
Hicap Permanent Well #:	Common Well #:	Specific Capacity: 0.9

1. Well Location

Town of LAGRANGE

Fire # (if avail.):

Street Address or Road Name and Number: COUNTY ET

Subdivision Name	Lot #	Block #

Latitude / Longitude in Decimal Degree (DD): °N °W

Method Code:

SE NW or Govt Lot #	Section	Township	Range
	32	18 N	1 W

2. Well Type New Well

of previous unique well #: constructed in

Reason for replaced or reconstructed well ?: NEW HOUSE SITE

Construction Type: Drilled

3. Well serves 1 # of

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ?

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
10	Surface	152
6	152	183

Upper Enlarged Drillhole / Lower Open Bedrock

- Rotary - Mud Circulation .....
- Rotary - Air .....
- Rotary - Air & Foam .....
- Drill-Through Casing Hammer
- Reverse Rotary
- Yes — Cable-tool Bit 10in. dia...
- Dual Rotary .....
- Yes — Temp. Outer Casing 12in. dia
- Yes — Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes				Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
		S		SAND	Surface	4
I		N		WHITE SANDSTONE	4	183

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	STEEL WELD SAWHILL AK3 18 97#	Surface	152.5
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)

7. Grout or Other Sealing Material

Method GROUT PUMP

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
NEAT PORTLAND CEMENT	Surface	152	46 S

9. Static Water Level

61 ft. below ground surface

10. Pump Test

Pumping level 80 ft. below surface

Pumping at 18 GP M for 24 Hrs.

Pumping Method ?

11. Well Is

36 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

12. Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed? No

NOT YET WILL DO LATER

13. Constructor / Supervisory Driller	Lic #	Date Signed
LN		
Drill Rig Operator	**Lic or Reg #**	**Date Signed**
MN		09-01-1998

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
Building Drain - Sanitary	>	20	Foundation Drain to Clearwater	>	12
Building Overhang	>	12	Foundation Drain to Sewer	>	20
Clearwater Sump	>	25	Landfill	>	637
Downspout/Yard Hydrant	>	12	Sewer - Building Sanitary	>	20

Comment:

Variance ID	Variance or Exception Type	Date	Reason
	Landfill Variance	01/06/1998	< REQUIRED 1200' FROM LANDFILL

Created On: 01-11-1999 Updated On: 10-24-2002 Review Status: