Well Construction Report
WISCONSIN UNIQUE WELL NUMBER RN972

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: TORNMIRE, FRANCIS			Phone #: (608)536-3986
Mailing Address: 25650 JACKSON ST			
City: MUSCODA	State: WI	Zip Code: 53573	
County: Richland	Co. Permit #:	Notification #:	Completed: 07-22-2003

1. Well Location

Town of DAYTON

Fire # (if avail.):

Street Address or Road Name and Number: 25650 JACKSON ST

Subdivision Name: | Lot #: | Block #:

Well Constructor (Business Name): DONALD HERBECK	Lic. #: 229	Facility ID # (Public Wells):	Latitude / Longitude in Decimal Degree (DD): 43.32633 °N -90.52893 °W
Address: A-D WELL & PUMP SERVICE SEXTONVILLE WI 53584		Well Plan Approval #:	Method Code: GPS008
		Approval Date (mm-dd-yyyy):	SE SE / Section: 19 / Township: 10 N / Range: 1 W (or Govt Lot #)
Hicap Permanent Well #:	Common Well #:	Specific Capacity: 0.5	

2. Well Type Replacement

of previous unique well #: constructed in:

Reason for replaced or reconstructed well ?: NONCOMPLYING POINT

3. Well serves 1 # of

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ?

Construction Type: Drilled

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
6	Surface	124

Upper Enlarged Drillhole / Lower Open Bedrock

- Rotary - Mud Circulation .....
- Rotary - Air .....
- Rotary - Air & Foam .....
- Drill-Through Casing Hammer
- Reverse Rotary
- Yes — Cable-tool Bit 6in. dia... — Yes
- Dual Rotary .....
- Temp. Outer Casing ____in. dia
  Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes				Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
G	V	C	-	NONCAVING GREY CLAY	Surface	8
Y	Q	S	-	CAVING YELLOW SAND	8	42
E	-	P	-	GREEN HARDPAN	42	48
Y	-	Y	-	YELLOW SAND/GRAVEL	48	79.5
I	H	N	-	FIRM WHITE SANDSTONE	79.5	124

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	SCH40 ASTMA53B 6.625X.280 PE L21 HT CST NSF61 WHEATLAND	Surface	79.5
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)

9. Static Water Level

6 ft. below ground surface

10. Pump Test

Pumping level 27 ft. below surface

Pumping at 10 GP M for 1 Hrs.

Pumping Method ?

11. Well Is

12 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

7. Grout or Other Sealing Material

Method MOUNDED

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
#8 MESH BENTONITE	Surface		2 S

12. Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed? Yes

CONTRACTOR SEALED POINT

13. Constructor / Supervisory Driller	Lic #	Date Signed
DAH		08-04-2003
Drill Rig Operator	**Lic or Reg #**	**Date Signed**

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
Clearwater Sump	>	8	Downspout/Yard Hydrant	>	8
Collector Sewer - San or Storm	>	25	Landfill	>	1200
			Sewer - Building Sanitary	>	25

Comment:

Created On: 08-21-2003 Updated On: 08-25-2022 Review Status: