Well Construction Report
WISCONSIN UNIQUE WELL NUMBER TX985

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: EUNICE STUECK EST, STUECK, MAR	Phone #: (920)323-9230
Mailing Address: 3401 HWY VV	
City: TWO RIVERS	State: WI Zip Code: 54241
County: Manitowoc	Co. Permit #:
Notification #: 25253070	Completed: 03-16-2007
Well Constructor (Business Name): RETZLAFF WELL DRILLING INC	Lic. #: 86
Facility ID # (Public Wells):	
Address: PO BOX 81 LUXEMBURG WI 54217-0081	
Well Plan Approval #:	
Approval Date (mm-dd-yyyy):	
Hicap Permanent Well #:	Common Well #:
Specific Capacity: 0.3	

1. Well Location

Town of TWO RIVERS

Fire # (if avail.):

Street Address or Road Name and Number: 3401 HWY VV

Subdivision Name	Lot #	Block #

Latitude / Longitude in Decimal Degree (DD)	Method Code
44.1748 °N -87.5967 °W	GCD013

NW SW or Govt Lot #	Section	Township	Range
	26	20 N	24 E

2. Well Type Replacement

of previous unique well #: constructed in:

Reason for replaced or reconstructed well ?: SAND POINT

Construction Type: Drilled

3. Well serves 1 # of

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ?

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
8.75	Surface	83
6	83	250

Upper Enlarged Drillhole / Lower Open Bedrock

- Yes — Rotary - Mud Circulation ..... — No
- Rotary - Air .....
- No — Rotary - Air & Foam ..... — Yes
- Drill-Through Casing Hammer
- Reverse Rotary
- Cable-tool Bit ____in. dia...
- Dual Rotary .....
- Temp. Outer Casing ____in. dia
- Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes	Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
- - S -	SAND	Surface	75
- - G -	GRAVEL	75	83
- - L -	LIMESTONE	83	250

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	WHEATLAND STEEL PE 18.97 PER FT BLACK NEW ASTM A53B MADE IN USA	Surface	83
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)

9. Static Water Level

5 ft. below ground surface

10. Pump Test

Pumping level 65 ft. below surface

Pumping at 20 GP M for 1 Hrs.

Pumping Method ?

11. Well Is

18 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

7. Grout or Other Sealing Material

Method

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
CLAY SLURRY	Surface	83	

12. Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed? Yes

13. Constructor / Supervisory Driller	Lic #	Date Signed
JR		03-16-2007
Drill Rig Operator	**Lic or Reg #**	**Date Signed**
KG		

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
POWTS dispersal component (soil absorption unit or mound)		60	Clearwater Sump		25
Building Overhang		4	Septic or Holding, or POWTS Tank		25

Comment:

Created On: 04-17-2007 Updated On: 10-15-2019 Review Status: