

Well Construction Report WISCONSIN UNIQUE WELL NUMBER				UT827		Drinking Water and Groundwater - DG/5 Department of Natural Resources, Box 7921 Madison WI 53707				Form 3300-077A									
Property Owner HEILMAN, DAVID						Phone # (920)901-7436		1. Well Location				Fire # (if avail.)							
Mailing Address 4132 KUSS RD						Town of GIBSON													
City TWO RIVERS						State WI		Zip Code 54241											
County Manitowoc		Co. Permit #		Notification # 31556090		Completed 11-25-2008		Subdivision Name				Lot # Block #							
Well Constructor (Business Name) KENNETH GREGORICH				Lic. # 6985		Facility ID # (Public Wells)				Latitude / Longitude in Decimal Degree (DD) 44.25593 °N -87.70343 °W				Method Code GPS008					
Address 5861 MARY'S RD NEW FRANKEN WI 54229				Well Plan Approval #		SW SW Section Township Range or Govt Lot # 27 21 N 23 E		2. Well Type New Well of previous unique well # constructed in Reason for replaced or reconstructed well ? Construction Type Drilled											
				Approval Date (mm-dd-yyyy)															
Hicap Permanent Well #		Common Well #		Specific Capacity 0.6															
3. Well serves 1 # of Private, potable Heat Exchange ___ # of drillholes				Hicap Well ? No Hicap Property ? No Hicap Potable ?															
4. Potential Contamination Sources - ON REVERSE SIDE																			
5. Drillhole Dimensions and Construction Method														8. Geology					
Dia. (in.)		From (ft.)		To (ft.)		Upper Enlarged Drillhole				Lower Open Bedrock		Geology Codes		Type, Caving/Noncaving, Color, Hardness, etc...		From (ft.)		To (ft.)	
8.75		Surface		61		Rotary - Mud Circulation <u>Yes</u> Rotary - Air <u>No</u> <u>No</u> Rotary - Air & Foam <u>Yes</u> Drill-Through Casing Hammer Reverse Rotary Cable-tool Bit ___ in. dia... Dual Rotary Temp. Outer Casing ___ in. dia Removed? ___ depth ft. (If NO explain on back side)				- - C G CLAY & STONES - - L - LIMESTONE		Surface 4 4 143							
6. Casing, Liner, Screen						9. Static Water Level				11. Well Is									
Dia. (in.)		Material, Weight, Specification Manufacturer & Method of Assembly				From (ft.)		To (ft.)		47 ft. below ground surface				24 in. above grade					
6		WHEATLAND STEEL P.E. 18.97 PER FT. BLACK NEW ASTM-A-53-B MADE IN USA				Surface		61		10. Pump Test Pumping level 80 ft. below surface Pumping at 20 GP M for 1 Hrs. Pumping Method ?				Developed ? Yes Disinfected ? Yes Capped ? Yes					
Dia. (in.)		Screen type, material & slot size				From (ft.)		To (ft.)											
7. Grout or Other Sealing Material Method PRESSURE PUMPED										12. Notified Owner of need to fill & seal ? Filled & Sealed Well(s) as needed? Yes									
Kind of Sealing Material		From (ft.)		To (ft.)		# Sacks Cement													
PORTLAND CEMENT TRIMIE PILE		Surface		61		13 S													
						13. Constructor / Supervisory Driller				Lic #		Date Signed							
						KG						11-25-2008							
						Drill Rig Operator				Lic or Reg #		Date Signed							

4a. Potential Contamination SourcesIs the well located in floodplain ? No

Type	Qualifier	Distance	Type	Qualifier	Distance
Building Overhang		10	Septic or Holding, or POWTS Tank		80

Comment:

Created On: 01-20-2009

Updated On: 10-15-2019

Review Status: