Well Construction Report
WISCONSIN UNIQUE WELL NUMBER VC046

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707
Form 3300-077A

Property Owner: LAURENT, KEVIN	Phone #: (920)595-0063
Mailing Address: W2737 AUTUMN CT	
City: SEYMOUR	State: WI — Zip Code: 54165
County: Outagamie	Co. Permit #:
Notification #: 48565835	Completed: 07-17-2013
Well Constructor (Business Name): THOMAS A SCHMIDT	Lic. #: 3966
Facility ID # (Public Wells):	
Address: SCHMIDTS WELL DRILLING, BLACK CREEK WI 54106-9803	
Well Plan Approval #:	
Approval Date (mm-dd-yyyy):	
Hicap Permanent Well #:	Common Well #:
Specific Capacity: 0.2	

1. Well Location

Town of OSBORN				Fire # (if avail.): W2737
Street Address or Road Name and Number: W2737 AUTUMN CT				
Subdivision Name:			Lot #:	Block #:
Latitude / Longitude in Decimal Degree (DD): 44.47842 °N -88.32273 °W				Method Code: GPS008
NE / SW / or Govt Lot #:	Section: 9	Township: 23 N	Range: 18 E	

2. Well Type New Well
of previous unique well # constructed in
Reason for replaced or reconstructed well ?
Construction Type: Drilled

3. Well serves 1 # of
Private,potable
Heat Exchange____# of drillholes
Hicap Well ? No
Hicap Property ? No
Hicap Potable ?

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
8.75	Surface	270
6	270	300

Upper Enlarged Drillhole: Yes
Lower Open Bedrock: Yes

- Rotary - Mud Circulation .....
- Rotary - Air .....
- Rotary - Air & Foam .....
- Drill-Through Casing Hammer
- Reverse Rotary
- Cable-tool Bit ____in. dia...
- Dual Rotary .....
- Temp. Outer Casing ____in. dia
  Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes				Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
R	S	C	G	CLAY RED & STONES	Surface	58
T	M	N	-	BROWN SANDSTONE	58	120
R	M	N	-	RED SANDSTONE	120	240
T	M	N	-	LIGHT BROWN SANDSTONE	240	270
K	M	N	-	BLACK SANDSTONE	270	300

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	NEW BLACK STEEL WHEATLAND TEXAS PIPE 18.97 # ASTM A53 WELDED-PD DRIVE SHOE	Surface	270
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)

9. Static Water Level
100 ft. below ground surface

10. Pump Test
Pumping level 160 ft. below surface
Pumping at 10 GP M for 0.5 Hrs.
Pumping Method ?

11. Well Is
18 in. above grade
Developed ? Yes
Disinfected ? Yes
Capped ? Yes

7. Grout or Other Sealing Material
Method BRADENHEAD

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
NEAT GROUT CEMENT	Surface	270	65 S

12. Notified Owner of need to fill & seal ?
Filled & Sealed Well(s) as needed? Yes

13. Constructor / Supervisory Driller	Lic #	Date Signed
TAS		08-14-2013
Drill Rig Operator	**Lic or Reg #**	**Date Signed**

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance
POWTS dispersal component (soil absorption unit or mound)		180

Type	Qualifier	Distance
Building Overhang		217
Septic or Holding, or POWTS Tank		147

Comment:

Created On: 11-04-2013 Updated On: 02-09-2023 Review Status: