Well Construction Report
WISCONSIN UNIQUE WELL NUMBER YW898

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: HERMAN, RICHARD			Phone #: (608)515-0964
Mailing Address: 159 E MAIN ST			
City: MARSHALL	State: WI	Zip Code: 53559	
County: Forest	Co. Permit #:	Notification #: 7093124401	Completed: 03-03-2018

1. Well Location

Town of CRANDON

Fire # (if avail.): 9894

Street Address or Road Name and Number: 9894 HARRIS LN

Subdivision Name: | Lot #: | Block #:

Well Constructor (Business Name): DOUGLAS J MORIN	Lic. #: 6311	Facility ID # (Public Wells):	
Address: MORIN AND JOHNSON WELL DRLG & PUMP NIAGARA WI 54151		Well Plan Approval #:	
		Approval Date (mm-dd-yyyy):	
Hicap Permanent Well #:	Common Well #:	Specific Capacity: 0.1	

Latitude / Longitude in Decimal Degree (DD): 45.5986 °N -88.932 °W

Method Code: GPS008

NW / SE	Section	Township	Range
or Govt Lot #	13	36 N	12 E

2. Well Type Replacement

of previous unique well # | constructed in

Reason for replaced or reconstructed well ?: POINT WAS INADEQUATE

Construction Type: Drilled

3. Well serves 1 # of

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ?

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
6	Surface	102

Upper Enlarged Drillhole / Lower Open Bedrock

- Rotary - Mud Circulation .....
- Rotary - Air .....
- Rotary - Air & Foam .....
- Drill-Through Casing Hammer
- Reverse Rotary
- Cable-tool Bit ____in. dia...
- Dual Rotary .....
- Temp. Outer Casing ____in. dia
  - Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes				Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
-	-	S	-	SAND	Surface	18
-	-	Z	M	CLAYISH GRAVEL/SILT	18	51
-	B	Q	-	BROKEN GRANITE	51	64
-	H	Q	-	FIRM GRANITE	64	102

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
6	ASTM A53B IPSCO .289 W18.97 LB/FT WELDED	Surface	51
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)

9. Static Water Level

31 ft. below ground surface

10. Pump Test

Pumping level 80 ft. below surface

Pumping at 6 GP M for 2 Hrs.

Pumping Method ?

11. Well Is

16 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

7. Grout or Other Sealing Material

Method MOUNDED BENTONITE

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
GRANULAR BENTONITE	Surface	51	3 S

12. Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed? No

STILL IN USE

13. Constructor / Supervisory Driller	Lic #	Date Signed
DJM		03-08-2018
Drill Rig Operator	Lic or Reg #	Date Signed

4a. Potential Contamination Sources Is the well located in floodplain ?

Type	Qualifier	Distance	Type	Qualifier	Distance
POWTS dispersal component (soil absorption unit or mound)	>	60	Sewer - Building Sanitary	>	80
Building Drain - Sanitary	>	40	Septic or Holding, or POWTS Tank	>	50

Comment:

Created On: 04-17-2018 Updated On: 06-16-2020 Review Status: