Well Construction Report
WISCONSIN UNIQUE WELL NUMBER YX803

Drinking Water and Groundwater - DG/5
Department of Natural Resources, Box 7921
Madison WI 53707

Form 3300-077A

Property Owner: IRRGAY, JIM	Phone #
Mailing Address: 7538 RUBY DR	
City: TREGO	State: WI Zip Code: 54888
County: Washburn	Co. Permit #:
Notification #: 6997057501	Completed: 11-09-2017
Well Constructor (Business Name): DAVID M BEECROFT	Lic. #: 6242
Facility ID # (Public Wells):	
Well Plan Approval #:	
Address: W8760 CTY J SHELL LAKE WI 54871	Approval Date (mm-dd-yyyy):
Hicap Permanent Well #:	Common Well #:
Specific Capacity: 1.5	

1. Well Location

Town of TREGO	Fire # (if avail.): 7538
Street Address or Road Name and Number: RUBY DR	
Subdivision Name:	Lot #: Block #:
Latitude / Longitude in Decimal Degree (DD): 45.9078 °N -91.8339 °W	Method Code: GCD013

SW	NE	Section	Township	Range
or Govt Lot #		34	40 N	12 W

2. Well Type New Well

of previous unique well #: constructed in

Reason for replaced or reconstructed well ?:

Construction Type: Drilled

3. Well serves 1 # of CABIN

Private,potable

Heat Exchange____# of drillholes

Hicap Well ? No

Hicap Property ? No

Hicap Potable ?

4. Potential Contamination Sources - ON REVERSE SIDE

5. Drillhole Dimensions and Construction Method

Dia. (in.)	From (ft.)	To (ft.)
8	Surface	55

Upper Enlarged Drillhole / Lower Open Bedrock

- Rotary - Mud Circulation .....
- Rotary - Air .....
- Rotary - Air & Foam .....
- Drill-Through Casing Hammer
- Reverse Rotary
- Cable-tool Bit ____in. dia...
- Dual Rotary .....
- Temp. Outer Casing ____in. dia
  - Removed? ____depth ft. (If NO explain on back side)

8. Geology

Geology Codes				Type, Caving/Noncaving, Color, Hardness, etc...	From (ft.)	To (ft.)
-	-	Y	-	SAND & GRAVEL	Surface	55

6. Casing, Liner, Screen

Dia. (in.)	Material, Weight, Specification Manufacturer & Method of Assembly	From (ft.)	To (ft.)
4	PVC CRESTLINE SOLVENT SDR21	Surface	51
Dia. (in.)	Screen type, material & slot size	From (ft.)	To (ft.)
4	STAINLESS ATTACHED 20 SLOT	51	55

7. Grout or Other Sealing Material

Method TREMIE PRESSURE

Kind of Sealing Material	From (ft.)	To (ft.)	# Sacks Cement
BENTONITE	Surface	48	8 S
RED FLINT #30	48	55	6 S

9. Static Water Level

20 ft. below ground surface

10. Pump Test

Pumping level 30 ft. below surface

Pumping at 15 GP M for 1 Hrs.

Pumping Method ?

11. Well Is

18 in. above grade

Developed ? Yes

Disinfected ? Yes

Capped ? Yes

12. Notified Owner of need to fill & seal ?

Filled & Sealed Well(s) as needed?

13. Constructor / Supervisory Driller	Lic #	Date Signed
DMB		11-09-2017
Drill Rig Operator	Lic or Reg #	Date Signed

4a. Potential Contamination Sources Is the well located in floodplain ? No

Type	Qualifier	Distance
Septic or Holding, or POWTS Tank		60

Comment:

Created On: 12-22-2017 Updated On: 06-26-2020 Review Status: